

**IDAHO STATE POLICE FORENSIC SERVICES  
LATENT PRINT SECTION  
ANALYTICAL METHOD  
HISTORY PAGE**

The original version of the Latent Fingerprint Section SOP Manual is dated August 30, 2000.

Revision 1, revised from revision 0 was effective July 13, 2001.

Revision 2, revised from revision 1 was effective December 27, 2001.

Revision 3, the entire manual was reviewed and revised from revision 2. Revision 3 is effective January 12, 2007.

Revision 4: Section 11 “Digital Imaging Procedure” was reviewed and revised from revision 3. Revision 4 is effective May 15, 2007.

Revision 5: Section 5.6 “Retained Evidence” clarified retained latent evidence procedure 5.6.1, added section 5.6.1.1 addresses the issue of retained evidence from crime scenes, Appendix C “Latent Section Abbreviations” removed from Analytical Method. Revision 5 is effective September 12, 2007.

Revision 6: Section 10.1 “Amido Black” 10.1.5 Procedure, removed the presumptive blood testing requirement. (renumbered accordingly) Section 10.5 “Ninhydrin” 10.5.6.1 Procedure, removed the presumptive blood testing requirement. (renumbered accordingly) revision 6 is effective July 22, 2008.

Revision 7: Section 8.1.1 Remove wording on ALS use. 11.4 Modify documentation for new equipment. 12.4.3.2.1 and 12.4.3.2.2 and “reasonable”. 14.2.3.4 add “and date verified”. 14.3 update suggested wording for case reports. Appendix A change checks of balances to annually from monthly, addition of CA chamber to equipment list. Remove Appendix B “Latent Section Consumables”. revision 7 is effective March 24, 2009.

Revision 8: Sections 1.5.3, 8.1.5.2, 9.2.6, 10.2.8, 11.4.3, 11.5.2, 12.4.4.3, 13, 14.3.1 Revision 8 is effective December 01, 2009.

Revision 9: Changes made to Sections; 5.6, 5.6.1, 5.6.2, and 7.10.2, Revision 9 is effective 01/28/2011.

Revision 10: Changes made to Sections; 3, 7, 7.2.2, 10.2.8.5, 12.4.2.4, 13.14, 13.6.3.2, 14.2.3.4, 14.2.3.4.2, 14.2.4.1.2, 14.3.1, 14.6, Appendix A. Balance, Revision 10 is effective 06/02/2011.

Revision 11: Changes made to Sections; 3, 5.2, 5.3.1, 5.3.2, 5.3.2.1, 6.1.3, 7.2.1, 7.2.2, 10.5, 11.3.2.2, 11.3.3.2.2, 11.4.2, 11.4.3, 11.4.4, 11.4.5, 11.4.6, 11.4.7, 11.4.8.5.2, 11.4.9, 11.5.1, 11.5.2, 11.5.3, 11.5.4, 11.5.5, 11.6.1, 11.6.3, 11.6.4.2, 11.6.5, 11.8.3.2, 11.8.3.4, 12.2, 12.4.1.1, 12.4.1.1.1, 12.4.1.2, 12.4.1.2.1, 12.4.1.7, 12.4.1.8, 12.4.1.9, 12.4.1.2.2, 12.4.1.2.3, 12.4.1.2.1.4, 12.4.1.2.5, 12.4.1.3, 12.4.2, 12.4.2.1, 12.4.2.5.2, 12.4.3.1, 12.4.3.2, 12.4.3.2.1, 12.4.3.3, 12.4.3.3.2, 12.4.4, 12.4.5, 12.4.5.1, 12.4.5.2, 12.4.6, 12.4.6.1, 12.4.6.2, 13.3, 13.4.5, 14.2.3, 14.2.3.1, 14.2.3.2, 14.2.3.3, 14.2.3.3.1, 14.2.3.4, 14.2.3.5, 14.2.3.5.1, 14.2.3.5.2, 14.2.3.5.3, 14.2.3.5.4, 14.2.3.5.5, 14.2.4.1.2, 14.4 Revision 11 is effective 02/22/2012.

**Revision 12:** Changes made to Sections; 2, 3 Definitions, 5.3.2, 6.3.3.3 deleted, 7.1.1, 7.1.2, 7.3, 7.12.2 #4, 8.1.5.1, 8.1.5.2, 8.1.5.5, 8.1.5.6 deleted, 8.1.6.1, 8.1.6.2, 8.1.6.4, 8.1.9, 9.1 Flame Method deleted, 10.5 1,2 Indanedione added, 10.6.8.1, 10.9 RAM added, 10.12 Traditional Film Development (Black & White) deleted, 11.4.8.4, 11.5.5, 11.6.4.1, 11.6.4.2, 11.6.5, 11.6.6, 13.3, 13.4, 13.4.3, 13.4.3.1, 13.4.3.2 deleted, 13.5, 13.6.2, 13.6.3.1 deleted, 13.6.3.2 deleted, 13.6.3.3 deleted, 13.6.4 deleted, 13.11.2, 13.15.1, 13.15.2, 14.2.1, 14.2.4.1.1, 14.2.4.1.2, 14.2.3, 14.2.3.1, 14.2.3.3, 14.3.1, 14.4, 14.6.2, added 14.7, 14.8 Revision 12 is effective 06/17/2013.

**Revision 13:** Changes made to Sections; 1.4, 3 Definitions, 5.4.2, 5.6.2, 7.9 6.2, 8.1.2.2, 8.1.5.1, 8.1.5.5, 9.1.2.1, 10.1.8.3, 10.2.2.1, 10.2.3, 10.2.4, 10.2.5.6.1, 10.2.6.1, 10.2.9.4, 10.2.11.1, 1, 10.3.7.4, 10.3.8.3, 10.5.1, 10.5.2.1, 10.5.2.2, 10.5.8.1, 10.5.8.1.5, 10.6.2.1, 10.6.2.2, 10.7.2.2, 10.7.2.3, 10.7.6.3, 10.10.1, 10.2.6.5, 10.10.6.3, 10.9.1, 10.9.7.3, 10.10.8.2, 11.1, 11.3.1.4, 11.3.1.5, 11.3.2, 11.4.2, 11.4.2.1, 11.4.8.4.2, 11.8.3.2 deleted, 11.8.4, 12.4.1.2.1, 12.4.1.3, 12.4.1.10 added, 12.4.2.4, 12.4.8.1, 13.2.3, 13.4, 13.4.5 deleted, 13.5.2, 13.6, 13.9, 13.11.1, 13.12, 13.12.1, 13.12.2, 13.12.3, 13.12.4, 13.13.1 deleted, 13.18.1, 14.2.1, 14.2.2.2.1, 14.2.3, 14.2.3.2, 14.2.3.3, 14.2.3.3.1, 14.2.3.5.1, 14.2.3.5.2, 14.2.3.5.3, 14.2.3.5.4, 14.2.4.1.1, 14.2.4.1.2, 14.3.1 deleted, 14.4 deleted, 14.6.3, 14.6.6 deleted, 14.7.2, 14.8 deleted: Revision 13 is effective 04/11/2014

**Revision 14:** Changes were made to Sections 1, 2, 3, & 4 Added Sections 5- Safety, 6- Ordering of Chemicals/Supplies & Preparation of Reagents; 7- Evidence Preparation and Handling Procedures, 8- Validation, 9- Equipment, Calibration, Repair, and Maintenance. Renumbered all remaining sections; with content changes to sections 10 through 18. Revision 14 is effective 1/20/2016.

**IDAHO STATE POLICE FORENSIC SERVICES  
LATENT SECTION ANALYTICAL METHOD**

**TABLE OF CONTENTS**

<b>i</b>	<b>HISTORY PAGE AND APPROVAL</b>
<b>ii</b>	<b>TABLE OF CONTENTS</b>
<b>1</b>	<b>BACKGROUND/SCOPE</b>
<b>2</b>	<b>GENERAL REFERENCES</b>
<b>3</b>	<b>DEFINITIONS</b>
<b>4</b>	<b>RESPONSIBILITIES</b>
<b>5</b>	<b>SAFETY</b>
<b>6</b>	<b>ORDERING OF CHEMICALS/SUPPLIES &amp; PREPARATION OF REAGENTS</b>
<b>7</b>	<b>EVIDENCE PREPARATION AND HANDLING PROCEDURES</b>
<b>8</b>	<b>VALIDATION</b>
<b>9</b>	<b>EQUIPMENT, CALIBRATION, MAINTENANCE AND REPAIR</b>
<b>10</b>	<b>GENERAL LATENT PROCESSING</b>
<b>11</b>	<b>QUICK REFERENCE SEQUENTIAL PROCESSING GUIDE</b>
<b>12</b>	<b>LIGHT BASED METHODS</b>
12.1	Alternate Light Source (ALS)
12.2	Krimesite Imager (KSI)
<b>13</b>	<b>PHYSICAL METHODS</b>
13.1	Iodine Fuming
13.2	Lifting Methods
13.3	Powder Detection Methods
13.4	Small Particle Reagent (SPR)
13.5	Sticky-Side Powder
13.6	Taking Known Exemplars (Reference Standards)
<b>14</b>	<b>CHEMICAL METHODS</b>
14.1	Amido Black

- 14.2 Cyanoacrylate Ester
- 14.3 1, 8 Diazfluoren-9-ONE (DFO)
- 14.4 Gentian Violet
- 14.5 1,2 Indanedione
- 14.6 Leucocrystal Violet (LCV)
- 14.7 Ninhydrin
- 14.8 Physical Developer (PD)
- 14.9 RAM
- 14.10 Rhodamine 6G
- 14.11 Sudan Black

**15 DIGITAL IMAGING PROCEDURE**

**16 FRICTION RIDGE EXAMINATION METHODOLOGY**

**17 ABIS**

**18 CASE WORK DOCUMENTATION AND REPORT WRITING**

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016

# 1 BACKGROUND/SCOPE

- 1.1 The discipline of Latent Print Analysis is the process of determining whether a particular area of friction ridge skin produced a particular latent print.
- 1.2 It is a discipline based on the development and comparison of multiple levels of detail such as pattern type, ridge characteristics (also known as minutiae), ridge shapes, etc. between a latent print and a known print.
- 1.3 When there is agreement between the details in a latent or questioned print and those in the known print, without any unexplainable dissimilarities, an identification can be declared.
- 1.4 The principles behind latent print evidence are: Friction Ridge Skin (FRS) is permanent, in that it does not change naturally throughout one's life and Friction Ridge Skin is unique and individual, in that no two areas of FRS have been found to possess identical ridge characteristics.
- 1.5 It is the combination of uniqueness and persistency that allow for individualization.
- 1.6 This Analytical Method defines both technical procedures for processing the majority of evidence encountered by the Latent Print Discipline and comparison methodology.
  - 1.6.1 These methods will describe procedures and techniques that are routinely used in the examination of evidence.
  - 1.6.2 These methods cannot be expected to address each and every situation or type of evidence encountered.
  - 1.6.3 The individual analyst must exercise sound judgment in selecting the methods at their discretion which will best suit the requirements of the evidence submitted in a specific case; therefore, the procedures are designed to accommodate the majority of evidence encountered.

## 2 GENERAL REFERENCES

Idaho State Police Forensic Services – Quality Manual Section 2.0 NORMATIVE REFERENCES

The Scientific Working Group on Friction Ridge Analysis, Study and Technology (SWGFAST) - *SWGFAST documents are published* on the SWGFAST website <http://www.swgfast.org/>

\*Additional references are listed within individual procedures.

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016

### 3 DEFINITIONS

**ABIS** – Automated Biometric Identification System; the generic term for the new generation of fingerprint matching, storage, and retrieval systems.

**ACE-V** - Comparison methodology consisting of Analysis, Comparison, Evaluation, and Verification.

**AFIS** - Automated Fingerprint Identification System; the generic term for a fingerprint matching, storage, and retrieval system; the predecessor to ABIS.

**ABIS Databases** - These are various databases available to ISP Forensic Services for searching latents. These databases include Idaho, WIN, WA, CAL-DOJ, NGI, as well as other local databases.

**ALTERNATE LIGHT SOURCE (ALS)/FORENSIC LIGHT SOURCE** - Any light source, other than a laser, used to excite luminescence of latent prints, body fluids, etc.

**ANALYSIS** - The methodical examination of friction skin impressions, separation into parts so as to determine the nature of the whole. First step of the ACE-V method.

**ANATOMICAL SOURCE** - An area of friction ridge skin from an individual from which an impression originated.

**ARCH – PLAIN** - A fingerprint pattern in which the ridges enter on one side of the impression, and flow, or tend to flow, out the other with a rise or wave in the center.

**ARCH – TENTED** - A type of fingerprint pattern that possesses either an angle, an up-thrust, or two of the three basic characteristics of the loop.

**ARTIFACT**- Any distortion or alteration not in the original friction ridge impression, produced by an external agent or action; any information not present in the original object/image, inadvertently introduced by image capture, processing, compression, transmission, display, or printing.

**BIAS**- See cognitive bias, confirmation bias, and contextual bias.

**BIFURCATION** - The point at which one friction ridge divides into two friction ridges.

**BLIND VERIFICATION** - The independent examination of one or more friction ridge impressions at any stage of the ACE process by another competent examiner who is provided with no, or limited, contextual information, and has no expectation or knowledge of the determinations or conclusions of the original examiner.

**CANDIDATE** - An individual's fingerprint record under consideration for comparison to the latent fingerprint.

**CATEGORY 1 IMAGE** – Images used to demonstrate what the photographer or recording device witnessed. They are not analyzed by subject matter experts and may include general crime scene, documentation of items of evidence in the laboratory, etc.

**CATEGORY 2 IMAGE** – Images that subject matter experts use for scientific analysis. These can include, but are not limited to, latent prints or other impression evidence, patterned evidence, or questioned documents.

**CHARACTERISTICS** - Distinctive details of the friction ridges, including Level 1, 2, 3 details (also known as features).

**CLARITY** - Visual quality of a friction ridge impression.

**CLASS CHARACTERISTICS** - Characteristics used to put things into groups or classes (e.g., arches, loops, and whorls).

**CLASSIFICATION** - Alpha/numeric formula of finger and palm print patterns used as a guide for filing and searching.

**COGNITIVE BIAS** - The effect of perceptual or mental processes on the reliability and validity of one's observations and conclusions.

**COMPARISON** - The second step of the ACE-V method. The observation of two or more impressions to determine the existence of discrepancies, dissimilarities, or similarities.

**COMPETENCY** - Possessing and demonstrating the requisite knowledge, skills, and abilities to successfully perform a specific task.

**COMPLEX EXAMINATIONS** - The encountering of uncommon circumstances during an examination (e.g. the existence of high distortion, low quality or quantity, simultaneous impressions, or conflicts among examiners).

**CONCLUSION** - Determination made during the evaluation stage of ACE-V, including individualization, inconclusive, exclusion.

**CONFIRMATION BIAS** - The tendency to search for data or interpret information in a manner that supports one's preconceptions.

**CONFLICT** – A difference of conclusions that becomes apparent during, or at the end of, an examination.

**CONSULTATION** - a significant interaction (i.e. guidance or exchange of information) between examiners regarding one or more impressions in question that ultimately affects the analyst's opinion about the latent print.



**CONSENSUS DETERMINATION OR CONCLUSION** - Agreement reflecting the collective judgment of a group of examiners trained to competency when making determinations or conclusions with respect to one or more impressions.

**CONTEXTUAL BIAS** - The effect of information or outside influences on the evaluation and interpretation of data.

**CORE** - The approximate center of a pattern; a specific formation within a fingerprint pattern, defined by classification systems such as Henry.

**CREASE** - A line or linear depression; grooves at the joints of the phalanges, at the junction of the digits and across the palmar and plantar surfaces that accommodate flexion.

**DELTA** - That point on a ridge at or nearest to the point of divergence of two type lines, and located at or directly in front of the point of divergence.

**DERMIS** - The layer of skin beneath the epidermis.

**DESTINATION** – The ABIS database (i.e. Idaho, WID, NGI) or database section searched (e.g. Rolled, Slapped, Both, Palm, or Writer's Palm).

**DEVIATION** – A change in ridge path; an alteration or departure from a documented policy or method.

**DISCREPANCY** - The presence of friction ridge detail in one impression that does not exist in the corresponding area of another impression. See also Dissimilarity.

**DISSIMILARITY** – A difference in appearance between two friction ridge impressions. See also Discrepancy.

**DISSOCIATED RIDGES** – Disrupted, rather than continuous friction ridges; an area of friction ridge units that did not form into friction ridges, generally due to a genetic abnormality.

**DISTORTION** - Variances in the reproduction of friction skin caused by pressure, movement, force, contact surface, etc. Distortion is not a discrepancy and is not a basis for exclusion.

**DOT** - An isolated ridge unit whose length approximates its width in size.

**EDGEOSCOPY**- Study of the morphological characteristics of friction ridges; contour or shape of the edges of friction ridges.

**ELASTICITY** -The ability of skin to recover from stretching, compression, or distortion.

**ELIMINATION PRINTS** - Exemplars of friction ridge skin detail of persons known to have had access to the item examined for latent prints.

**ENDING RIDGE** - A single friction ridge that terminates within the friction ridge structure.

**EPIDERMIS** - The outer layer of the skin.

**ERRONEOUS EXCLUSION** - The incorrect determination that two areas of friction ridge impressions did not originate from the same source.

**ERRONEOUS INDIVIDUALIZATION/IDENTIFICATION** - The incorrect determination that two areas of friction ridge impressions originated from the same source.

**EVALUATION** - The third step of the ACE-V method wherein an examiner assesses the value of the details observed during the analysis and the comparison steps and reaches a conclusion.

**EXCLUSION** - The determination that there is sufficient quality and quantity of detail in disagreement to conclude that two areas of friction ridge impressions did not originate from the same source.

**EXEMPLARS**- The prints of an individual, associated with a known or claimed identity, and deliberately recorded electronically, by ink, or by another medium (also known as known prints).

**FALSE NEGATIVE RATE** - The proportion of the comparisons between mated prints that result in an erroneous exclusion conclusion.

**FALSE POSITIVE RATE** - The proportion of the comparisons between non-mated prints that result in an erroneous individualization conclusion.

**FEATURES** – Distinctive details of the friction ridges, including Level 1, 2, and 3 details.

**FINGERPRINT** - An impression of the friction ridges of all or any part of the finger.

**FOCAL POINTS** - In classification, the core and delta(s) of a fingerprint; another term for target group.

**FRICITION RIDGE** - A raised portion of the epidermis on the palmar or plantar skin, consisting of one or more connected ridge units of friction ridge skin.

**FRICITION RIDGE DETAIL (MORPHOLOGY)** - An area composed of the combination of ridge flow, ridge characteristics, and ridge structure.

**FRICITION RIDGE SKIN** – a specialized type of skin present on the palmar portion of the hands and the plantar portion of the feet.

**FRICTION RIDGE UNIT** - Single section of friction ridge containing one pore.

**FURROWS** - Valleys or depressions between the friction ridges.

**GALTON DETAILS** - Term referring to friction ridge characteristics attributed to the research of English fingerprint pioneer, Sir Francis Galton.

**GROUND TRUTH** – Definitive knowledge of the actual source of an impression.

**HENRY CLASSIFICATION** – An alpha-numeric system of fingerprint classification named for Sir Edward Richard Henry.

**HIT** – likely candidate generated as the result of an ABIS search.

**HYPOTHENAR**- The fleshy eminence along the ulnar side of the palm.

**IDENTIFICATION/INDIVIDUALIZATION** - The decision by an examiner that there are sufficient discriminating friction ridge features in agreement to conclude that two areas of friction ridge impressions originated from the same source. Individualization of an impression to one source is the decision that the likelihood the impression was made by another (different) source is so remote that it is considered as a practical impossibility.

**ILIMS** – Idaho Laboratory Information Management System.

**IMAGE PROCESSING** - the process of digitally developing an image to improve the visibility of detail present.

**INCIPIENT RIDGE** - A friction ridge, not fully developed, which may appear shorter and thinner in appearance than fully developed friction ridges (i.e. interstitial, nascent).

**INCONCLUSIVE** - The inability to either individualize or exclude an area of friction ridge detail.

**INTERDIGITAL** – the fleshy portion of the palm located directly below the fingers.

**INTERVENING RIDGES** - The number of friction ridges between two characteristics.

**JOINT** - The hinged area that separates segments of the finger.

**KNOWN PRINT (FINGER, PALM, FOOT)/EXEMPLAR** - A recording of an individual's friction ridges with black ink, electronic imaging, photography, or other medium on a contrasting background.

**LATENT PRINT** - Transferred impression of friction ridge detail not readily visible; generic term used for questioned friction ridge detail.

**LEVEL 1 DETAIL** - Friction ridge flow, pattern type, and general morphological information.

**LEVEL 2 DETAIL** - Individual friction ridge paths and associated events including minutiae (e.g., bifurcations, ending ridges, and dots).

**LEVEL 3 DETAIL** - Friction ridge dimensional attributes (e.g. width, edge shapes, and pores).

**LIFT** - An adhesive or other medium used to transfer a friction ridge impression from a substrate.

**LIVE SCAN** – The process recording of friction ridges (fingers and/or palms) through an electronic system, as opposed to traditional inking methods.

**LI** – ABIS term for Latent Inquiry.

**LI\_COMBO** – ABIS term for Latent Inquiry followed by automatic registration in the unsolved latent database when no HIT is generated.

**LIP** – ABIS term for Latent Inquiry Palm

**LIP\_COMBO** – ABIS term for Latent Inquiry Palm followed by automatic registration in the unsolved latent database when no HIT is generated.

**LR** - ABIS term for Latent Registration in the unidentified latent database.

**LOOP** – A pattern type in which one or more friction ridges enter upon one side, recurve, touch or pass an imaginary line between delta and core and flow out, or tend to flow out, on the same side the friction ridges entered. Types include left slant loops, in which the pattern flows to the left in the impression; right slant loops, in which the pattern flows to the right in the impression. When the hand of origin is known they may be referred to as radial loops, in which the pattern flows in the direction of the radius bone of the forearm (toward the thumb); and ulnar loops, in which the pattern flows in the direction of the ulna bone of the forearm (toward the little finger).

**LR** - ABIS term for Latent registration in the unsolved latent database.

**MAJOR CASE PRINTS/COMPLETE FRICTION RIDGE EXEMPLARS** - A systematic recording of all of the friction ridge detail appearing on the palmar sides of the hands. This includes the extreme sides of the palms, joints, tips, and sides of the fingers. Under special circumstances complete friction ridge exemplars may also need to be taken from the plantar portion of the feet.

**MATRIX** - The substance that is deposited or removed by the friction ridge skin when making an impression.

**MINUTIAE** - Events along a ridge path, including bifurcations, ending ridges, and dots (also known as Galton details).

**MISSED EXCLUSION** - The failure to make an exclusion when in fact the friction ridge impressions are non-mated (includes false positive, non-consensus inconclusive and non-consensus no value).

**MISSED IDENTIFICATION/INDIVIDUALIZATION** - The failure to make an identification when, in fact, both friction ridge impressions are from the same source.

**NCIC CLASSIFICATION** - An alpha/numeric system of fingerprint classification.

**NDP** – No ridge detail present.

**NEGATIVE CONTROL** – A test performed to demonstrate that no false positives result from the performance of a procedure.

**NGI** – ABIS term for the FBI's Next Generation Identification system that replaced IAFIS.

**NON-COMPLEX** - The encountering of common circumstances during an examination (e.g., low distortion, high quality or quantity, or no conflicts among examiners).

**NON-POROUS** - Non-absorbent.

**NV**- indicates the presence of friction ridge impressions assessed for comparison but not designated as such due to a lack of quantity and/or clarity of detail. These impressions are not individually marked.

**ORIGINAL IMAGE** –an accurate replica (pixel for pixel) of the primary image.

**PALM PRINT** – An impression of the friction ridge of all or any part of the palmar surface of the hand.

**PATENT PRINT** - Friction ridge impression of unknown origin, visible without development.

**PATTERN TYPE** – Fundamental pattern of the ridge flow: arch, loop, whorl. Arches are subdivided into plain and tented arches; loops are subdivided into right slant and left slant loops; whorls are subdivided into plain whorls, double loops, central pocket loops, and accidental whorls.

**PLASTIC PRINT** - Friction ridge impression of unknown origin that is impressed in a soft substrate to create a three-dimensional impression.

**PORES** - Small openings in the skin through which perspiration is released.

**POROSCOPY** - A study of the size, shape, and arrangement of pores.

**POROUS** - Absorbent.

**POSITIVE CONTROL** – A test performed prior to or in parallel with casework samples that is designed to demonstrate that a procedure works correctly.

**PRIMARY IMAGE** – The first recording of an image onto media.

**PRESERVED** - Casting, photography, lifting, or other method used to capture latent impressions for further examination.

**PROFICIENCY** - The ongoing demonstration of competency.

**QUALIFIED ANALYST** -An individual who has completed the internal training program, passed competency testing, and been approved to perform case work.

**QUALITY** - The clarity of information contained within a friction ridge impression.

**QUANTITY**- The amount of information contained within a friction ridge impression.

**REAGENT** - Substance used in a chemical reaction to detect, examine, measure, or produce other substances.

**RELATIVE POSITION** - Proximity of characteristics to each other.

**RIDGE FLOW** - The direction of one or more friction ridges; a component of Level 1 detail.

**RIDGE PATH** - The directional flow of a single friction ridge; a component of Level 2 detail.

**RIDGEOLOGY**-The study of the uniqueness of friction ridge skin and its use for personal identification.

**SEQUENTIAL PROCESSING** - Use of a series of development methods in a specific order to maximize development of friction ridge detail.

**SIMULTANEOUS IMPRESSION**- Two or more friction ridge impressions from the same hand or foot deposited concurrently.

**SEMI-POROUS** - a substrate that demonstrates both absorbent and non-absorbent properties.

**SOURCE**- An area of friction ridge skin from an individual from which an impression originated.

**STOCK SOLUTION** - Concentrated solution diluted to prepare a working solution.

**SUBSTRATE** - Surface upon which a friction ridge impression is deposited.

**SUFFICIENCY** - The product of the quality and quantity of the objective data under observation (e.g., friction ridge, crease, and scar features).

**SUFFICIENT** - The analyst's determination that adequate unique details of the friction skin source exist in the impression to support the conclusion.

**SUITABLE** - The determination that there is sufficiency in an impression to be of value for further analysis or comparison.

**TARGET GROUP** - A distinctive group of ridge features (and their relationships) that can be recognized.

**TECHNICAL REVIEW** – Review of notes, documents, and other data that forms the basis for a scientific conclusion.

**TEN PRINT**- A generic reference to examinations performed on intentionally recorded friction ridge impressions; a controlled recording of an individual's available fingers using ink, electronic imaging, or other medium.

**THENAR** - the fleshy mass on the palm of the hand at the base of the thumb.

**TLI** - ABIS term for ten print to latent inquiry.

**TOLERANCE** - The amount of variation in appearance of friction ridge features to be allowed during a comparison, should a corresponding print be made available.

**VERIFICATION** - The independent confirmation of the ACE process as utilized by a subsequent qualified examiner to either support or refute the conclusions of the original examiner.

**WHORL – ACCIDENTAL** - A fingerprint pattern consisting of two different types of patterns, with the exception of the plain arch, with two or more deltas; or a pattern which possesses some of the requirements for two or more different types; or a pattern which conforms to none of the definitions.

**WHORL - CENTRAL POCKET LOOP** - A type of fingerprint pattern which has two deltas and at least one ridge which makes, or tends to make, one complete circuit, which may be spiral, oval, circular, or any variant of a circle. An imaginary line drawn between the two deltas must not touch or cross any re-curving ridges within the inner pattern area.

**WHORL - DOUBLE LOOP** - A type of fingerprint pattern that consists of two separate loop formations with two separate and distinct sets of shoulders and two deltas.

**WHORL – PLAIN** - A type of fingerprint pattern which consists of one or more ridges which make, or tend to make, a complete circuit, with two deltas, between which, when an imaginary line is drawn, at least one re-curving ridge within the inner pattern area is cut or touched.

**WORKING SOLUTION** - Solution at the proper dilution for processing.

**REFERENCES:**

SWGFAST Document #19 Standard Terminology of Friction Ridge Examination (Latent/Tenprint), Ver. 4.1

SWGFAST Individualization/Identification Position Statement  
3/06/2012 ver. 1.0

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016



## 4 RESPONSIBILITIES

- 4.1 The Latent Program Supervisor is responsible for ensuring that personnel adhere to established analytical methods, safety practices, and laboratory policies and procedures.
- 4.2 The Latent Program Supervisor shall ensure that analysts' training records are on file in the latent section.
- 4.3 Individual analysts are responsible for adherence to established analytical methods, safety practices, and laboratory policies and procedures.
- 4.4 Latent print analyst duties include, but are not limited to:
  - 4.4.1 Development of friction ridge impressions;
  - 4.4.2 Documentation of visible or developed friction ridge impressions;
  - 4.4.3 Digitally preserving and processing friction ridge impressions;
  - 4.4.4 Analysis, comparison, and evaluation of friction ridge impressions;
  - 4.4.5 Verification of compared friction ridge impressions;
  - 4.4.6 Issuing reports of examination activities;
  - 4.4.7 Performing technical and administrative casework reviews;
  - 4.4.8 Obtaining known exemplars from living and deceased subjects;
  - 4.4.9 Responding to crime scenes to the extent to which they are trained;
  - 4.4.10 Satisfactorily completing annual proficiency tests;
  - 4.4.11 Presenting expert testimony in court.

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy 01/16/2016  
OBSOLETE DOCUMENT

## 5 SAFETY

- 5.1 Safety is a primary concern of this section as well as the laboratory. Analysts are directed to the Idaho State Police Forensic Services Health and Safety Manual or the Laboratory Safety Officer for instructions regarding general safety procedures.
- 5.2 Latent print development techniques may utilize chemicals and reagents that are hazardous and may include known or potential carcinogens, teratogens or mutagens.
- 5.3 In addition to the information included with each development technique, analysts should consult the Material Safety Data Sheets (MSDS) for further safety information for particular chemicals. The MSDS sheets for the section are located in a yellow binder in latent print chemical laboratory and are available online from the manufacturer or the following websites:  
<http://www.hazard.com/msds>  
<http://www.msds.com>
- 5.4 Analysts must use caution when handling chemicals and evidence.
- 5.5 The following personal protective equipment should be worn while working in the laboratory:  
Lab coat or other protective clothing  
Gloves  
Safety glasses  
Dust mask or respirator (if applicable)
- 5.6 If an analyst encounters evidence that may cause a health risk (foul odor, burning sensation, loaded weapon, etc.), the item should be placed in a fume hood and the Laboratory Manager, Section Supervisor, or Laboratory Safety Officer contacted prior to proceeding.

## 6 ORDERING OF CHEMICALS/SUPPLIES & PREPARATION OF REAGENTS

- 6.1 General laboratory policies and procedure regarding the purchase of chemicals and preparation of reagents are covered in the ISP Forensic Services Quality/Procedure Manual.
- 6.2 Chemical and supply orders will be placed on an as needed basis either by or with the approval of the Section Supervisor.
- 6.3 Reagents prepared in-house will be made with great care following all quality and safety procedures.
  - 6.3.1 Chemical reagents should be prepared in the fume hoods located in the chemical processing lab.
  - 6.3.2 It is best practice to don a dust mask while weighing all powdered chemicals.
- 6.2 Each reagent intended for batch use (i.e. not used one time and disposed of) has a corresponding Reagent Log. When prepared, the date of preparation, manufacture and lot numbers of the chemicals used, initials of the preparing analyst, and quality control test results (applicable to working solutions), are recorded on the corresponding "Reagent Log." The Reagent Log folder is located in the chemical processing laboratory.
- 6.3 The container shall be labeled with the reagents name, analyst's initials, date of preparation and approximate shelf life (if applicable). An NFPA label shall be placed on the reagent container indicating the chemical hazard categories.
- 6.4 Quality control tests for one time use reagents such as sticky side powder shall be noted in the case notes.
- 6.5 All reagents shall be tested after they are prepared and prior to use.
- 6.6 If the same lot of a working solution is used multiple times in the same day, the results of the initial control tests shall be noted on the "ISP FS Latent Section Control Test Log". Subsequent use of the reagent on the same day shall utilize the result to the prior test.
- 6.7 Control test results shall be recorded in the notes sections of ILIMS whenever applicable. In ILIMS a "Yes" in the "+/- Control" field indicates that both positive and negative controls performed as expected.
- 6.8 Should a control fail, the analyst should document that the control failed, attempt to determine the cause, and rectify the problem.

- 6.9 Many reagents will remain viable past their expiration date. A reagent may continue to be used past its expiration date provided both positive and negative control tests are performed and appropriate results obtained.
- 6.10 Expired or unsatisfactory chemicals/reagents will be disposed of in an appropriate manner.

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016

## 7 EVIDENCE PREPARATION AND HANDLING PROCEDURES

- 7.1 Evidence handling will be in accordance to ISPFS Quality/Procedure Manual.
- 7.2 Cases may be generated when customer agencies submit evidence through the Idaho Laboratory Information Management System (ILIMS) or by analysts in response to an ABIS TLI HIT, or as a supplementary assignment to a previous analysis.
- 7.3 Types of cases being worked by a particular analyst may vary and will depend on the types of analysis a specific analyst is approved to perform, case priority (i.e. crimes against persons, impending trial date), and current case load.
- 7.3.1 Analysts should query the ILIMS system for cases assigned to the section, by priority and/or by task type (Processing, Comparison, ABIS Only, etc.).
- 7.4 Analysts are responsible for the security and integrity of all evidence transferred into their custody by Forensic Evidence Specialist staff.
- 7.5 When not under the direct control of section personnel, evidence and in-progress work product will be secured either by closing and locking the laboratory door or by its return to secured storage (analyst's personal evidence cabinet or equivalent).
- 7.6 Should laboratory access be required by non-laboratory personnel while evidence is in process (i.e. maintenance, auditors etc.), they shall be accompanied at all times by latent section personnel.
- 7.7 When evidence packages are opened, original seals should be left intact whenever possible.
- 7.8 All evidence should be examined on a clean workstation covered by butcher paper.
- 7.8.1 Use a 10% bleach solution, or equivalent disinfectant before and after examining biologically contaminated evidence.
- 7.8.2 Care should be taken to prevent cross contamination and deleterious change. Separately packaged items of evidence that could be cross contaminated (e.g. with DNA) should not be examined simultaneously on the same work surface.
- 7.8.3 Potential trace evidence may be transferred to the butcher paper; handle it accordingly. It is acceptable to preserve the butcher paper and return it with the item in the original packaging. Preservation of the butcher paper should be noted in the case notes.
- 7.8.4 Each item of evidence should be evaluated by the analyst to determine the potential for other types of evidence. In the event that other

evidence may be present on an item, the analyst may contact the agency and/or an analyst from the appropriate discipline to determine how to proceed.

- 7.9 Latent print processing has the potential to irreparably damage items of evidence. If an item is suspected to have great value (monetary or sentimental), the analyst should contact the submitting agency to explain potential damage and gain verbal approval prior to processing.
- 7.10 Items to be processed for latent prints may be marked after processing to avoid altering potential evidence. Items shall be marked with the case number, item number, and analysts initials in accordance with the ISP Forensic Services Quality/Procedure Manual.
- 7.11 In order to ensure a correct count, money shall be counted by the analyst and witnessed by one other person when first opened (if possible) and again when it is resealed. If the dollar amount is less than \$20.00 a count witness is not required. The identification of the witness shall be noted in ILIMS.
- 7.12 Evidence that contains a measurable amount of a controlled substance may be handled and processed in the latent section.
  - 7.12.1 If a recoverable amount of substance is received, the analyst will separate the substance from the packaging, re-package the substance in a secondary container and return the secondary container to the original packaging. Repackaging shall be noted in ILIMS
  - 7.12.2 The Latent Section shall not measure/weigh any suspected controlled substance.
  - 7.12.3 The preferred practice is for the submitting agency to separate the suspected controlled substance from the packaging material.
- 7.13 Submission of hands, fingers, or feet of deceased persons to the Latent Section shall only occur when normal printing procedures have failed or cannot be applied due to decomposition.
  - 7.13.1 Hands, fingers, or feet should only be removed by the attending medical examiner/coroner or under their authority and supervision.
  - 7.13.2 When possible, it is desirable to have the hands severed at the wrist, and forwarded in their entirety. This eliminates the possibility of getting fingers mixed up or incorrectly labeled. If it is not possible to send the hands, the fingers may be submitted. Fingers should be severed at the palm, placed in individual containers, and immediately labeled as to which they are.
  - 7.13.3 It is requested that hands, fingers, etc. be submitted as soon as possible in the same condition as found. If the hands were immersed in water, transport in water. If found dried out, place in an airtight container and transport without using any preservative.
  - 7.13.4 Tissue should be refrigerated if possible.

- 7.13.5 **Do not use a formaldehyde solution** to preserve the tissue as it causes it to become brittle and hard, making the task of obtaining identifiable prints very difficult.
- 7.13.6 Body parts received by the lab shall be sealed and placed in an evidence refrigerator or freezer.
- 7.13.7 Body parts shall be promptly returned to the submitting agency after being processed.
- 7.14 Case related comparison photographs are retained in the Digital Imaging System. Images will be made available to the agency and/or prosecutor upon request.
- 7.15 All submitted evidence including any derived latent lift cards will be returned to the FES staff for return to the submitting agency.
- 7.15.1 When latent lift cards are generated during processing, an Impression Evidence Packet (IEP) shall be created. The analyst will add the IEP to the case on the ITEMS tab in ILIMS. The Item # will be "IEP." They will note the packaging, Item Type - "IMP Latent Print Comparison Item(s)," and the description field shall detail how many lifts are contained in the IEP and from which item they were derived (e.g. three latent lift cards: 2 from item 1.1 and one from item 3.3). If the original IEP has been returned to the agency and additional submissions result in generation of LLCs, Item numbers on subsequent IEPs will follow the pattern of IEP2, IEP3, etc.
- 7.15.2 The analyst will then print a bar code for the IEP and associate the IEP with the appropriate assignment on the ASSIGNMENTS tab in ILIMS.
- 7.16 Evidence may be temporarily retained for future reference with the approval of the Discipline Leader. Approval shall be documented in ILIMS.

## 8 VALIDATION

- 8.1 Procedures for the validation and/or performance verification of methods used in ISP Forensic Services are outline in the ISP Forensic Services Quality/Procedure Manual.
- 8.2 Validations and/or performance verifications shall also be conducted in accordance with SWGFAST Document #17 “Standard for the Validation and Performance Review of Friction Ridge Impression Development and Examination Techniques version 2.0” or its current replacement document.
- 8.3 Validation/performance verification data, results and summaries for those methods employed in the Latent Print Section will be maintained in that section.

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016



## 9 EQUIPMENT CALIBRATION, MAINTENANCE, AND REPAIR

- 9.1 General laboratory procedures for the calibration and maintenance of equipment are covered in the ISP Forensic Services Quality/Procedure Manual.
- 9.2 Operating manuals for section equipment/instrumentation are maintained in the product information file located in the digital imaging laboratory.
- 9.3 Records from outside vendors, Instrument Maintenance Logs and Monthly QC check forms are maintained in the latent section QC binder located in the chemical processing laboratory.
- 9.4 The function of the following equipment is documented on the Monthly QC check form:  
Fume Hoods  
Eyes washes  
Chemical shower  
Balance  
Cyanoacrylate fuming chamber  
Fingerprint development chamber
- 9.5 General, routine, maintenance such as wiping off the outside of an instrument, cleaning the glass on flatbed scanners, cleaning camera lenses is not required to be noted on the instrument maintenance logs.
- 9.6 Instrument maintenance logs shall be utilized in the event of instrument malfunction, failure, scheduled maintenance, certifications, and other non-routine maintenance.
- 9.7 Instrument failure will result in equipment being taken “out of service”. A sign will be placed on the instrument and it will not be returned to service until it has passed appropriate performance testing and documentation of such has been recorded on the appropriate instrument maintenance log. These logs are maintained for the following:

### **ALS - Alternate Light Sources**

General maintenance shall consist of cleaning the exterior of the ALS with a soft cloth dampened with a mild detergent solution. Clean the ends of light guides, optical filters and lenses as needed using non-abrasive tissue moistened with ethanol or Windex. Replace bulbs as needed (document on instrument maintenance log).

### **Mini –Crimescope MCS-400**

The wheels may be opened with a screw driver to allow for cleaning of both sides of the filters and lenses with lens tissue and ethanol. Eliminate dust if it has accumulated in the wheel (document on instrument maintenance log).

### **Ominchrome Omniprint 1000A**

Remove the cover and use compressed air to remove debris. Clean fan air filter by removing from the instrument and rinsing with tap water. Allow filter to dry completely and replace (document on instrument maintenance log).

**Rofin Polilight PL400** is a self-calibrating instrument. The unit will calibrate on its own via an internal microprocessor. If the instrument is not functioning properly, the unit will display an error message. Errors that are not self-correcting will require maintenance.

### **Balance - Mettler Toledo**

Clean housing and weighing pan with a cloth and if necessary, a mild cleaning agent.

Balance is checked annually by an external provider. A Calibration Certificate will be issued and placed in the equipment maintenance log (document on instrument maintenance log).

Intermediate checks may be conducted as needed and documented on the QC worksheet. The allowable deviation from the standard weights is 0.01g or 0.1%, whichever is greater (.01g deviation for the 0.10g & 1.00g and 0.1g for the 100g weights-document on monthly QC log).

If the balance fails an intermediate or annual check, it will be taken out of service until it can be recalibrated or repaired (document on instrument maintenance log).

Balances and ASTM weights used for checks are calibrated yearly by an outside source and are stored in the chemistry section of the laboratory.

### **Cameras - Canon EOS 6D, Fujifilm IS Pro F5, Fujifilm IS Pro**

Use a blower to blow away dust on the lens, viewfinder, reflex mirror and focusing screen. Do not use cleaners that contain organic solvents. Use a lint free cloth and lens cleaning solution to clean lenses.

### **CAE Fuming Chambers - Air Science**

The chamber shall be cleaned monthly and as needed using soapy water or CAE cleaner (document on monthly QC log).

The humidifier wick filter shall be inspected monthly and replaced as needed. Filter replacement schedules for these instruments are based on frequency of use. For the CA30, small chamber, the main carbon filter (ASTM-001) should be replaced annually with pre-filters (ASTMT-PRF & CA-PRF) changed every three months. For the CA60T, large chamber, the main carbon filter (ASTM-001) should be replaced every two year with pre-filters (ASTMT-PRF & CA-PRF) changed every six months. The proceeding shall be documented on the instrument maintenance log.

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 26 of 119

### **Chemical Exhaust Hoods (commercially purchased hoods)**

The impression evidence section currently has three of these hoods located in the latent section chemical laboratory. All hoods are equipped with continuous flow monitoring devices. Capture velocity at the open face of the commercially purchased hoods is at least 100 feet/minute. Capture velocity at the open face of the sink hoods ranges between 75-100 feet/minute. If a hood fails a monthly check, the check will be repeated. If the hood still fails, it will be taken out of service until it can be repaired. The hood shall be tagged indicating that it is out of service.

General maintenance consists of cleaning.

Hoods are checked annually by an outside vendor and documentation is retained in the equipment maintenance log.

Additional maintenance shall be conducted as needed and will be recorded in the maintenance log.

### **Fingerprint Development Chamber – Caron 6105**

The distilled water reservoir (bottle) and drains should be checked monthly. The system is gravity fed so the bottle should be at least half full and the bottle cap should have a “weep hole” or otherwise allow for air flow. The bottle shall be maintained with distilled, de-ionized, or nano-pure water obtained from the biology unit. The chamber should be cleaned monthly (document on monthly QC log).

When using the chamber for ninhydrin processing, the glass should be warm to the touch and condensation within the chamber should be visible. When using the chamber for DFO, the glass should be warm to the touch and no condensation should be visible. If the preceding specifications are not observed, refer to the manufacturer’s instrument operation manual section on trouble shooting. If the problem cannot be resolved, the chamber will be taken out of service until it can be repaired. The chamber shall be tagged indicating that it is out of service. Maintenance, service calls, etc. will be recorded in the maintenance log.

### **Krime Site Images (KSI)**

For KSI maintenance see method 12.2

### **Powder Hoods (Not commercially purchased)**

The latent section currently has four of these hoods located in the latent section powder laboratory.

These hoods are checked annually by an outside vendor. General maintenance consists of cleaning. Filters are changed regularly by building maintenance

staff. Additional maintenance shall be conducted as needed and will be recorded in the maintenance log.

## **SCANNERS**

### **Flatbed Scanners – Epson V850 Pro & V700**

Clean the scanner glass and the transparency unit window with a soft dry cloth. If needed, use a small amount of glass cleaner on a soft cloth. Do not spray glass cleaner directly on the scanner glass. To clean the outside of the unit, turn the scanner off and unplug the power cord. Clean the outer case with a cloth dampened with mild detergent and water.

### **Fujitsu ScanSnap ix500**

To clean the outside of the unit, turn the scanner off and unplug the power cord. Clean the outside of the Scan Snap with a dry cloth or cloth moistened with cleaner/mild detergent. Be careful not to get any moisture or water inside the scanner during cleaning.

It is recommended that the inside of the scanner be cleaned when streaking occurs on scans. To clean the inside of the unit, turn the scanner off, unplug the power cord, and wait at least 15 minutes for the unit to cool. Clean the pick rollers, brake rollers, idle rollers, ultrasonic sensor, and wipe off all glass surface areas. See user manual or Fujitsu website for location of parts. Clean with a lint free cloth and Fujitsu F1 cleaner or lint free cloth moistened with isopropyl alcohol. Do not use canned air. Cleaning the inside of the scanner shall be documented on instrument maintenance log.

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy 01/16/2016  
OBSOLETE DOCUMENT

## 10 GENERAL LATENT PROCESSING

- 10.1 Latent print evidence is processed according to the nature of the substrate (surface) to be processed.
- 10.1.1 Substrate types include porous, semi-porous, and non-porous.
  - 10.1.2 Consideration should be given to the color and texture of the surface in order to determine which technique will provide suitable contrast.
  - 10.1.3 Processing is generally carried out in a sequential manner employing methods appropriate to the substrate type
  - 10.1.4 ISP Forensic Services Latent Section reserves the right to process evidence items as a whole when items are not listed and/or submitted individually (e.g. bag of miscellaneous items).
- 10.2 Latent print evidence is also processed with regards to the composition of the latent print matrix. For example, a latent print may be composed of perspiration, blood, or a combination of both.
- 10.2.1 Eccrine sweat glands are most concentrated on the palmar portion of the hands and plantar portion of the feet. Secretions from these glands consist of 99.0 to 99.5 percent water and 0.5 to 1.0 percent solids (organic substances and inorganic salts).
  - 10.2.2 Latent prints may also consist of fats and oils (sebum) secreted by the sebaceous glands. These glands are most concentrated on the nose, ear, and groin areas. They are not located on the palmar portion of the hands and plantar portion of the feet, but sebum may be transferred to them via contact with other portions of the body.
  - 10.2.3 Fats, oils, and other contaminants may also be transferred to friction ridge skin by contact with sources external to the body.
- 10.3 Latent print processing generally proceeds from the least invasive technique to the most invasive technique.
- 10.4 Impressions deemed suitable for further analysis shall be marked and preserved.
- 10.4.1 Fingerprints of known orientation may be marked with an arch above the print.
  - 10.4.2 Palm prints and fingerprints of indeterminate orientation may be marked with a line or partial bracket.
  - 10.4.3 Upon marking, latents will be giving a unique identifier consisting of the item number followed by the latent number.
- 10.5 For the purpose of this manual, latent print methods are divided into three categories: light based methods, physical methods, and chemical methods.
- 10.5.1 LIGHT BASED METHODS
    - 10.5.1.1 Latent prints may be visualized through the use of various angles and wavelengths of light.

10.5.1.2 Visualization of latent prints through the use of forensic lighting methods is non-destructive and should be attempted prior to other processing methods.

#### 10.5.2 PHYSICAL METHODS

10.5.2.1 The development of latent prints through the use of physical methods does not involve a chemical reaction between the impression and the method used.

10.5.2.2 Physical methods encompass dusting and other discoloration methods often relying on the adhesive quality of certain latent prints.

10.5.2.3 The taking of known exemplars from a living or deceased person shall be considered a physical method for the purposes of this manual.

#### 10.5.3 CHEMICAL METHODS

10.5.3.1 The development of latent prints through the use of chemical methods occur because of a chemical reaction between the latent print residue components and the reagent.

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016

## 11 QUICK REFERENCE SEQUENTIAL PROCESSING GUIDE

*Processing steps indicated by bold typeface are a base requirement that shall be conducted when processing a specific evidence type. If the base requirement is not performed, the analyst shall have adequate documentation in their notes to justify why a particular step was not or could not be utilized. Justification shall be to the extent that another qualified examiner would come to the same conclusion (e.g. not processing the adhesive side of a label when there is no evidence it was accessed by the subject or not proceeding with powder processing due to excessive adhesion to the background).*

*When changes to processing necessitate not following the recommended sequence and/or require the elimination of two or more base requirements (excluding **VISUAL** examinations), the analyst shall contact the discipline lead to request a deviation. The request shall be made prior to beginning processing, and shall include the level of deviation as defined by the ISP Quality/Procedure Manual and a clearly defined reason for the request. Documentation of the approved deviation is required in the case file.*

### 11.1 GENERAL EVIDENCE:

#### 11.1.1 POROUS:

1. **Visual:** White light
2. Alternate Light Source (ALS)
3. Iodine Fuming
4. **Visual:** White light
5. 1,8 Diazafluorenone-9-one (ДФО)
6. **Visual:** ALS
7. **Ninhydrin**
8. **Visual:** White light
9. 1,2-Indanedione
10. **Visual:** ALS
11. Physical Developer
12. **Visual:** White light

#### 11.1.2 NON-POROUS:

1. **Visual:** White light
2. ALS
3. **Cyanoacrylate Fuming**
4. **Visual:** White light
5. **Dye Stain**
6. **Visual:** ALS
7. **Powders:** Luminescent or non-luminescent
8. **Visual:** White light and/or ALS

### 11.2 BLOOD EVIDENCE:

#### 11.2.1 POROUS:

1. **Visual:** White light
2. ALS/UV (background luminescence)

3. **Ninhydrin** or **Leucocrystal Violet (LCV)** or **Amido Black/De-stain**
4. **Visual:** White light

11.2.2 NON-POROUS:

1. **Visual:** White light
2. ALS/UV (background luminescence)
3. **Cyanoacrylate Fuming**
4. **Visual:** White light
5. **Amido Black/De-stain** or **Leucocrystal Violet (LCV)**
6. **Visual:** White light
7. **Dye Stain**
8. **Visual:ALS**
9. **Powders:** Luminescent or non-luminescent
10. **Visual:** White light/ALS

11.3 GLOSSY PAPER/GLOSSY CARDBOARD/PHOTO PAPER:

11.3.1 Glossy Side

1. **Visual:** White light
2. ALS
3. Iodine
4. **Cyanoacrylate Fuming**
5. **Visual:** White light
6. **Powders:** Luminescent or non-luminescent magnetic powder
7. **Visual:** White light/ALS
8. 1,8 Diazafluorenone-9-one (DFO) or Ninhydrin or 1,2 Indanedione
9. **Visual:** White light
10. Physical Developer
11. **Visual:** White light

11.3.2 Non-glossy - process as for porous evidence

11.4 LEATHER:

1. **Visual:** White light
2. ALS
3. **Cyanoacrylate Fuming**
4. **Visual:** White light
5. **Powders:** Luminescent or non-luminescent
6. **Visual:** White light/ALS

11.5 PAINTED SURFACES:

1. Latex Paint: process as for porous evidence
2. Semi-gloss/enamel paint: process as for non-porous evidence



11.6 SEMI-POROUS (e.g. Rubber/Synthetic gloves):

1. **Visual:** White light
2. ALS
3. Iodine
4. **Visual:** White light
5. **Cyanoacrylate fuming**
6. **Visual:** White light
7. **Ninhydrin**
8. **Visual:** White light
9. **Dye Stain**
10. **Visual:** ALS
11. **Powders:** Luminescent or non-luminescent
12. **Visual:** White light/ALS
13. Physical Developer

11.7 TAPE:

11.7.1 Non-adhesive side of non-porous tape:

1. **Visual:** White light
2. ALS
3. **Cyanoacrylate Fuming**
4. **Visual:** White light.
5. **Dye Stain**
6. **Visual:** ALS
7. **Powders:** Luminescent or non-luminescent
8. **Visual:** White light/ALS

11.7.2 Adhesive side of tape (select method that contrasts with the color of the tape):

1. **Visual:** White light
  2. ALS
  3. **Gentian Violet** or **Small Particle Reagent** or **Sticky Side Powder**
  4. **Visual:** White light
- OR
1. **Visual:** White light
  2. ALS
  3. **Cyanoacrylate Fuming**
  4. **Visual:** White light
  5. **Dye Stain**
  6. **Visual:** ALS

11.8 VARNISHED WOOD:

1. **Visual:** White light
2. ALS
3. **Cyanoacrylate fuming**
4. **Visual:** White light
5. **Dye Stain**
6. **Visual:** ALS

5. **Visual:** ALS
6. **Powders:** Luminescent or non-luminescent
7. **Visual:** White light/ALS

11.9 WET SURFACES:

11.9.1 POROUS:

1. **Visual:** White light
2. ALS
3. Dry to room temperature
4. **Visual:** White light/ALS
5. **Physical developer**
6. **Visual:** White light

11.9.2 NON-POROUS:

1. **Visual:** White light
2. ALS
3. **Small Particle Reagent (SPR)**
4. **Visual:** White light
5. Tape lift

11.10 EXEMPLARS FROM HUMAN SKIN:

11.4.1 Decomposing and/or Macerated Friction Ridge Skin (water soaked)

1. Ink and/or powder lift method (if possible)
2. Photography

11.4.2 Mummified Friction Ridge Skin (dried)

1. Ink and/or powder lift method (if possible)
2. Photography
3. Casting
4. Attempt to re-hydrate (kit available)

11.4.3 Burned Friction Ridge Skin

1. Photograph
2. Ink

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016

## 12 LIGHT BASED METHODS

### 12.1 ALTERNATE LIGHT SOURCE

#### 12.1.1 BACKGROUND:

Alternate light sources (ALS) are portable, multi-waveband, and tunable light sources that are used to enhance or visualize potential items of evidence. Latent impressions may be composed of various substances such as blood, perspiration, chemicals or other organic substances that react differently to different wavelengths of light. When a luminescent deposit is excited with a particular wavelength of light, the deposit absorbs the light and re-emits it at a different wavelength. The short-lived light being re-emitted is termed fluorescence. There are several alternate light sources available to analysts that adequately meet the needs described in this manual.

#### 12.1.2 SCOPE:

12.1.2.1 The ALS is used to attempt to create contrast between an impression and the substrate.

12.1.2.2 Fluorescence may occur due to a naturally occurring substance within the latent print residue itself (inherent luminescence), may be transferred to the friction ridge skin via contamination and re-deposited, or may be induced in latent print residue with certain chemicals and powders known to exhibit fluorescent properties. Fluorescence of the substrate may also occur.

#### 12.1.3 EQUIPMENT AND MATERIALS:

Alternate light source  
Filtered goggles

#### 12.1.4 REAGENTS:

Not applicable

#### 12.1.5 PROCEDURE:

12.1.5.1 Turn on ALS. Make sure the ALS comes to full operating power (fan and bulb reach consistent speed/brightness).

12.1.5.2 Turn on the lamp. The lamp function will vary slightly in different models.

12.1.5.3 Choose the band-width you wish to use. Some models have a variable power dial that may need to be adjusted.

12.1.5.4 Observe evidence with the appropriate wavelength/goggle combination:

<u>WAVELENGTH</u>	<u>CORRESPONDING FILTER</u>
< 400nm	yellow or clear UV safe
400-450nm	yellow

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 35 of 119

450-540nm            orange  
540->700nm        red

12.1.5.5 Turn off the ALS lamp and allow to cool completely before powering off ALS.

12.1.6 ADDITIONAL INFORMATION:

12.1.6.1 If an ALS malfunctions, it will be taken out of service until it can be repaired. The ALS shall be tagged indicating that it is out of service. Maintenance, service, etc. will be recorded in the maintenance log.

12.1.6.2 No calibration is required of these units.

12.1.6.3 The manufacturer's operator manuals shall be read prior to initial use of the equipment.

12.1.7 CONTROLS:

Not applicable

12.1.8 SAFETY:

12.1.8.1 As with other electrical appliances, guard against electrical shock. This can be accomplished by ensuring that all connections are proper and that no loose, damaged, or frayed wires exist. Make sure the ALS is unplugged before attempting any maintenance and do not use outdoors if wet conditions exist.

12.1.8.2 The eyes are generally more vulnerable than the skin, and appropriate eye protection must be used to protect them. Permanent eye damage can occur from reflected, refracted, or direct illumination to the eye. Most of the light emitted by an ALS is not absorbed, but is reflected and scattered off the surface being examined. Extreme care should be taken around highly reflective surfaces. Never look directly into the light or allow beams to bounce off the surface into your eyes or the eyes of another person in the vicinity. Filtered goggles or shields shall be utilized when using this equipment as they provide protection from potentially harmful rays and provide additional enhancement for viewing latent prints.

12.1.8.3 The nature and extent of all potential hazards are not yet known because in-depth assessments have not been made on most of the high intensity light sources used in forensic identification work.

12.1.9 REFERENCES:

Advances in Fingerprint Technology, Henry Lee and R. E. Gaensslen, pages 90, 115-118.

An Introduction to Lasers, Forensic Lights, and Fluorescent Fingerprint Detection Techniques, E. Roland Menzel, (1991).

Friction Ridge Skin, James F. Cowger, (1983), pages 106-107.

Omnichrome Evidence Detection with Forensic Laser Technology, (1989).

Omniprint 1000A Operating Instructions, Omnichrome.

Mini-CrimeScope Tunable Forensic Light Source Model MCS-400W Operation and Maintenance Instructions (2003).

Rofin Polilight PL400 Forensic Light source, Polilight PL400 Instruction Manual, Version 1 11/2001

## 12.2 KRIMESITE IMAGER

### 12.2.1 BACKGROUND:

The KRIMESITE IMAGER (KSI) is an image-intensifying device that locates untreated latent prints and other evidence of forensic interest on non-porous surfaces by utilizing Reflective Ultra-Violet Imaging System technology (RUVIS). Ultra-violet (UV) light will reflect off of a fingerprint at a different wavelength or speed than it will off the substrate. This creates contrast that is able to be visualized because the KSI system takes UV light and converts it to visible light.

### 12.2.2 SCOPE:

12.2.2.1 No treatment with powders or chemicals is necessary, however, use of the imager may greatly enhance results obtained by cyanoacrylate fuming.

12.2.2.2 The KSI is most effective on non-porous surfaces, but can detect recently deposited prints on some porous surfaces.

12.2.2.3 The KSI is not affected by ambient light, which means it can be used in daylight or total darkness, indoors or outdoors.

12.2.2.4 The most appropriate method to preserve KSI-located impressions is through photography.

12.2.2.5 The KSI system may be used in the laboratory or when providing technical field assistance.

### 12.2.3 EQUIPMENT AND MATERIALS:

Short wave 254 nm ultraviolet light source

Camera

Reflective Ultraviolet Imaging System

Tripod

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 37 of 119

## Eye protection

### 12.2.4 PROCEDURE:

- 12.2.4.1 Attach the KSI to a tripod or use it as a hand held device.
- 12.2.4.2 Position the sliding filter system assembly to the UV position window (mirror facing away from analyst and the catalogue number facing the analyst).
- 12.2.4.3 Turn the KSI unit on and verify the red light is lit.
- 12.2.4.4 Turn on the ultraviolet light source. If using both 6-watt bulbs on the UV source, turn one bulb on at a time or both bulbs of the unit will only illuminate at half-power.
- 12.2.4.5 For best results, direct the UV light at a 15° to 45° angle from the surface of interest. Point the KSI perpendicular to the surface.
- 12.2.4.6 Set the aperture to the f/3.5 position (completely open).
- 12.2.4.7 Focus the 60mm lens.
- 12.2.4.8 Focus the eyepiece until you have the clearest largest picture.
- 12.2.4.9 When scanning an item or area for possible latent evidence the most effective distance for viewing is 0 –5 ft with the 12 watt UV light source and 5-10 ft with the 30 watt UV light source. The operator of the lamp and all others present should remain behind the light source when it is turned on.
- 12.2.4.10 If a latent impression is located, mark the location using the marking devices supplied or an adhesive scale. Always use a UV scale to insure proper sizing when photographing images with the KSI.
- 12.2.4.11 Use the Canon Power Shot G3 or other appropriate digital camera to capture KSI images.
- 12.2.4.12 After locating a latent print, attach the KSI unit to the copy stand or a tripod.
- 12.2.4.13 Focus using the short-wave UV light. Make sure that the KSI aperture is all the way open (f/3.5) and leave the KSI eyepiece in place.
- 12.2.4.14 Attach the digital camera using the adapter.
- 12.2.4.15 Turn the camera on, ensure it is set to auto, turn on the MACRO setting, turn off the flash, and set to highest resolution possible.
- 12.2.4.16 Press the shutter button half way to activate the auto focus.
- 12.2.4.17 Use the zoom function to fill the viewing field with the latent image.
- 12.2.4.18 Capture the image by fully pressing the shutter button. It is preferable to use the remote to avoid shaking the camera.
- 12.2.4.19 Once the examination is complete, turn all equipment off, and store appropriately.

### 12.2.5 ADDITIONAL INFORMATION:

- 12.2.5.1 Refer to the digital camera manufacturer's operator manual for full camera operation.
- 12.2.5.2 General maintenance consists of periodic laser pointer battery replacement, cleaning the surface of the KSI band pass filter with a lens cleaning solution and tissue, and cleaning the short-wave UV lamps and KSI UV lens with an alcohol moistened soft cloth. General maintenance shall be performed as needed.
- 12.2.5.3 UV lamps should be replaced as needed, taking care to dispose of lamps in a proper environmental manner as they contain mercury.
- 12.2.5.4 If the KSI malfunctions, it will be taken out of service until it can be repaired. The KSI shall be tagged indicating that it is out of service. Maintenance, service, etc. will be recorded in the instrument maintenance log.
- 12.2.5.5 No calibration is required of this unit.
- 12.2.5.6 The manufacturer's operator manuals for this equipment shall be read prior to initial use of the equipment.

#### 12.2.6 CONTROLS:

- 12.2.6.1 Testing of the KSI is performed prior to each use.
- 12.2.6.2 This test involves the making of a quality latent print on a non-porous surface similar to the evidence being examined, if possible.
- 12.2.6.3 The test print is viewed with the KSI as outlined in the procedure.
- 12.2.6.4 An analyst shall not proceed with the processing of the evidence until a control test bearing positive results (visualization of a green colored print) has been carried out and documented in the laboratory case notes.
- 12.2.6.5 The area surrounding the intentionally deposited latent print shall serve as a negative control.

#### 12.2.7 SAFETY:

- 12.2.7.1 Serious eye and skin injury along with allergic reactions may result if personnel are inadequately protected from the lamp or other improper use of the equipment occurs.
- 12.2.7.2 Exposure to UV-C and UV-B present great risk to the cornea. The short-wave UV-C light used with the KSI operates at 254 nm. Short-term injury may include keratoconjunctivitis (snow blindness or welder's flash, a condition where the corneal epithelial cells are damaged or destroyed) and severe sunburn-like symptoms. Chronic (repeated) exposure is known to cause premature aging of the skin and skin cancers.
- 12.2.7.3 Never operate the UV lamps without wearing protective eyewear. Failure to do so may result in severe burns, long-term injury to the eyes, or blindness. Avoid needless exposure. UV

light, although invisible, reflects in a manner similar to visible light. Turn lamps off when not in use.

12.2.7.4 All persons present should utilize protective measures including, UV absorbing face shields or glasses, long sleeved shirts, and gloves when the lamps are in use. These measures may not eliminate all UV radiation, but they will lessen the risk of severe exposure.

12.2.7.5 Some individuals are abnormally sensitive to UV radiation. If you believe yourself to be particularly sensitive to sunlight, do not work in an area where short-wave UV light is in use. Certain common medications and cosmetics may greatly increase your sensitivity to UV radiation. Consult your physician concerning any medication you may be taking.

12.2.7.6 Use extra caution when new lamps are installed as radiation levels may be markedly higher.

#### 12.2.8 REFERENCES:

“Detecting and Enhancing Latent Fingerprints with Short Wave UV Reflection Photography,” Wang Gui Qiang. Proceedings of the International Symposium on Fingerprint Detection and Identification, Israel National Police, 1991 pgs. 37-49

“Evaluation of a Reflected Ultraviolet Imaging System for Fingerprint Detection,” Richard Saferstein, and Susan L. Graf. *Journal of Forensic Identification*, 51 (4), 2001 pgs. 385-393.

*Krimesite Imager User's Manual*, Sirchie Finger Print Laboratories, Inc.

“Krimesite Training Notes,” Instructor: Chris Harris, Sales and Training Representative, Sirchie Fingerprint Laboratories, Inc.

“Reflected Ultraviolet Imaging System Applications,” Edward R. German. Proceedings of the International Symposium on Fingerprint Detection and Identification, Israel National Police, 1996 pgs. 115-118.

“UV Detection of Untreated Latent Fingerprints,” Hadrian Fraval, Alex Bennett, and Eliot Springer. Proceedings of the International Symposium on Fingerprint Detection and Identification, Israel National Police, 1996 pgs. 51-58.



## 13 PHYSICAL METHODS

### 13.1 IODINE FUMING

#### 13.1.1 BACKGROUND:

Iodine fuming is one of the oldest latent print methods currently employed in the examination processes for the visualization of latent prints. Iodine vapors are physically absorbed by fats and oils of a latent print deposit and turn the latent print a yellow/brown color.

#### 13.1.2 SCOPE:

13.1.2.1 Use when attempting to develop prints that are thought to be recently deposited and/or composed of fatty or oily residue.

Iodine reacts to recently deposited prints because specified residue tends to become less receptive to this process with time.

13.1.2.2 Other latent print methods such as DFO or ninhydrin tend to dissolve the fats with which iodine reacts. Therefore, if iodine fuming is to be used, it must be used prior to other latent print development processes.

13.1.2.3 Iodine is not suitable for metals or dark surfaces.

#### 13.1.3 EQUIPMENT AND MATERIALS:

Fume hood

Chamber or a heavy-duty sealable plastic bag

#### 13.1.4 REAGENT:

Iodine crystals

#### 13.1.5 PROCEDURE 1 - CHAMBER METHOD:

13.1.5.1 In a fume hood, break open a glass ampoule of iodine crystals to reveal the iodine crystals.

13.1.5.2 Place the crystals in an airtight chamber (ex. sealable heavy plastic bag, commercial fuming chamber, etc.).

13.1.5.3 Apply heat if necessary. The application of heat may be accomplished in various ways including transfer of body heat, contained hot water, or an electric heater. Iodine crystals will start to sublime, go from a solid to a gas, resulting in purplish fumes with the application of heat (approximately 100° F).

13.1.5.4 Place the control test and the questioned surface in the chamber and proceed with fuming.

13.1.5.5 The control test and evidence are monitored by viewing through the chamber to determine when processing is complete.

13.1.5.5.1 Latent prints, if developed, will turn a yellow-brown color.

13.1.5.5.2 The process needs to be carefully monitored so that over-development does not occur.

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 41 of 119

13.1.5.6 Developed prints are evaluated to determine their suitability for comparison.

13.1.5.7 Prints deemed to be of value are marked and photographed as soon as possible, and notes are taken.

#### 13.1.6 ADDITIONAL INFORMATION:

13.1.6.1 The resulting yellow-brown latent prints can vanish and must be preserved.

13.1.6.2 It is suggested that the camera be set up prior to iodine processing.

13.1.6.3 Iodine prints that have faded, or are completely gone, can sometimes be redeveloped by reprocessing. Iodine reprocessing cannot be done if other methods have been used or if too long of a time span has elapsed.

13.1.6.4 Shelf life of sealed iodine is indefinite.

13.1.6.5 Iodine crystals originating from glass ampoules shall be disposed of in the hazardous waste containers located in the fume hoods.

#### 13.1.7 CONTROLS:

13.1.7.1 Testing of iodine is performed simultaneously with the evidence processing.

13.1.7.2 This test involves the making of a quality latent print (oil based) on a test surface similar to the evidence being examined. The area surrounding the intentionally deposited latent print shall serve as a negative control.

13.1.7.3 The test print is exposed to the fumes in the same manner as the questioned surface would be. Positive results (development of a yellow-brown impression) and negative results (minimal development in negative control areas) are documented in the laboratory case notes.

#### 13.1.8 SAFETY:

13.1.8.1 Safety is a serious concern when using the iodine fuming method. *Iodine is toxic in any form. ALWAYS AVOID INHALING IODINE FUMES.*

13.1.8.2 Iodine fumes may irritate the skin and damage the respiratory tract. Headaches that can last for several days may result from exposure to iodine. Long-term effects to the thyroid gland may result from exposure.

13.1.8.3 Adequate ventilation when using the method is mandatory as the fumes are corrosive to metals and may discolor other surfaces that they come in contact with.

13.1.8.4 Iodine shall be purchased in glass ampoules. The ampoules shall stay sealed until use.

### 13.1.9 REFERENCES:

Friction Ridge Skin, James F. Cowger, (1983), pages 93-96.

Fingerprint Techniques, Andre A. Moenssens, (1971), pages 114-120.

Scott's Fingerprint Mechanics, Robert D. Olsen, (1978), pages 247-256.

Manual of Fingerprint Development Techniques, British Home Office, (1998), Chapter 4. Peavey Product Guide, (1999).

## 13.2 LIFTING METHODS

### 13.2.1 BACKGROUND:

Lifting methods are effective for the preservation of latent print impressions because the adhesive on the lifting medium is stickier than the surface on which the latent print deposit resides. It is a good idea to have a variety of lifting mediums as they vary in clarity, adhesion, and flexibility.

### 13.2.2 SCOPE:

13.2.2.1 Lifting methods are applicable to prints that have first been developed utilizing other methods such as powders, SPR, and occasionally prints deposited in dust.

13.2.2.2 Lifts are inexpensive, easy, and a quick method of preserving developed latent images for future comparison.

13.2.2.3 Latent print lifting is one of the most common and effective methods of preserving latent print images at a crime scene.

13.2.2.4 Lifting may not be the most effective method of preserving a particular latent print.

### 13.2.3 EQUIPMENT AND MATERIALS:

Powder station exhaust vent or hood

Various sizes and types of standard lifting tapes

Hinge lifts

Elastic tapes

Gel lifters

Casting compounds

### 13.2.4 PROCEDURE 1 - HINGE LIFTS, TAPES, AND GEL LIFTERS:

13.2.4.1 Ensure that the surface has been prepared for lifting by removing excess powder.

13.2.4.2 Lifting mediums should be removed from their backing in a smooth, continuous motion without hesitation to avoid lines in the adhesive.

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 43 of 119

- 13.2.4.3 The lifting medium is then applied to the latent bearing surface in a smooth, continuous motion, taking care to avoid air pockets and creases. It may be necessary to firmly rub the lifting medium onto the surface using a fair amount of pressure.
- 13.2.4.4 Removal of the lifting medium from the latent bearing surface should also be performed in a smooth continuous motion and applied to the glossy side of the latent lift card in the same manner as noted above.
- 13.2.4.5 Latent lift cards shall be filled out as completely as possible and shall include the following:  
Unique case identifier;  
Date and initials;  
Impression source (description or source identifier);  
Significant information about the orientation and/or position of the latent print on the object through description and/or diagram(s). One should be able to pinpoint the area and orientation of a latent print on the object.
- 13.2.4.6 Lifts from multiple areas (different latents) shall be placed on individual cards.
- 13.2.4.7 Multiple lifts of the same latent may be placed on the same card. A notation indicating the order in which they were lifted shall be made on the card.

13.2.5 PROCEDURE 2- CASTING COMPOUNDS:

- 13.2.5.1 Ensure that the surface has been prepared for lifting by removing excess powder.
- 13.2.5.2 Casting material is mixed either by hand or through the use of an extruder gun.
- 13.2.5.3 Casting material is applied to the latent bearing surface in a manner that precludes air pockets. It may be necessary to place the casting material to the side of the latent and then smooth it across the surface.
- 13.2.5.4 The casting material is left in place until solidified.
- 13.2.5.5 It then is removed from the surface and attached to a latent lift card. The appropriate documentation is noted as detailed in 9.2.4.5.

13.2.6 ADDITIONAL INFORMATION:

- 13.2.6.1 Caution should be exercised in using general-purpose tapes (those not developed for lifting latents) as they may cause migration of some latent print ridge detail or may have striations or other imperfections making it hard to do comparisons.
- 13.2.6.2 Lifting should be performed after any necessary photography. The analyst's training and experience will determine the use and/or sequence of the lifting and photographic processes.

13.2.6.3 Store lifting mediums and casting compounds in a cool dry place.

13.2.6.4 Dispose of lifting mediums and casting compounds in the trash.

13.2.7 CONTROLS:  
Not applicable

13.2.8 SAFETY:  
There are no known health hazards associated with the use of lifting mediums or casting compounds.

13.2.9 REFERENCES:  
Scott's Fingerprint Mechanics, Robert D. Olsen, (1978). Pages 369-387.  
Fingerprint Techniques, Andre, A. Moenssens, (1971). Pages 109-112.  
Friction Ridge Skin, James F. Cowger, (1983). Pages 85-88.  
Manual of Fingerprint Development Techniques Home Office Police Scientific Development Branch (1998).

### 13.3 POWDER DETECTION METHODS

13.3.1 BACKGROUND:  
Many commercially produced latent print powders are available and no powder is universally applicable to all types of non-porous surfaces. Most analysts stock a variety of different types and colors of powders as well as a variety of brushes for specialized applications. Powder particles physically adhere to latent print residue allowing the latent print to be visualized. This coloring of the friction ridge residue occurs because the residue has greater adhesion properties than the substrate.

13.3.2 SCOPE:

13.3.2.1 Latent print powders are used to develop invisible ridge detail, improve contrast of visible ridge detail, and to facilitate lifting and preservation of fingerprint evidence from non-porous surfaces.

13.3.2.2 The type of powder that is selected is dependent upon:

13.3.2.2.1 Whether resulting latents will be photographed. If so, a powder color that contrasts with the surface is often desirable.

13.3.2.2.2 The nature of the surface to be processed. Traditional powders are often most effective on non-textured surfaces while magnetic powders are often most effective on plastics and textured surfaces. The use of

magnetic powders and wands should generally be avoided on substrates that contain iron. Fluorescent powders tend to have limited use. They are useful on multicolored surfaces or surfaces with a light texture that doesn't accept magnetic powder well.

13.3.2.3 The type of applicator selected is dependent upon:

13.3.2.3.1 The size of area to be dusted. Larger brushes are ordinarily used for large areas and smaller brushes on concentrated work or individual latent prints. Fiberglass brushes are often used for both instances.

13.3.2.3.2 The type of powder to be used. Magnetic wands are used in conjunction with magnetic powders while traditional powders are used with a variety of brushes. Traditional fluorescent powders are applied with a feather brush and their application requires the use of an ALS.

13.3.2.4 The prior use of cyanoacrylate esters often increases the adhesion of powders to latent print residue.

13.3.2.5 Powder processing is not suitable for surfaces that are wet, tacky, or exceptionally rough and is generally the last step in the latent print processing sequence.

13.3.2.6 Best practice dictates that disposable powders and brushes be employed in cases with known blood or other biological contaminants. Should disposable brushes/powders be employed, a notation to that effect should be made in the case notes.

### 13.3.3 EQUIPMENT AND MATERIALS:

Hood/exhaust vents/particulate filters

Traditional, magnetic, and fluorescent powders

Magnetic wand, feather brush, fiberglass brush, animal hair, etc.

Alternate light source

Filtered goggles

### 13.3.4 PROCEDURE 1 - TRADITIONAL POWDERS:

13.3.4.1 A variety of brushes or applicators may be utilized with the exception of magnetic wands.

13.3.4.2 Apply a small amount of powder to the brush and remove excess powder.

13.3.4.3 Powder should generally be applied to the surface in a smooth circular motion with only the tips of the brush touching the surface. Once the direction of ridge flow can be established, powdering should proceed by following the ridge flow until optimal development is achieved.

13.3.4.4 The adherence of powder to a latent print may be enhanced by utilizing the "huffing technique." i.e. gently breathing on the surface while dusting for latent prints, which sometimes adds

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 46 of 119

moisture to the latent print residue, thus enabling the powder to adhere more effectively. All visible moisture should be evaporated prior to powder application.

13.3.4.5 If too much powder has been applied, it may be possible to remove excess powder by tapping the object, blowing air over the surface, or by brushing it out.

13.3.4.6 Developed prints are evaluated to determine their suitability for comparison.

13.3.5.7 Prints deemed to be of value are marked and may be photographed or lifted.

### 13.3.5 PROCEDURE 2 - MAGNETIC POWDERS:

13.3.5.1 Magnetic powders generally utilize a magnetic wand in their application.

13.3.5.2 The wand is dipped into the magnetic powder where the powder is picked up by the tip of the wand. The powder actually forms a bristle-less brush that is then applied directly to the surface. The actual wand should not come in contact with the surface.

13.3.5.3 The application of magnetic powders is similar to the dusting method described in 13.3.4.3 & 13.3.4.4.

13.3.5.4 The plunger located at the end of the brush is pulled to its fully extended position to release the powder from the tip of the brush.

13.3.5.5 Excess powder may be removed by passing a wand over the surface without making contact.

13.3.5.6 Developed prints are evaluated to determine their suitability for comparison.

13.3.5.7 Prints deemed to be of value are marked and may be photographed or lifted.

### 13.3.6 PROCEDURE 3 - FLUORESCENT POWDERS:

13.3.6.1 A variety of brushes or applicators may be utilized.

13.3.6.2 Lightly dip the brush into the powder. Remove excess powder. A very small amount of fluorescent powder goes a long way.

13.3.6.3 If possible, it is best to use an ALS while applying the powder. This will prevent over powdering and loss of ridge detail. The application of fluorescent powders is similar to the dusting methods described in 13.3.4.3 & 13.4.4.4.

13.3.6.4 Developed prints are evaluated to determine their suitability for comparison.

13.3.6.5 Prints deemed to be of value are marked and may be photographed or lifted. When photographing latents developed with fluorescent powders, it is necessary to use an ALS and a camera filter that corresponds to the color of viewing goggle utilized with the ALS. It is necessary to use black latent lift cards with fluorescent powders.

### 13.3.7 ADDITIONAL INFORMATION:

- 13.3.7.1 Occasionally, latent quality may be enhanced by repeated powdering and lifting of the same area.
- 13.3.7.2 An ample number of appropriate brushes will help preclude cross-contamination of powders and brushes.
- 13.3.7.3 When powder-processing evidence known to be biologically contaminated, every effort shall be made to avoid cross contamination by utilizing previously unused brushes and powder. Brushes and powder will be discarded after use on contaminated items. Magnetic wands will be disinfected.
- 13.3.7.4 Powders stored in a cool dry place have an indefinite shelf life.
- 13.3.7.5 Dispose of powders in the trash.

### 13.3.8 CONTROLS:

Test impressions are generally not applicable. However, when there is doubt as to the suitability of a powder for processing a particular surface a test impression should be made on a similar surface if available. If a similar surface is not available, then an area of the suspected surface may be explored "blindly" (i.e. wiped clean and used for testing). This test impression shall be destroyed immediately after it has served its purpose, its use shall be documented in the case notes

### 13.3.9 SAFETY:

- 13.3.9.1 Safety concerns when using commercial fingerprint powders are minimal.
- 13.3.9.2 Analysts are required to use the hoods or exhaust vents positioned at each workstation when performing powdering and lifting in the laboratory.
- 13.3.9.3 When fingerprint powders are to be used for an extended period of time, a dust mask or half face respirator with dust filters should be worn to minimize the inhalation of the powder particles.
- 13.3.9.4 Persons using fingerprint powders should monitor reactions (if any) to the fingerprint powders.

### 13.3.10 REFERENCES:

Scott's Fingerprint Mechanics, Robert D. Olsen, (1978), pages 209-235.

Fingerprint Techniques, Andre A. Moenssens, (1971), pages 106-109 and 112-114.

Friction Ridge Skin, James F. Cowger, (1983), pages 85-88.

Manual of Fingerprint Development Techniques Home Office Police Scientific Development Branch (1998).



## 13.4 SMALL PARTICLE REAGENT

### 13.4.1 BACKGROUND:

Two types of small particle reagents (SPR) are available for use, traditional SPR which consists of a suspension of fine molybdenum disulfide ( $\text{MoS}_2$ ) particles in a detergent solution and commercially available white SPR. These solutions work like a liquid fingerprint powder by adhering to the fatty portion of the latent print residue resulting in a gray or white colored latent.

### 13.4.2 SCOPE:

13.4.2.1 Small particle reagent is used to develop latent prints from a variety of surfaces including adhesives and non-porous items that are or have been wet.

13.4.2.2 The color of SPR should be chosen to contrast with the background.

13.4.2.3 SPR may be used by dipping or spraying. Dipping is the preferred method as spraying is less sensitive. It is, however, difficult to prevent damage to fingerprints located on the lower side of an article in a dish and spraying is a valid alternative when processing large items, vehicles, or responding to crime scenes.

13.4.2.4 Surfaces that need other forensic examinations such as biology, questioned document, or trace examinations should be carefully evaluated prior to processing to determine if the SPR procedure will have an impact on subsequent examinations.

### 13.4.3 EQUIPMENT AND MATERIALS:

Beaker  
Balance  
Magnetic stirrer/stirring bar  
Spray bottles  
Processing tray

### 13.4.4 REAGENTS:

Commercially available white SPR  
Molybdenum Disulfide ( $\text{MoS}_2$ )  
Photo Flo 200  
Distilled water

#### Small Particle Reagent Working Solution:

1. Place a 1500 ml beaker on magnetic stirrer base.
2. Add 1000 ml of distilled water to the beaker.
3. Place a magnetic stirring bar in the beaker.
4. Dissolve 30g of  $\text{MoS}_2$  in the water ( $\text{MoS}_2$  may be purchased in 30g bottles).

5. Add three to four drops of Photo Flo 200 to the solution.

**13.4.5 PROCEDURE 1 - DIPPING METHOD:**

13.4.5.1 Shake or stir the SPR thoroughly and pour the solution into a tray.

13.4.5.2 Add the item to be processed to the solution. The item should be submerged.

13.4.5.3 Agitate the solution in the tray for 2-3 minutes, remove the item from the SPR and gently rinse with tap water.

13.4.5.4 Allow the surface to dry (if feasible).

13.4.5.5 Developed prints are evaluated to determine their suitability for comparison.

13.4.5.6 Prints deemed to be of value are marked and may be photographed or lifted. Depending on the circumstances, the item may or may not be dried prior to lifting.

**13.4.6 PROCEDURE 2 - SPRAY METHOD:**

13.4.6.1 Place the SPR into a spray bottle and shake thoroughly. The bottle should be shaken often to keep the MoS<sub>2</sub> in suspension.

13.4.6.2 Spray the SPR onto the item being examined. If the location of the latent print is known, spray the area above the prints and allow the SPR to flow over the prints. Otherwise, spray the area to be examined starting at the top and working downwards.

13.4.6.3 Gently rinse the processed area with tap water and allow it to dry (if feasible).

13.4.6.4 Developed prints are evaluated to determine their suitability for comparison.

13.4.6.5 Prints deemed to be of value are marked and may be photographed or lifted. Depending on the circumstances, the item may or may not be dried prior to lifting.

**13.4.7 ADDITIONAL INFORMATION:**

13.4.7.1 Pre-mixed molybdenum has an indefinite shelf life. The shelf life of the SPR working solutions is at least six months, but shall be tested prior to each use.

13.4.7.2 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

**13.4.8 CONTROLS:**

13.4.8.1 Testing of SPR is performed each day prior to use.

13.4.8.2 This test involves the making of a quality latent print on a test surface similar to the one being examined. The area surrounding the intentionally deposited latent print shall serve as a negative control.

13.4.8.3 The test print is exposed to the SPR in the same manner as the questioned surface.

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 50 of 119

13.4.8.4 An analyst shall not proceed with the processing of the evidence until a control test bearing positive results (development of a gray colored latent with traditional SPR or a white colored latent with white SPR) and a negative control test (minimal background development) has been carried out and documented in the laboratory case notes.

#### 13.4.9 SAFETY:

There does not appear to be any health hazards associated with small particle reagent, but the process should be monitored to see if there are any allergies. Lab coats, gloves, and safety glasses should be worn.

#### 13.4.10 REFERENCES:

Manual of Fingerprint Development Techniques, British Home Office, (1998), chapter 4.

Advances in Fingerprint Technology, Henry C. Lee and R.E. Gaensslen, (1991), pages 82-83.

Technical Notes #1-2757, Lightning Powder Co.

### 13.5 STICKY-SIDE POWDER

#### 13.5.1 BACKGROUND:

Processing adhesives on the sticky sides of tape and other items, such as labels, presents problems in processing. The traditional powdering methods will not work (unless modified) because the adhesive properties cause the powder to obscure latent print deposits. Sticky-side powder is a liquid fingerprint detection method that develops latent prints when applied to adhesive surfaces. Sticky-side powder detects the fatty/oily and/or epithelial cells often left when handling adhesive surfaces.

#### 13.5.2 SCOPE:

13.5.2.1 Sticky-side powder is used to process adhesives. Due to the color of the resulting latent print, sticky-side powder may be more appropriate for certain types of tapes than for others (e.g. masking tape vs. electrical tape).

13.5.2.2 When the item to be processed contains both an adhesive side and a non-porous side, the non-porous side should be processed prior to the application of sticky-side powder.

13.5.2.3 Sticky-side powder can be used in two ways, the powder solution can be painted on, or the surface can be immersed in an aqueous solution containing the powder solution.

13.5.2.4 Surfaces that require other forensic examinations, such as trace or biology, should be carefully evaluated prior to processing to

determine if this procedure will have an impact on subsequent examinations.

13.5.2.5 The following procedure provides two formulations for sticky-side powder; "Sticky-Side Powder Working Solution" & "Sticky-Side Powder Equivalent Working Solution." Either may be used dependent upon examiner preference.

#### 13.5.3 EQUIPMENT AND MATERIALS:

Balance  
Small glass beaker  
Stir rod  
Soft brush (animal hair, paint brush, etc.)  
Glass tray

#### 13.5.4 REAGENTS:

Sticky-Side powder  
Photo-Flo  
Non-magnetic Powder  
Liqui-Nox detergent or equivalent  
Tap or distilled water

##### Sticky-Side Powder Working Solution:

1. Mix a solution of water and Photo-Flo in a glass beaker in a 1:1 ratio.
2. Mix approximately equal amounts of sticky-side powder into the Photo-Flo solution to make a liquid that has the consistency of paint. Mix a volume suitable for the application at hand.

##### Sticky-Side Powder Equivalent Working Solution:

1. Measure out 0.5g of non-magnetic fingerprint powder and place in a glass beaker.
2. Add 1 ml of water.
3. Add 1 ml of Liqui-Nox or other equivalent detergent.
4. Thoroughly mix the liquid and fingerprint powder.

#### 13.5.5 PROCEDURE:

13.5.5.1 The reagent is painted onto the adhesive surface with soft brush or the item may be submersed in the solution. When using the submersion method, ensure that the adhesive side is up as some agitation may be necessary.

13.5.5.2 Allow the reagent to remain on the surface for 10 to 20 seconds.

13.5.5.3 Rinse with water.

13.5.5.4 Examine the adhesive surface for latent prints. The surface may be reprocessed to improve contrast and/or make the latent print(s) darker.

13.5.5.5 Allow the surface to dry thoroughly.

13.5.5.6 Any suitable latent prints are marked and photographed or covered with a protective cover such as lifting tape or clear plastic.

13.5.6 ADDITIONAL INFORMATION:

13.5.6.1 Pre-mixed sticky-side powder has an indefinite shelf life. The working solution shall be mixed prior to each use.

13.5.6.2 Working solution may be rinsed down the drain or disposed of in the trash.

13.5.7 CONTROLS:

13.5.7.1 Testing of sticky-side powder is performed each day prior to use.

13.5.7.2 This test involves the making of a quality latent print on a test surface similar to the evidence being examined and following the processing procedure. The area surrounding the intentionally deposited latent print shall serve as a negative control.

13.5.7.3 An analyst cannot proceed with the processing of the evidence until a control test bearing positive results (development of a print) and a negative control (minimal background development) has been carried out and documented in the laboratory case notes.

13.5.8 SAFETY:

When using sticky-side powder in the previously described manner, there does not appear to be a significant health hazard. When using the powder in the dry form, precautions should be taken to prevent the powder from becoming airborne and possibly inhaled. Small amounts of sticky-side powder can be safely washed down the drain, while larger amounts should be collected in a suitable container for disposal.

13.5.9 REFERENCES:

Journal of Forensic Identification, Vol. 44, No. 2, "Sticky-Side Powder: The Japanese Solution", Darren S. Burns, pages 133-138.

"Sticky-Side Powder", Technical Note, Lightning Powder Co., (April, 1994).

**13.6 TAKING KNOWN EXEMPLARS (REFERENCE STANDARDS)**

13.6.1 BACKGROUND:

Known exemplars (reference standards) is a term used to describe friction ridge impressions that are purposely made. These impressions may be made using a number of techniques, including, but not limited to, traditional ink, live scan, and powder/adhesive lift methods. The goal

of the process is to produce legible impressions that are suitable for classification and/or comparison.

13.6.2 SCOPE:

13.6.2.1 The following techniques are used when analysts are called upon to take fingerprints of living and/or deceased persons. It is up to the analyst's discretion to determine the appropriate methods for the given circumstances.

13.6.2.2 The section on post-mortem fingerprinting does not signify that the procedures be mandated to the extent that it precludes the use of variations of the procedures or different procedures for recording impressions. Each case is unique as to its requirements and it is up to the analyst to determine the procedure appropriate for the given circumstances. The printer's task is to obtain usable prints; any reasonable technique that accomplishes this is acceptable.

13.6.3 EQUIPMENT AND MATERIALS:

- Black printers ink
- Brayer & inking plate
- Porelon pad
- Black fingerprint powder
- Fiberglass brush
- Fingerprint cards/paper
- Fingerprint stand
- Adhesive lifts/covers
- Needle and syringe
- Fingerprinting spoon
- Protective apparel (lab coat, safety glasses, face shield etc.)

13.6.4 REAGENTS:

- Post-mortem injection solution (tissue builder, water, air etc.)

13.6.5 PROCEDURE 1 - KNOWN EXEMPLARS:

13.6.5.1 Insure that the area to be printed is dry and free of debris.

13.6.5.2 Inked Fingerprints

13.6.5.2.1 Place the fingerprint card in the cardholder.

13.6.5.2.2 Beginning with the right thumb, roll the thumb from nail-bed to nail-bed on an inking plate or Porelon pad. Roll the thumb in the same manor on the fingerprint card in the space marked "1. R. Thumb." Roll the thumb with even pressure to avoid smearing.

13.6.5.2.3 Continue this procedure for each finger ensuring the prints are placed in the corresponding box on the fingerprint card.

13.6.5.2.4 If a mistake is made, the analyst may affix an adhesive tab over the error and roll a new print or destroy the card.

13.6.5.2.5 Ink the right and left thumbs and place a plain impression in the corresponding box at the bottom of the fingerprint card. Repeat the procedure with the right and left four fingers simultaneously placing plain impressions in the corresponding boxes at the bottom of the fingerprint card.

13.6.5.2.6 If an amputation, deformity, or injury makes it impossible to print a finger, make a notation to that effect in the individual finger block.

### 13.6.5.3 Inked Palm Prints

13.6.5.3.1 Place a piece of white paper or palm print card around a cylindrical object (piece of pipe, cardboard tube etc.).

13.6.5.3.2 Using a brayer, apply a thin coat of ink to the palmar friction ridges from the wrist to the tips of the fingers.

13.6.5.3.3 Place the wrist of the inked palm on the paper and roll the cylinder back toward the subject while applying pressure to the palm. This method will produce quality ridge detail for the entire palmar surface, even hard to capture areas such as the medial and proximal phalanges and the center portion of the palm.

13.6.5.3.4 Individually ink and roll the thenar and hypothenar portions of the palm using the inking plate. The sides of the hand are placed on the inking plate at an approximate 45° angle and partially rolled to ink the correct portion of the palm. The same motion is then repeated to transfer the ink to the palm print sheet. These impressions may be placed on the same sheet if there is adequate room.

13.6.5.3.5 Repeat the above procedure for the other hand.

### 13.6.5.4 Complete Friction Ridge Exemplars.

13.6.5.4.1 Complete friction ridge exemplars are often referred to as major case prints. They consist of recordings of all friction ridge skin on the palmar surface of the hands and on occasion, the plantar portion of the feet. A complete set of palmar major case prints includes a set of rolled fingerprints, palm prints, sides of palms, sides of fingers (full length), and finger tips.

13.6.5.4.2 These prints may be obtained through traditional inking methods or by using the black powder/adhesive lift method.

### 13.6.5.5 Black Powder/Adhesive Lift Method

13.6.5.5.1 Lightly powder the portion of friction ridge skin to be printed using a fiberglass brush and black powder.

13.6.5.5.2 Choose an adhesive lift of appropriate size and remove the backing.

13.6.5.5.3 Place the powder-processed skin onto the adhesive lift and ensure that it makes good contact.

13.6.5.5.4 Carefully remove the adhesive from the skin and smooth an acetate cover over the lift avoiding creases and air pockets.

13.6.5.6 All exemplars should be marked with the date, analyst's name, case number (if known) and subject's name (if known).

#### 13.6.6 PROCEDURE 2 – POST-MORTEM EXEMPLARS

13.6.6.1 Prints may be recovered from the deceased in the same manner as stated above. However, due to injury, decomposition or other circumstances, traditional methods may not yield satisfactory results.

13.6.6.2 Examine the remains to determine the appropriate method.

13.6.6.3 Clean the remains with a soft brush or cloth and warm water.

13.6.6.4 Dry the friction ridge areas to be printed.

13.6.6.5 Choose an appropriate post-mortem method. It is up to the analyst to determine the appropriate procedure for the given circumstances. The following are recommendations only:

13.6.6.5.1 Printing the Recently Deceased

13.6.6.5.1.1 If the body has been refrigerated, it is helpful to allow it to warm near room temperature prior to printing. This will reduce condensation that may interfere with the printing process.

13.6.6.5.1.2 If rigor mortis has set in, attempt to "break the rigor" by forcefully bending the joints back and forth.

13.6.6.5.1.3 If the fingers have begun to wrinkle due to decomposition or exposure, an attempt should be made to pull the skin tight while taking the impression.

13.6.6.5.1.4 If complete impressions still cannot be obtained, this condition may be corrected through the use of a commercially available post mortem injection solution.

13.6.6.5.1.4.1 Fill a syringe with the post mortem injection solution.

13.6.6.5.1.4.2 Insert the needle just below the skin at the distal joint of the finger and into the distal phalanx area. Inject the solution until the pattern is rounded out. Care should be



taken to prevent the needle from puncturing the skin after the initial insertion. If necessary, a string may be tied just above the site to prevent the solution from leaking out.

13.6.6.5.1.5 Print the finger as outlined in one of the above methods.

13.6.6.5.2 Printing Badly Decomposed or Macerated Remains

13.6.6.5.2.1 In cases of advanced decomposition or extended periods of immersion, it is common for the epidermal layer of skin to separate from the dermis.

13.6.6.5.2.2 Wash and dry the friction ridge skin.

13.6.6.5.2.3 Attempt to photograph and/or record with ink or powder methods.

13.6.6.5.2.4 If the separated friction ridge skin is too fragile to work with, it may be cleansed, flattened under a piece of glass, and photographed.

13.6.6.5.2.5 Occasionally, a large portion of the epidermis separates in the form of an "epidermal glove." If this occurs, the skin may be placed on the analyst's gloved hand and the impressions recorded in a traditional fashion. It may be necessary to excise the skin from the underlying tissue if it is still partially attached.

13.6.6.5.2.6 If the epidermal layer is no longer available, it may still be possible to obtain usable prints by photographing the dermis and/or using the black powder lift method.

13.6.6.5.3 Printing Mummified Remains

13.6.6.5.3.1 As the drying process occurs, friction ridge areas may become shrunken, hard, dry, and deeply creased making fingerprinting via traditional means impossible.

13.6.6.5.3.2 Depending on the circumstances, an analyst may attempt traditional ink and/or powder lift methods, photography, casting, or re-hydration techniques.

13.6.6.5.3.2.1 See literature for re-hydration solutions.

13.6.6.5.3.2.2 If re-hydration is successful the tissue may be printed as

Property of Idaho State Police Forensic Services  
Uncontrolled Internal Copy  
OBSOLETE DOCUMENT (1/16/2016)

outlined in one of the above methods.

13.6.6.5.4 Printing Burned Remains

13.6.6.5.4.1 Remove hardened and partially loosened skin by gently twisting.

13.6.6.5.4.2 Examine the underside of the skin for friction ridges.

13.6.6.5.4.3 Gently clean the skin using a soft brush and warm water.

13.6.6.5.4.4 Allow the skin to dry.

13.6.6.5.4.5 Photograph and/or attempt to ink, powder and lift, or cast.

13.6.6.6 Examine impressions as soon as they are obtained to ensure that adequate clear impressions have been obtained.

13.6.7 CONTROLS:

Not applicable

13.6.8 SAFETY:

13.6.8.1 All human tissue shall be treated as if infectious.

13.6.8.2 Gloves, eye protection, lab coat, and/or a protective disposable apron shall be worn at all times when working with any body parts.

13.6.8.3 Utensils shall be disposed of or cleaned and disinfected after use. Surfaces will be disinfected with a 10% bleach solution or commercially available equivalent.

13.6.9 REFERENCES:

Friction Ridge Skin, Comparison and Identification of Fingerprints, James F. Cowger (1993) Chapter 2 *Taking Inked Prints*, pages 9-33,

The Science of Fingerprints, U.S. Department of Justice, F.B.I. Laboratory Division, (1984), pages 111-157.

Scotts Fingerprint Mechanics, Robert D. Olsen, SR (1977), pages 55-92.

## 14 CHEMICAL METHODS

### 14.1 AMIDO BLACK BLOOD PRINT PROCESSING

#### 14.1.1 BACKGROUND:

Amido Black is also known as Amido Black 10B, Amido Black 12B, Naphthol Blue Black, or Napthalene Black. Amido black is a dye that stains the protein portion of blood a blue-black color.

#### 14.1.2 SCOPE:

14.1.2.1 Blood contaminated prints may be processed with amido black to detect faint deposits of friction ridge skin impressions. It is generally used on dried blood stains on non-porous surfaces, but has been successful in developing prints on some semi-porous and porous surfaces as well. When used on porous or semi porous surfaces consideration should be given for the potential of excessive background staining.

14.1.2.2 Amido black will not detect the normal constituents of latent prints and therefore must be used in the proper sequence with other latent processing methods.

14.1.2.3 The amido black process utilizes a working solution, a rinse solution, and a wash solution (distilled water). Blood must be fixed prior to the application of amido black to prevent the liquid solutions used in the process from washing away some or all of the blood deposits.

14.1.2.4 Bloodstains must be carefully examined and evaluated to preclude destruction of potentially valuable evidence. Any samples to be used for the biological examination of blood deposits or trace analysis should be collected prior to enhancement. It is often necessary to coordinate with investigators and/or other laboratory sections (biology for example) to determine which procedures may provide the most valuable findings.

#### 14.1.3 EQUIPMENT AND MATERIALS:

Balance, magnetic stirrer/stirring bar  
Pipettes  
Beakers  
Graduated cylinder  
Appropriately sized storage bottles  
Squirt bottles

#### 14.1.4 REAGENTS:

Amido Black  
Glacial acetic acid  
Methanol

Distilled water

Amido Black Working Solution:

1. Weigh out 3-5 grams of amido black and place in a clean, dry beaker.
2. Measure out 100 ml of acetic acid and add to the amido black.
3. Measure out 900 ml of methanol and add to the beaker containing the amido black and acetic acid.
4. Stir the solution with a magnetic stirrer for thirty minutes and transfer the solution to a clean storage bottle.

Amido Black Rinse Solution (de-stain):

1. Measure out 100 ml of acetic acid and pour into a clean, dry glass beaker.
2. Measure the 900 ml of methanol and add it to the beaker.
3. Stir the solution for two to three minutes and transfer the solution to a clean, dry storage bottle.

#### 14.1.5 PROCEDURE:

- 14.1.5.1 Determine if samples for biology should be taken prior to processing.
- 14.1.5.2 Conduct control tests using prepared blood slides stored in the laboratory refrigerator.
- 14.1.5.3 Fix impressions using heat, methanol, or cyanoacrylate. Blood can be fixed to an object by heating in a 100° centigrade oven for thirty minutes (restricted to non-heat sensitive objects). Methanol may be sprayed or pipetted over the item. The first amido black rinse that contains methanol will suffice for this fixing rinse. Cyanoacrylate is an effective method for non-porous evidence as it will fix all possible latent prints not just those contaminated with blood.
- 14.1.5.4 Immerse the item in the amido black working solution for two to three minutes. Alternatively, the item may be sprayed or irrigated with the amido black working solution.
- 14.1.5.5 Immerse or irrigate the item with the de-stain rinse solution to remove the excess dye.
- 14.1.5.6 Resulting latent prints are a dark blue-black. The above process may be repeated to improve contrast.
- 14.1.5.7 Immerse or irrigate the surface with distilled water wash (optional).
- 14.1.5.8 Allow the item to dry thoroughly.
- 14.1.5.9 Developed prints are evaluated to determine their suitability for comparison.
- 14.1.5.10 Prints deemed to be of value are marked and photographed.

#### 14.1.6 ADDITIONAL INFORMATION:

- 14.1.6.1 Shelf life of the pre-mixed amido black, working solution, and de-stain is indefinite.

14.1.6.2 Excess reagent shall be collected, when possible, and placed in the hazardous waste container located in the fume hood.

14.1.7 CONTROLS:

14.1.7.1 Testing of amido black is performed each day prior to use.

14.1.7.2 Control tests are performed by the application of the reagent to a slide prepared with known blood. For safety reasons, analysts *will not* prepare friction ridge impressions made with blood. A smear will be applied to the slide instead. The area surrounding the intentionally deposited blood smear shall serve as a negative control.

14.1.7.3 An analyst shall not proceed with the processing of the evidence until a control test bearing positive results (known blood staining a blue-black color) and a negative control (minimal background staining) has been carried out and documented in the laboratory case notes.

14.1.8 SAFETY:

14.1.8.1 Gloves, lab coats, goggles, and respirators, (if there is a chance of the reagents becoming airborne) are worn when mixing or using Amido Black.

14.1.8.2 Glacial acetic acid is corrosive and extremely irritating to the eyes and respiratory system. Avoid breathing the vapors and use in a fume hood, with a respirator, or with adequate ventilation. Glacial Acetic Acid will cause burns if it comes in contact with skin.

14.1.8.3 Methanol is *flammable*. It needs to be handled carefully with gloves during the mixing and use of Amido Black. Methanol is toxic in quantities as small as 30 ml and should not be allowed to come in contact with the skin, eyes, or mouth. It is possible for methanol to be absorbed through the skin. If methanol comes into contact with the eyes or mouth, the area should be flushed with generous amounts of water and a doctor may be consulted. Inhalation of methanol vapors should be kept at a minimum and the solution should be used in a hood or well-ventilated area.

14.1.8.4 In addition, analysts must be aware of the biological hazards associated with blood and other body fluids and take extra precautions to protect themselves.

14.1.9 REFERENCES:

Manual of Fingerprint Development Techniques, British Home Office, (1998).

Journal of Forensic Identification, Vol. 45, No. 5 Sept/Oct 1995, "Superglue of Latent Shoe Prints in Blood Prior to Processing", pages 498-50.

Proceedings of the International Forensic Symposium on Latent Prints, "Enhance Latent Prints in Blood With New Staining Techniques", Paul Norkus and Kevin Noppinger, page 147.

## 14.2 CYANOACRYLATE ESTER

### 14.2.1 BACKGROUND:

Cyanoacrylate ester (CAE), also referred to as "superglue," is sold as a number of brands and in a number of viscosities. Items that are to be processed with CAE need to be exposed to an atmosphere rich in CAE fumes. This may be accomplished through the use of a fuming chamber, CAE fuming wand, or vacuum chamber.

### 14.2.2 SCOPE:

14.2.2.1 Fuming with cyanoacrylate ester (CAE) is a process that is used to visualize latent print deposits on non-porous and some semi-porous objects. CAE processing also prepares the surface for the acceptance of powders and dye-stains that may enable further visualization of the latent prints.

14.2.2.2 When CAE vapors contact moisture and other components of friction ridge residue, the cyanoacrylate ester polymerizes fixing the latents to the surface. This makes them more stable and less easily damaged.

14.2.2.3 The process is temperature, humidity, and pressure sensitive.

14.2.2.4 Objects that need additional forensic examinations such as trace or questioned document examinations should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

### 14.2.3 EQUIPMENT AND MATERIALS:

Fuming chamber (computerized)

Relatively airtight container such as a tank or sealed plastic bag

Vacuum chamber

CAE fuming wand

Cups/warm water (optional)

Low temperature heating element (optional)

Disposable aluminum dishes

### 14.2.4 REAGENTS:

Cyanoacrylate gel or liquid

One shot fuming kit or equivalent

CAE cartridges

### 14.2.5 PROCEDURE 1 - TRADITIONAL FUMING CHAMBER:

- 14.2.5.1 Select the appropriately sized fuming chamber.
- 14.2.5.2 Place the surface to be processed in the chamber (suspend if possible).
- 14.2.5.3 Add control test.
- 14.2.5.4 Add humidity to the chamber via cups of hot water (larger chambers will require more cups, smaller chambers fewer).
- 14.2.5.5 Allow the chamber to warm (if necessary) and humidity to build (80 degrees Fahrenheit and 80 % humidity is optimal but satisfactory results may be obtained at varying temperatures and humidity levels).
- 14.2.5.6 Add the CAE source.
  - 14.2.5.6.1 Hot Plate Method - plug in the hot plate and place in the chamber. Add an approximately 2-3 cm in diameter pool of liquid CAE to a disposable aluminum dish and place on the hot plate.
  - 14.2.5.6.2 Gel Packet Method - open and add one or more foil CAE gel packets (dependent on size of chamber, fuming rate, and analyst's preference) to the chamber. Once the gel is exposed to the air, the CAE will begin to vaporize at a controlled rate.
  - 14.2.5.6.3 "ONE SHOT" fuming kits - place the "activator solution" in the jar provided. Add the "activator canister" to the solution. Empty the CAE on to the top of the "activator canister." This method is generally reserved for crime scene response.
- 14.2.5.7 Secure the door to the chamber.
- 14.2.5.8 Fuming times will vary by the size of the chamber, the properties of the cyanoacrylate being used, the amount of heat and humidity, and the properties of the evidence being fumed. Control test should be carefully monitored by the analyst to prevent over or under fuming. Proper development is achieved when ridge characteristics on the control turn slightly white in color and begin to show good contrast. In the event of under fuming, the item may be re-fumed.
- 14.2.5.9 When development is complete evacuate the CAE fumes and remove the CAE source from the chamber.
- 14.2.5.10 Remove the item from the chamber and examine for comparable ridge detail.
- 14.2.5.11 Prints may be marked and photographed at this point, but are more commonly further enhanced with powders or dyes prior to preservation.

#### 14.2.6 PROCEDURE 2 –CAE FUMING WAND METHOD

- 14.2.6.1 In a fume hood or other well ventilated area, place a CAE cartridge over the end of the fuming wand. Select cartridge size dependent upon amount and size of evidence.

- 14.2.6.2 Set control level to high and ignite the fuming wand. Fumes should be visible once the wand is hot, approximately 1-2 minutes.
- 14.2.6.3 Lower the heat level if desired.
- 14.2.6.4 Conduct a control test.
- 14.2.6.5 Fume the item by holding the fuming wand approximately 4-8 inches away. Fumes from the wand will rise so it is best to direct the fumes below your item if possible or deflect the fumes toward your item. Do not hold the wand too close to the item or in the same area too long, as damage and/or over development may occur.
- 14.2.6.6 Turn the fuming wand off and allow the unit to cool completely prior to removing cartridges or repackaging.
- 14.2.6.7 Examine item for comparable ridge detail.
- 14.2.6.8 Prints may be marked and photographed at this point, but are more commonly further enhanced with powders or dyes prior to preservation.

#### 14.2.7 PROCEDURE 3 - VACUUM CHAMBER METHOD

- 14.2.7.1 Place items of evidence and controls into the vacuum chamber. It is not necessary to unfold garbage bags or leave large amounts of space between the items. *Do not place pressurize items such as sealed cans, bottles etc. in the chamber as they may explode.*
- 14.2.7.2 Add the CAE source. Foil CAE gel packs are recommended (number is dependent on chamber size and space), but a small dish with liquid CAE may also be used.
- 14.2.7.3 Place the lid on the vacuum chamber and close the release valve.
- 14.2.7.4 Turn on the vacuum pump.
- 14.2.7.5 Open the Gas Ballast Valve about one half turn.
- 14.2.7.6 Open the Isolation Valve (silver lever) to up position. If necessary, press on the lid until the chamber begins to evacuate.
- 14.2.7.7 Close the Gas Ballast Valve.
- 14.2.7.8 Evacuate the chamber to approximately 25 inches of mercury as shown on the chamber gauge.
- 14.2.7.9 Close the Isolation Valve.
- 14.2.7.10 Open the Gas Ballast Valve, wait 2-3 seconds and turn off the pump.
- 14.2.7.11 Close the Gas Ballast Valve.
- 14.2.7.12 Leave the items under vacuum for at least 20 minutes. There is no danger of over fuming.
- 14.2.7.13 Evacuate the chamber by slowly opening the release valve.
- 14.2.7.14 Remove glue and evidence. Examine item for comparable ridge detail.



14.2.7.15 Prints may be marked and photographed at this point, but are more commonly further enhanced with powders or dyes prior to preservation.

14.2.8 PROCEDURE 4 – CYANOACRYLATE FUMING CHAMBER:

14.2.8.1 Turn on power

14.2.8.2 The menu screens are designed to prompt the use of action to be taken to complete a full cycle. Screen is touch operated. Do not tap on screen with any object that could damage it.

14.2.8.3 Upon start-up the unit will load software and self-calibrate.

14.2.8.4 Once running, the unit will prompt the user for each activity.

14.2.8.5 Set the desired humidity level and fuming time. The unit default is 80% relative humidity (RH) for 15 minutes.

14.2.9 ADDITIONAL INFORMATION:

14.2.9.1 In the event of over-fuming, it may be possible to use an adhesive lifting technique (tape, gel lifter etc.) to lift away heavy upper deposits, revealing underlying ridge detail.

14.2.9.2 The “foil packets” may be stored at room temperature and have a shelf life of six months to a year. The shelf life of the “foil packets” can be greatly extended by refrigeration. CAE should be in a gel form, ensure CAE has not dried out/crystallized prior to use. Liquid CAE and cartridges may be stored at room temperature with an indefinite shelf life.

14.2.9.3 CAE may be disposed of in the trash.

14.2.9.4 Analysts shall read the manufacture’s operating instructions for the CAE fuming wand and vacuum chambers prior to initial use of this equipment.

14.2.10 CONTROLS:

14.2.10.1 Testing of CAE and processing are performed at the same time.

14.2.10.2 A quality test print is applied to a non-porous surface and put into the tank in an easily-monitored position with the questioned surface. Placing one’s own fingerprints on a black latent lift card works well for this purpose. The area surrounding the intentionally deposited latent print shall serve as a negative control.

14.2.10.3 When the development of the positive control test is complete, the questioned surface is also finished. Positive results (indicated by development of a white print) and negative results (a lack of background development) shall be documented in the laboratory case notes.

14.2.11 SAFETY:

- 14.2.11.1 CAE fuming should only be conducted in a filtered chamber or well-ventilated area. Precautions should be taken to avoid inhaling or allowing the vapors to contact the eyes, as the vapors can be irritating to the eyes, nose, and throat. Persons wearing contact lenses should not open CAE chambers without taking proper precautions. Non-vented goggles should be worn.
- 14.2.11.2 Precautions include using relatively sealed CAE chambers and evacuating the fumes from the chambers prior to removal of the questioned and test surfaces.
- 14.2.11.3 Gloves should be worn to prevent the cyanoacrylate from contacting the skin. If liquid glue is allowed to contact the skin, adhesion may result. If the skin sticks together, immerse affected areas in warm water. This will loosen the skin so that it can be gently pulled apart.

#### 14.2.12 REFERENCES:

“Methods of Latent Print Development”, Henry C. Lee and R. E. Gaensslen, 1987 Proceedings of the International Symposium on Latent Prints, pages 15-23.

Advances in Fingerprint Technology, Henry C. Lee and R. E. Gaensslen, (1991).

Journal of Forensic Identification, Vol.46, No. 4 July/August, 1996; Vol. 46, No. 1 January/February, 1996.

Coleman Vacu-Print Instructions and Notes, Lightning Powder, (1995).

Manual of Fingerprint Development Techniques, British Home Office, Chapter 4, (1998).

Air Science, Operating Manual: SAFEFUME Cyanoacrylate Fuming Chamber, Rev 2 July-11-2008.

### 14.3 1,8 DIAZFLUOREN-9-ONE (DFO)

#### 14.3.1 BACKGROUND:

1,8 Diazfluoren-9-one is an analogue of the ninhydrin molecule. DFO develops latent prints containing amino acids. Resulting prints must be excited with an alternate light source in order to be visualized.

#### 14.3.2 SCOPE:

- 14.3.2.1 DFO is used to develop prints on porous surfaces such as paper and cardboard.
- 14.3.2.2 DFO will detect latent prints on porous surfaces that ninhydrin will not and the reverse is also true. It does not replace ninhydrin but is used in addition to it.
- 14.3.2.3 DFO should be used after iodine and prior to ninhydrin or physical developer.
- 14.3.2.4 Surfaces that need other forensic examinations such as trace or questioned document examinations should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

#### 14.3.3 EQUIPMENT AND MATERIALS:

- Fume hood
- Balance
- Magnetic stirrer/stirring bar
- Alternate light source/filtered goggles
- Lab oven
- Beaker
- Graduated cylinder
- Pipettes or trays

#### 14.3.4 REAGENTS:

- DFO
- Methanol
- Ethyl acetate
- Acetic acid
- Petroleum ether

##### DFO Stock Solution:

1. In a fume hood, dissolve 0.5 gram of DFO powder in 100 ml of methanol. This may be facilitated by use of a magnetic stirrer.
2. Add 100 ml of ethyl acetate and mix thoroughly.
3. Add 20 ml of acetic acid.
4. Store stock solution in a dark brown glass or polypropylene bottle.

##### DFO Working Solution:

1. Add 220 ml of stock solution to 780 ml of petroleum ether.
2. Mix thoroughly.

If less working solution is desired, halve or quarter the stock solution and petroleum ether accordingly.

#### 14.3.5 PROCEDURE:

- 14.3.5.1 Conduct control tests.
- 14.3.5.2 Pour a sufficient amount of the working solution into a glass tray.

14.3.5.3 Dip or irrigate the evidence with the solution for ten seconds (DFO may also be painted on). Although it is possible to spray this solution, it is *not recommended* due to the health hazards involved and its inability to soak the specimen adequately.

14.3.5.4 Allow to dry for approximately three minutes.

14.3.5.5 Repeat 14.3.5.3 and 14.3.5.4.

14.3.5.6 Apply dry heat.

14.3.5.6.1 When using the fingerprint development chamber, the specimen should be heated for ten minutes at 100° C with a dry heat.

14.3.5.6.2 A hair dryer or dry iron will work as an alternative to an oven. Place a thick towel or other protective material on the counter, followed by the evidence, and then a few paper towels. Apply dry heat to the surface for several minutes. A dry iron can be placed directly on top of the paper towels and used the same as when ironing clothes. One advantage to this method is that it is possible to stop heating and check the progress with an alternate light source. If the latent prints are not very bright, continue to heat. Added heating time may improve resulting print development.

14.3.5.7 DFO-developed latent prints may or may not be visible to the naked eye and should be viewed under an alternate light source. DFO fluoresces when illuminated with monochromatic light in the 485 nm to 510 nm range.

14.3.5.8 Developed prints are evaluated to determine their suitability for comparison.

14.3.5.9 Prints deemed to be of value are marked and photographed using the ALS and a filter on the camera (orange or red).

14.3.5.10 Faint latent prints may be made to fluoresce brighter with a second or third application of DFO. The second and third applications of DFO (if necessary) are performed in the same manner as the first.

#### 14.3.6 ADDITIONAL INFORMATION:

14.3.6.1 Shelf life of pre-mixed DFO is indefinite. The shelf life of the DFO stock solution and working solution is six months.

14.3.6.2 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

#### 14.3.7 CONTROLS:

14.3.7.1 Testing of DFO is performed each day prior to use.

14.3.7.2 This test involves the making of a quality latent print on a test surface similar to the evidence being examined and following the processing procedure. The area surrounding the

intentionally deposited latent print shall serve as a negative control.

14.3.7.3 The test is illuminated with an alternate light source as outlined in 14.3.5.7.

14.3.7.4 An analyst shall not proceed with the processing of the evidence until control tests bearing positive results (fluorescence) and negative results (a lack of background development) have been carried out and documented in the laboratory case notes and on the control tests work sheet.

#### 14.3.8 SAFETY:

14.3.8.1 DFO has not been fully investigated for potential health hazards but is thought to be similar to ninhydrin, which may act as an irritant. Gloves, lab coats, and safety glasses should be worn when mixing and using DFO. The application of the DFO working solution should be performed in a fume hood, well-ventilated area, or while wearing an air-purifying respirator equipped with an organic vapor cartridge.

14.3.8.2 Glacial acetic acid is *corrosive* and extremely irritating to the eyes and respiratory system. Avoid breathing the vapors and use in a fume hood or with adequate ventilation. Glacial acetic acid will cause burns if it comes in contact with skin.

14.3.8.3 Methanol needs to be handled carefully with gloves during mixing and use. Methanol is toxic in quantities as small as 30 ml and should not be allowed to come in contact with the skin, eyes, or mouth. It is possible for methanol to be absorbed through the skin. If methanol comes into contact with the eyes or mouth, the area should be flushed with generous amounts of water and a doctor may be consulted. Inhalation of methanol vapors should be kept at a minimum.

#### 14.3.9 REFERENCES:

Manual of Fingerprint Development Techniques, British Home Office, Chapter 4, (1998).

Technical Notes #1-0038, Lightning Powder Co., 1,8-Diazafluoren-9-One (DFO)

## 14.4 GENTIAN VIOLET

### 14.4.1 BACKGROUND:

Gentian Violet or Crystal Violet, is a biological stain used to dye epithelial cells and fatty components of latent print residues an intense purple color. Due to the toxic nature of this reagent, it should only be

used in small quantities with the appropriate safety precautions observed.

#### 14.4.2 SCOPE:

14.4.2.1 Gentian violet is a dye stain used in the laboratory to visualize latent print deposits on many types of adhesive surfaces.

14.4.2.2 Gentian violet may also be used on small non-porous surfaces contaminated with grease and oils. It is not suitable for water-soluble adhesives or porous surfaces.

14.4.2.3 Surfaces that need other forensic examinations such as biology or trace should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

#### 14.4.3 EQUIPMENT AND MATERIALS:

Balance

Magnetic stirrer/stirring bar

Graduated cylinder

Glass beaker

Glass tray

Storage bottles

#### 14.4.4 REAGENTS:

Gentian Violet or crystal violet

Distilled water

Gentian Violet Working Solution:

1. Weigh out 1 gram gentian violet.
2. Measure 1000 ml of distilled water and pour into glass beaker.
3. Slowly add the gentian violet.
4. Stir for approximately twenty-five minutes or until completely dissolved.

#### 14.4.5 PROCEDURE:

14.4.5.1 Pour a sufficient quantity of working solution into a glass tray.

14.4.5.2 Conduct control tests.

14.4.5.3 Immerse the adhesive substrate into the working solution for 1-2 minutes.

14.4.5.4 Rinse with cool tap water. Developed latents will appear purple in color.

14.4.5.5 The above process may be repeated until optimal development of latents is achieved.

14.4.5.6 Developed prints are evaluated to determine their suitability for comparison.

14.4.5.7 Prints deemed to be of value are marked and may be photographed or lifted.

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 70 of 119

14.4.6 ADDITIONAL INFORMATION:

- 14.4.6.1 Shelf life of pre-mixed gentian violet and working solution are indefinite.
- 14.4.6.2 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

14.4.7 CONTROLS:

- 14.4.7.1 Testing of gentian violet is performed each day prior to use.
- 14.4.7.2 This test involves the making of a quality latent print on a test surface similar to the evidence being examined and following the processing procedure. The area surrounding the intentionally deposited latent print shall serve as a negative control.
- 14.4.7.3 An analyst cannot proceed with the processing of the evidence until control tests bearing positive results (development of a purple print) and negative results (a lack of background development) have been carried out and documented in the laboratory case notes.

14.4.8 SAFETY:

- 14.4.8.1 Gentian violet/crystal violet is a suspected human carcinogen. It is known to affect the kidney, ureter, bladder, and thyroid of animals. It can be harmful if inhaled, and is irritating to the eyes and skin.
- 14.4.8.2 Gentian violet should not be used in large amounts.
- 14.4.8.3 A dust mask or respirator with dust filter should be used when working with the dry form. Gentian violet should be prepared and used in a fume hood or well-ventilated area. The analyst should wear a lab coat, heavy-duty (non-disposable) gloves, and safety glasses.

14.4.9 REFERENCES:

- Chemical Formulas and Processing Guide for Developing Latent Prints, FBI, (1994).
- Lightning Powder Technical Notes, "Crystal Violet," (2000).
- Processing Guide for Developing Latent Prints, "Gentian Violet," USDJ/FBI, (2000).

**14.5 1,2 INDANDIONE**

14.5.1 BACKGROUND:

1,2 Indanedione is an amino acid reagent that is used to develop and visualize latent prints on porous surfaces. It produces pale pink colored

prints upon exposure to ambient light. However, the prints fluoresce strongly when examined using a forensic alternate light source (ALS) with wavelengths between 450nm and 570nm using an orange or red filter. The addition of a Zinc Chloride solution was found to enhance the fluorescence results obtained with the 1,2 Indanedione reagent.

#### 14.5.2 SCOPE:

14.5.2.1 1,2 Indanedione is used to develop prints on porous surfaces such as paper and cardboard. 1,2 Indanedione should be used after Iodine processing and prior to processing with Physical Developer.

14.5.2.2 If used in conjunction with Ninhydrin, it should be used after processing with Iodine and Ninhydrin and prior to processing with Physical Developer.

14.5.2.3 Surfaces that need other forensic examinations such as handwriting analysis, body fluid examinations, or trace examinations should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

#### 14.5.3 EQUIPMENT AND MATERIALS:

Scale  
Graduated cylinders  
Balance  
Magnetic stir bar  
Spatula  
Beaker  
Forensic Alternate Light Source (ALS)  
Laboratory oven and/or Clothing Iron  
Pipettes or trays

#### 14.5.4 REAGENTS:

1,2 Indanedione  
Zinc Chloride  
Methylene Chloride (Dichloromethane)  
Ethyl Acetate  
Glacial Acetic Acid  
Absolute Ethanol  
Petroleum Ether

#### 14.5.5 Mixing Procedure

##### 14.5.5.1 Stock Solution 1:

1,2 Indanedione .	1 gram
Methylene Chloride	30 mL
Ethyl Acetate	60 mL
Glacial Acetic Acid	10 mL
Petroleum Ether	900 mL



10.5.5.1.1 Dissolve 1 gram of 1,2 Indanedione into 30 mL of Methylene Chloride. Next add 60 mL of Ethyl Acetate and stir. Next, add 10 mL of Glacial Acetic Acid followed by 900 mL of Petroleum Ether and stir.

14.5.5.2 Stock Solution 2:

Zinc Chloride	0.4 grams
Absolute Ethanol	10 mL
Ethyl Acetate	1 mL
Petroleum Ether	190 mL

14.5.5.2.1 Dissolve 0.4 grams of Zinc Chloride into 10 mL of Absolute Ethanol. Next add 1 mL of Ethyl Acetate followed by 190 mL of Petroleum Ether and stir.

14.5.5.3 Final 1,2 Indanedione and Zinc Chloride Working Solution:

100 mL of Stock Solution I

8 mL of Stock Solution 2

14.5.5.3.1 Add 8 mL of Stock Solution 2 to 100 mL of Stock Solution 1 and stir. Stock solutions should be stored in dark brown glass bottles in a darkened area. Shelf life of the working solution is approximately 3 months.

14.5.6 PROCEDURE:

14.5.6.1 Dip or irrigate the evidence into with the solution for five seconds (the solution may also be painted on). Although it is possible to spray this solution, it is *not recommended* due to the health hazards involved and its inability to soak the specimen adequately.

14.5.6.2 Allow the item to dry for approximately three minutes and then apply dry heat. When using a fingerprint development chamber, the specimen should be heated for fifteen minutes at 100° C with a dry heat. A hair dryer or dry iron will work as an alternative to an oven. Place a thick towel or other protective material on the counter, followed by the evidence, and then a few paper towels. Apply dry heat to the surface for several minutes. A dry iron can be placed directly on top of the paper towels and used the same as when ironing clothes. One advantage to this method is that it is possible to stop heating and check the progress with an alternate light source.

14.5.6.3 If the latent prints are not very bright, continue to heat. Added heating time may improve resulting print development. 1,2 Indanedione developed latent prints may or may not be visible to the naked eye and should be viewed under an alternate light source. 1,2 Indanedione fluoresces when illuminated with monochromatic light in the 450 nm to 570 nm range using an orange or red barrier filter.

- 14.5.6.4 Prints deemed to be of value should be marked and photographed. Prints developed with 1,2 Indanedione tend to fade over time if exposed to bright light. Therefore, the prints should be photographed as soon as possible after development.
- 14.5.6.5 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

14.5.7 CONTROLS:

- 14.5.7.1 Testing of the 1,2 Indanedione working solution is performed each day prior to use.
- 14.5.7.2 This test involves the making of a quality latent print on a test surface similar to the evidence being examined and following the processing procedure. The area surrounding the intentionally deposited latent print shall serve as a negative control.
- 14.5.7.3 An analyst cannot proceed with the processing of the evidence until control tests bearing positive results (fluorescence) and negative results (a lack of background development) have been carried out and documented in the laboratory case notes.
- 14.5.7.4 The test is illuminated with an alternate light source as outlined in 14.5.6.3.

14.5.8 SAFETY:

- 14.5.8.1 Eye protection, a lab coat, and gloves should be worn. All mixing and application of chemicals should be done inside a ventilated laboratory fume hood. Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

14.5.8.1.1 1,2 Indanedione

May be harmful by; inhalation, ingestion, and skin absorption. May cause skin and eye irritation.

14.5.8.1.2 Zinc Chloride

Hazardous, avoid contact with skin and eyes; known irritant, permeator and corrosive, classified as a possible human mutagen.

14.5.8.1.3 Dichloromethane (Methylene Chloride)

Hazardous, avoid contact with skin and eyes, known; irritant, permeator and corrosive. Inflammation of the eye is characterized by redness, watering, and itching. Classified as a possible human carcinogen.

14.5.8.1.4 Ethyl Acetate

Is hazardous if ingestion or inhalation and slightly hazardous in case of contact with skin or eyes. The substance is toxic to mucous membranes and the upper respiratory tract. blood, kidneys, liver, or the central

nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage.  
(Flammable)

#### 14.5.8.1.5 Glacial Acetic Acid

Glacial acetic acid is *corrosive* and extremely irritating to the eyes and respiratory system. Avoid breathing the vapors and use in a fume hood or with adequate ventilation. Glacial acetic acid will cause burns if it comes in contact with skin.

#### 14.5.8.1.6 Absolute Ethanol

Causes severe eye irritation. Flammable liquid and vapor. Causes respiratory tract irritation. This substance has caused adverse reproductive and fetal effects in humans. May cause central nervous system depression. May cause liver, kidney and heart damage. Causes moderate skin irritation.

#### 14.5.8.1.7 Petroleum Ether

Hazardous in case of eye contact (irritant), ingestion, or inhalation. Slightly hazardous in case of skin contact (irritant, permeator). Flammable.

## 14.6 LEUCOCRYSTAL VIOLET

### 14.6.1 BACKGROUND:

Leucocrystal violet is a biological stain used to dye the blood hemoglobin components of impression residues an intense purple color. Due to the toxic nature of this reagent, it should only be used in small quantities with the appropriate safety precautions observed.

### 14.6.2 SCOPE:

14.6.2.1 Leucocrystal violet is a dye stain used to visualize impression deposits in blood on many types of non-porous and porous surfaces such as some papers, metal and plastic as well as adhesive surfaces.

14.6.2.2 Leucocrystal violet may also be used on small non-porous surfaces contaminated with grease and oils. It is not suitable for water-soluble adhesives.

14.6.2.3 Surfaces that need other forensic examinations such as biology or trace should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

14.6.2.4 The following procedure gives two working formulations for leucocrystal violet. Either "Formula A" or "B" may be used for blood enhancement.

### 14.6.3 EQUIPMENT AND MATERIALS:

Balance  
Magnetic stirrer/stirring bar  
Graduated cylinder  
Glass beaker  
Glass tray  
Storage bottles

### 14.6.4 REAGENTS:

Leucocrystal Violet  
5-sulfosalicylic acid  
3% hydrogen peroxide  
Distilled water

#### 14.6.4.1 Formula "A"

14.6.4.1.1 Dissolve 10g of 5-sulfosalicylic acid in 100ml distilled water.

14.6.4.1.2 Add 400ml 3% hydrogen peroxide to sulfosalicylic acid solution.

14.6.4.1.3 Immediately prior to use, add 0.75g leucocrystal violet to above. Stir the mixture vigorously.

14.6.4.1.4 For ease of use at crime scenes, premix the 5-sulfosalicylic acid and 3% hydrogen peroxide then add premeasured LCV onsite and mix.

#### 14.6.4.2 Formula "B"

14.6.4.2.1 10g 5-sulfosalicylic acid dissolved in 500ml 3% hydrogen peroxide.

14.6.4.2.2 Add 3.7g sodium acetate and 1.0g leucocrystal violet. Stir the mixture vigorously.

### 14.6.5 PROCEDURE:

14.6.5.1 Determine if samples for biology should be taken prior to processing.

14.6.5.2 Conduct control tests using prepared blood slides stored in the laboratory refrigerator.

14.6.5.3 Spray the impression using a fine mist sprayer. Items may also be soaked or the surface flooded with the solution.

14.6.5.4 Development of dark purple impressions should occur in 30 seconds.

14.6.5.5 Developed impressions are evaluated to determine their suitability for comparison.

14.6.5.6 Impressions deemed to be of value are marked and shall be photographed and/or lifted.

### 14.6.6 ADDITIONAL INFORMATION:

- 14.6.6.1 Shelf life of the working solution is approximately 3 months.
- 14.6.6.2 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

#### 14.6.7 CONTROLS:

- 14.6.7.1 Testing of leucocrystal violet is performed each day prior to use.
- 14.6.7.2 This test involves the making of a mark in blood on a slide and following the processing procedure. The area surrounding the intentionally deposited mark shall serve as a negative control.
- 14.6.7.3 An analyst cannot proceed with the processing of the evidence until control tests bearing positive results (development of a purple mark) and a negative results (lack of background development) have been carried out and documented in the case notes .

#### 14.6.8 SAFETY:

- 14.6.8.1 Leucocrystal violet may be harmful by inhalation, ingestion, or skin absorption; may cause skin and eye irritation; may cause irritation to mucous membranes and upper respiratory tract.
- 14.6.8.2 Leucocrystal violet should not be used in large amounts.
- 14.6.8.3 A respirator should be used when working with the dry form. Leucocrystal violet should be prepared and used in a fume hood or well-ventilated area. The analyst should wear a lab coat, heavy-duty (non-disposable) gloves, and safety glasses.
- 14.6.8.4 In addition, analysts must be aware of the biological hazards associated with blood and other body fluids and take extra precautions to protect themselves.

#### 14.6.9 REFERENCES:

Bodziak, William J., "Use of Leucocrystal Violet to Enhance Shoe Prints in Blood", Forensic Science International, Vol. 82, No. 1, September 1996.

Chemical Formulas and Processing Guide for Developing Latent Prints, US Department of Justice, 1994, pp 47-48.

Fisher, John F., "An Aqueous Leucocrystal Violet Enhancing Reagent for Blood Impressions", Symposium on the Forensic Aspects of Footwear and Tire Impression Evidence, FBI Academy, 1994.

## 14.7 NINHYDRIN

### 14.7.1 BACKGROUND:

Ninhydrin (triketohydrindene hydrate) reacts with the amino acids and proteins present in the latent print deposit to produce a characteristic purple color (Rhuemann's Purple). The combination of heat and humidity accelerates the reaction of the amino acids and ninhydrin.

#### 14.7.2 SCOPE:

14.7.2.1 Ninhydrin is the most commonly used method for porous and semi-porous substrates. Excessive background discoloration may occur in substrates composed of a high plant or animal protein content (ex. leather and currency). It is not effective on items that have been wet.

14.7.2.2 Ninhydrin processing should be performed after iodine and DFO processing and prior to 1,2 Indanedione and physical developer.

14.7.2.3 Latent prints composed of blood can often be successfully darkened with the application of ninhydrin. This may be used on porous items as well as non-porous surfaces. To allow for further processing, non-porous surfaces should be processed with cyanoacrylate ester prior to the application of the ninhydrin reagent.

14.7.2.4 Surfaces that need other forensic examinations such as questioned document examinations should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

#### 14.7.3 EQUIPMENT AND MATERIALS:

Balance

Magnetic stirrer/stirring bar

Beaker

Graduated cylinder

Pipettes or trays

Brushes or tongs

Steam iron or fingerprint development chamber

#### 14.7.4 REAGENTS:

N-Hexane

Acetic acid

2-propanol (isopropyl alcohol)

Ninhydrin crystals

Ninhydrin Stock Solution:

1. Place a one-liter beaker on the magnetic stirrer.
2. Add 300 ml of 2-propanol to the beaker.
3. Add 100 ml of acetic acid.
4. Place the stirring bar in the beaker and turn the stirrer on to a low level.

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 78 of 119

5. Add 50g of ninhydrin crystals to the solution. It may take up to two hours for the ninhydrin to dissolve. Cover the beaker to avoid excess evaporation.

Ninhydrin Working Solution:

1. Add 30ml of the ninhydrin stock solution to a one-liter beaker.
2. Fill the beaker to the 1-liter mark with N-Hexane.
3. Stir and clarify with 2-propanol as needed.
4. Upon standing in its storage container, some of the ninhydrin will “fall out of solution” causing a visible yellow layer at the bottom. Do not dip, brush, or spray items with this yellow layer.

14.7.5 PROCEDURE 1 - POROUS SUBSTRATES:

14.7.5.1 Conduct control tests.

14.7.5.2 Saturate the item with the ninhydrin working solution in a fume hood. Dipping or irrigating are the preferred methods, though brushing the solution on works well with large items. Spraying is the least desirable of the application options as this allows the solution to become airborne.

14.7.5.3 Allow the item to dry.

14.7.5.4 Expose the item to a warm (approximately 80°C) and humid atmosphere (approximately 65%)-This can be accomplished in the fingerprint development chamber or with a hand held steam iron. The moving steam iron should remain approximately 1-2 inches above the surface, never being allowed to touch, as accidental contact will result in excessive discoloration.

14.7.5.5 Developed prints are evaluated to determine their suitability for comparison.

14.7.5.6 Prints deemed to be of value are marked and photographed as they may fade with time and may not be retrievable with reprocessing. It may be possible to increase the contrast between ninhydrin-developed prints and the substrate by black and white photography utilizing a green camera filter or through digital enhancement.

14.7.5.7 It is recommended that the item be re-examined after approximately 24 hours to ensure that no additional latent prints have developed.

14.7.6 PROCEDURE 2 - BLOOD ENHANCEMENT:

14.7.6.1 Determine if samples for biology should be taken prior to processing.

14.7.6.2 Conduct control tests using prepared blood slides stored in the laboratory refrigerator.

14.7.6.3 "Fix" impressions using heat or methanol.

Blood can be fixed to the object by heating in a 100° centigrade oven for one hour (restricted to non-heat sensitive

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 79 of 119

objects). Heat fixing may ruin latent prints that are composed of normal latent print constituents. Methanol may be pipetted over the item and limited to the stain so that the remainder of the surface is unaffected. Three or four applications of methanol are needed to fix the stain. Failure to fix the stain does not always render a lower quality latent print.

- 14.7.6.4 Apply the working solution to the stain and allow the item to remain at room temperature for approximately 48 hours. The ninhydrin will turn the protein component of the blood/serum stain a dark purple and may develop portions of the latent not previously seen.
- 14.7.6.5 Developed prints are evaluated to determine their suitability for comparison.
- 14.7.6.6 Prints deemed to be of value are marked and photographed as they may fade with time and may not be retrievable with reprocessing.

#### 14.7.7 ADDITIONAL INFORMATION:

- 14.7.7.1 Shelf life of pre-mixed ninhydrin is indefinite. The shelf life of the ninhydrin stock solution and working solution is up to one year.
- 14.7.7.2 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

#### 14.7.8 CONTROLS:

- 14.7.8.1 Testing of the ninhydrin working solution is performed each day prior to use.
- 14.7.8.2 This test involves the making of a quality latent print on a test surface similar to the evidence being examined and following the processing procedure. The area surrounding the intentionally deposited latent print shall serve as a negative control.
- 14.7.8.3 An analyst cannot proceed with the processing of the evidence until control tests bearing positive results (development of a purple print) and negative results (minimal background development) have been carried out and documented in the laboratory case notes.

#### 14.7.9 SAFETY:

- 14.7.9.1 Gloves, lab coat, and eye protection shall be worn when using or mixing ninhydrin. Precautions should also be taken to avoid inhalation of the fumes.
- 14.7.9.2 The solvent used in the ninhydrin working solution, Hexane, is *extremely flammable* and the solution is to be used or mixed in a fume hood or in another well-ventilated area. Ensure that



ninhydrin treated items are completely dry prior to exposing to the heat source.

14.7.9.3 Glacial acetic acid is *corrosive* and extremely irritating to the eyes and respiratory system. Avoid breathing the vapors and use in a fume hood or with adequate ventilation. Glacial acetic acid will cause burns if it comes in contact with skin.

14.7.9.4 2-Propanol, also known as Isopropyl Alcohol, is *flammable*. It is an irritant, and can be harmful if inhaled. Avoid breathing the vapors and use in a fume hood or with adequate ventilation.

14.7.10 REFERENCES:

Fingerprint Techniques, Andre A. Moenssens, (1971), pages 122-126.

Friction Ridge Skin, James F. Cowger, (1983), pages 96-98.

Processing Guide for Developing Latent Prints, FBI (2001).

Scott's Fingerprint Mechanics, Robert D. Olsen, (1978), pages 285-288.

**14.8 PHYSICAL DEVELOPER (PD)**

14.8.1 BACKGROUND:

Physical developer is a silver-based aqueous reagent that reacts with lipids, fats, oils, and waxes present in the fingerprint residue to form a silver-gray deposit.

14.8.2 SCOPE:

14.8.2.1 Physical developer is a method used for the development of latent prints on porous substrates. It is not suitable for non-porous surfaces.

14.8.2.2 This method is the final step in the sequential processing of porous items.

14.8.2.3 Physical developer is the only method to show adequate results on paper that has been wet, and has shown good results on paper currency.

14.8.2.4 Surfaces that need other forensic examinations such as body fluid, trace, or questioned document examinations should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

14.8.3 EQUIPMENT AND MATERIALS:

Graduated cylinder

Glass trays

Plastic tongs

#### 14.8.4 REAGENTS:

Physical Developer Kit (parts A & B)

1. Any contamination may ruin the physical developer working solution. To avoid contamination use clean glassware rinsed with tap water, then with distilled water prior to beginning.
2. Add 5 ml of solution A (20% silver nitrate solution) to 90 ml of solution B (reductant solution) in a beaker.
3. Stir the working solution for approximately one minute with a clean glass/plastic stirring rod.
4. Do not mix the working solution until you are ready to use it as it does not have a very long shelf life once mixed.

#### 14.8.5 PROCEDURE:

- 14.8.5.1 Arrange the glass trays in the stainless steel sink so that the evidence can be moved easily from one tray to another in the proper sequence.
- 14.8.5.2 Add the physical developer working solution to its dedicated glass tray.
- 14.8.5.3 Use plastic photographic tongs or plastic forceps without serrated edges to add or remove articles from PD solutions. Do not use metal tools.
- 14.8.5.4 Conduct control tests.
- 14.8.5.5 Immerse the item and gently rock the tray for approximately 5-15 minutes until friction ridge development is complete or adequate time has elapsed (analyst's discretion).
- 14.8.5.6 Remove the item from the physical developer working solution and place into a tray with running tap water. Rinse until the water runs clear.
- 14.8.5.7 Dry completely.
- 14.8.5.8 Developed prints are evaluated to determine their suitability for comparison.
- 14.8.5.9 Prints deemed to be of value are marked and photographed.

#### 14.8.6 ADDITIONAL INFORMATION:

- 14.8.6.1 Cleanliness is important in the physical developer method. A good deal of the instability in the earlier solutions was a result of laboratory equipment that was not spotless. Some contaminants, especially salts, will cause the silver nitrate in the solution to come out of suspension thus spoiling the physical developer solution and perhaps ruining the item being examined. It is important to keep the glassware spotless and rinsed with distilled or de-ionized water prior to use. When washing glassware, use detergent, not abrasive cleaners.

- 14.8.6.2 Physical developer will cause dark stains on many surfaces. Care must be taken to avoid spills in the laboratory. Full strength chlorine bleach will usually remove any stains from counter tops and floors, but the bleach may cause damage to fabrics stained with physical developer.
- 14.8.6.3 Shelf life for ready to use kit (un-mixed) is six months from date of purchase. The reagent shall be mixed upon each use.
- 14.8.6.4 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

14.8.7 CONTROLS:

- 14.8.7.1 Testing of physical developer is performed prior to each use.
- 14.8.7.2 This test involves the making of a quality (oil based) latent print on a test surface similar to the evidence being examined and following the processing procedure. The area surrounding the intentionally deposited latent print shall serve as a negative control.
- 14.8.7.3 An analyst shall not proceed with the processing of the evidence until control tests bearing positive results (development of a silver-gray print) and negative results (minimal background development) have been carried out and documented in the laboratory case notes and.

14.8.8 SAFETY:

- 14.8.8.1 Physical developer should only be used in a fume hood or well-ventilated area, as it is irritating to the respiratory tract. Standard laboratory protocol is followed for chemical handling.

14.8.9 REFERENCES:

Manual of Fingerprint Development Techniques, British Home Office, (1999), Chapter 4.

Advances in Fingerprint Technology, Henry C. Lee, R.E. Gaensslen, (1994), pages 79, 80, 81, 95, 112.

Technical Note #1-2730, Lightning Powder Co., (113133).

## 14.9 RAM

14.9.1 BACKGROUND:

RAM (Rhodamine, Ardrox, and MBD (7-(P-Methoxybenzlamino-4-Nitrobenz-2-Oxa-1, 3-Diazole) does not actually develop the latent print. The ridge detail must have been previously developed through the use of CAE.

14.9.2 SCOPE:

14.9.2.1 RAM is a dye-stain used to aid in the visualization of CAE developed latents on non-porous substrates.

14.9.2.2 RAM should be used after CAE and prior to powdering.

14.9.2.3 Surfaces that need other forensic examinations such as body fluid or trace examinations should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

#### 14.9.3 EQUIPMENT AND MATERIALS:

Balance

Spatula

Beaker

Spray or rinse bottles

Glass tray

Alternate light source/filtered goggles

Rhodamine 6G (dye content 99%)

MBD

Ardrox P133D

Methanol

Isopropanol

Acetonitrile

Petroleum ether

Acetone

#### 14.9.4 REAGENTS

Rhodamine 6G

Methanol

MBD

Acetone

Ardrox P133D

14.9.4.1 Mixing Procedure: The two stock solutions must be mixed prior to formulating the RAM dye.

##### 14.9.4.1.1 Stock Solution 1 (Rhodamine 6G)

Rhodamine 6G -1 g

Methanol - 1000 mL

Combine the ingredients and place on a stirring device until all the rhodamine 6G is thoroughly dissolved.

##### 14.9.4.1.2 Stock Solution 2 (MBD)

MBD- 1 g

Acetone- 1000 mL

Combine the ingredients and place on a stirring device until all the MBD is thoroughly dissolved.

##### 14.9.4.1.3 Ardrox P133D

Ardrox is used undiluted directly from the container.

##### 14.9.4.1.4 RAM Working Solution

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 84 of 119

Stock Solution 1- 3 mL  
Ardrox P133D- 2 mL  
Stock Solution 2- 7 mL  
Methanol - 20 mL  
Isopropanol - 10 mL  
Acetonitrile - 8 mL  
Petroleum ether - 950 mL

Combine the ingredients in the order listed. Do not place on a magnetic stirrer.

#### 14.9.5 PROCEDURE:

- 14.9.5.1 After an item has been processed with cyanoacrylate CAE, RAM can be applied.
- 14.9.5.2 Suspend the item to be processed over a glass collection tray.
- 14.9.5.3 Irrigate the working solution over the item. Allow the item to dry completely.
- 14.9.5.4 View the item through an orange filter using an alternate light source set in the 450 - 525 nm range.
- 14.9.5.5 Evaluate latent prints for comparable ridge detail. Prints deemed to be of value are marked and photographed.
- 14.9.5.6 Photography will require the aid of an orange filter on the camera and the use of an alternate light source.

#### 14.9.6 ADDITIONAL INFORMATION:

- 14.9.6.1 Stock solutions should be stored in dark bottles- shelf life is indefinite. The RAM working solution is stable for approximately 30 days. After 30 days it should be checked for separation. If the solution has separated, shake the container vigorously and the solution will usually return to suspension. If this does not occur, discard the solution.
- 14.9.6.2 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

#### 14.9.7 CONTROL TESTS:

- 14.9.7.1 Testing of RAM is performed each day prior to use.
- 14.9.7.2 This test involves placing a drop of the RAM working solution on to a surface. The area surrounding the intentionally deposited working solution shall serve as a negative control.
- 14.9.7.3 The test is illuminated with an alternate light source as outlined in 14.9.5.4.
- 14.9.7.4 An analyst shall not proceed with the processing of the evidence until control tests bearing positive results (fluorescence) and negative results (lack of fluorescence) have been carried out and documented in the laboratory case notes and on the control tests work sheet.

#### 14.9.8 SAFETY:

- 14.9.8.1 Eye protection, a lab coat and rubber gloves should be worn. All mixing and application of chemicals should be done inside a ventilated laboratory fume hood. Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.
- 14.9.8.2 Rhodamine 6G, Ardrox P133D, and MBD are classified as suspected animal carcinogens, but sufficient evidence of human carcinogenicity has not been established. RAM is thought to be relatively safe when exposure is at low levels. It should never be inhaled or allowed to get into the eyes or mouth, as it is an irritant. If this should occur, the eyes or mouth should be flushed with a generous amount of water.
- 14.9.8.3 Methanol, isopropanol, and petroleum ether are highly *flammable*. All three chemicals need to be handled carefully with gloves during mixing and use of the stain. Methanol and isopropanol are toxic in quantities as small as 30 ml and should not be allowed to come in contact with the skin, eyes, or mouth. It is possible for methanol and isopropanol to be absorbed through the skin. If methanol, isopropanol, or petroleum ether comes into contact with the eyes or mouth, the area should be flushed with generous amounts of water. Inhalation of vapors from either chemical should be kept at a minimum and the stain should be used in a fume hood or well-ventilated area.
- 14.9.8.4 Acetonitrile may be fatal if swallowed, inhaled or absorbed through skin; affects cardiovascular system, central nervous system, liver and kidneys; may cause irritation to skin, eyes, and respiratory tract; flammable liquid and vapor.

### 14.10. RHODAMINE 6G

#### 14.10.1 BACKGROUND:

Rhodamine 6G does not actually develop the latent print. The ridge detail must have been previously developed through the use of CAE.

#### 14.10.2 SCOPE:

- 14.10.2.1 Rhodamine 6G is a dye-stain used to aid in the visualization of CAE developed latents on non-porous substrates.
- 14.10.2.2 Rhodamine 6G should be used after CAE and prior to powdering.
- 14.10.2.3 Surfaces that need other forensic examinations such as body fluid or trace examinations should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

#### 14.10.3 EQUIPMENT AND MATERIALS:

Balance  
Spatula  
Beaker  
Spray or rinse bottles  
Glass tray  
Alternate light source/filtered goggles

#### 14.10.4 REAGENTS:

Rhodamine 6G powder  
Methanol or distilled water  
Rhodamine 6G working solution:

1. Measure out approximately 0.1 gram Rhodamine 6G (about the size of a BB) and add to the storage bottle.
2. Add approximately one liter of methanol OR distilled water depending on the carrier you wish to use.
3. Seal the bottle and agitate gently to mix.
4. Label the bottle with the type of carrier used (distilled water or methanol).

#### 14.10.5 PROCEDURE:

14.10.5.1 Suspend the item to be processed over a glass collection tray.

14.10.5.2 Irrigate the working solution over the item.

14.10.5.3 Rinse with an appropriate solution (methanol or water dependent on the working solution).

14.10.5.4 Allow the item to dry completely.

14.10.5.5 View the item through an orange filter using an alternate light source set in the 450 - 525 nm range. Visualization of developed ridge detail is dependent upon the condition of the item and background interference.

14.10.5.6 Evaluate latent prints for comparable ridge detail.

14.10.5.7 Prints deemed to be of value are marked and photographed. Photography will require the aid of an orange filter on the camera and the use of an ALS.

#### 14.10.6 ADDITIONAL INFORMATION:

14.10.6.1 The use of distilled water in lieu of methanol is useful when methanol may damage the item being processed, as may be the case with some lacquers, plastics, or tapes. The methanol formulation should be utilized in a fume hood or well ventilated area.

14.10.6.2 If there is concern over background staining, test a small area prior to processing the entire item.

- 14.10.6.3 The amount of the dye-stain used is left to the analyst's discretion.
- 14.10.6.4 The pre-mixed Rhodamine 6G and the working solution have an indefinite shelf life when stored at room temperature.
- 14.10.6.5 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

14.10.7 CONTROL TESTS:

- 14.10.7.1 Testing of Rhodamine 6G is performed each day prior to use.
- 14.10.7.2 This test involves placing a drop of the Rhodamine 6G working solution on to a surface. The area surrounding the intentionally deposited working solution shall serve as a negative control.
- 14.10.7.3 The test is illuminated with an alternate light source as outlined in 14.14.5.5.
- 14.10.7.4 An analyst shall not proceed with the processing of the evidence until control tests bearing positive results (fluorescence) and negative results (lack of fluorescence) have been carried out and documented in the laboratory case notes and on the control tests work sheet.

14.10.8 SAFETY:

- 14.10.8.1 Rhodamine 6G is classified as a suspected animal carcinogen, but sufficient evidence of human carcinogenicity has not been established. Rhodamine 6G is thought to be relatively safe when exposure is at low levels. It should never be inhaled or allowed to get into the eyes or mouth, as it is an irritant. If this should occur, the eyes or mouth should be flushed with a generous amount of water and a doctor may be consulted.
- 14.10.8.2 Methanol is highly *flammable*. It needs to be handled carefully with gloves during mixing and use of the stain. Methanol is toxic in quantities as small as 30 ml and should not be allowed to come in contact with the skin, eyes, or mouth. It is possible for methanol to be absorbed through the skin. If methanol comes into contact with the eyes or mouth, the area should be flushed with generous amounts of water and a doctor may be consulted. Inhalation of methanol vapors should be kept at a minimum and the stain should be used in a well-ventilated area.

14.10.9 REFERENCES:

An Introduction to Lasers, Forensic Lights and Fluorescent Fingerprint Detection Techniques, E. Roland Menzel, (1991), pages 42-44.

Manual of Fingerprint Development Techniques, British Home Office, (1998), chapter 4



Chemical Formulas and Processing Guide for Developing Latent Prints,  
U.S. Department of Justice, F.B.I. Laboratory Division, (1994), pages  
55-56.

Technical Notes #1-0041, Lightning Powder Co. Inc., pages 1-4.

## 14.11 SUDAN BLACK

### 14.11.1 BACKGROUND:

Sudan black B is a dye that stains fatty components to produce a blue-black image. It is considered to be a low-sensitivity method and contaminants such as grease are required as a target to which the reagent can bind.

### 14.11.2 SCOPE:

14.11.2.1 Sudan black is a dye-stain method used to develop friction ridge detail on non-porous waxy substrates and surfaces contaminated with grease, dried beverages, and foodstuffs. Sudan black will also enhance CAE developed fingerprints.

14.11.2.2 Sudan black is not suitable for use on porous surfaces or dark colored items.

14.11.2.3 Surfaces that need other forensic examinations such as biology or trace should be carefully evaluated prior to processing to determine if this procedure will have an impact on subsequent examinations.

### 14.11.3 EQUIPMENT AND MATERIALS:

Beaker  
Glass tray  
Graduated cylinder  
Balance  
Spatula  
Stirring rod  
Glass bottle

### 14.11.4 REAGENTS:

Sudan Black B powder  
Methanol  
Distilled water

#### Sudan Black B Working Solution:

1. Place 15g of sudan black powder into a 2-liter glass beaker.
2. Add 1-liter of methanol and stir with a plastic stirring rod.
3. Add 500 ml of distilled water to the beaker and stir with the stirring rod. Some of the sudan black will not dissolve, but will remain as

particulate matter. Pour the solution, including any solid matter, into a clean glass bottle with a tight-fitting screw top.

#### 14.11.5 PROCEDURE:

- 14.11.5.1 Shake the container of sudan black working solution and pour a sufficient amount into a tray large enough to hold the item of evidence.
- 14.11.5.2 Soak the item for 2-3 minutes. For large items, irrigate the solution over the surface, catching the run off in a tray for reuse on the item.
- 14.11.5.3 Rinse the article in cool running tap water.
- 14.11.5.4 Allow the item to dry at room temperature.
- 14.11.5.5 Evaluate latent prints for comparable ridge detail.
- 14.11.5.6 Reprocessing can sometimes enhance faintly developed latent prints.
- 14.11.5.7 Prints deemed to be of value are marked and photographed. While it is possible to lift the prints with tape, the tape frequently does not lift the print sufficiently and prints that have been lifted have been known to bleed causing the image to blur. Therefore, it is strongly recommended that prints be photographed prior to attempting to lift.

#### 14.11.6 ADDITIONAL INFORMATION:

- 14.11.6.1 The pre-mixed sudan black and the working solution have an indefinite shelf life at room temperature.
- 14.11.6.2 Excess reagent shall be collected and placed in the hazardous waste container located in the fume hood.

#### 14.11.7 CONTROL TESTS:

- 14.11.7.1 Testing of sudan black is performed each day prior to use.
- 14.11.7.2 This test involves the making of a quality (oil based) latent print on a test surface similar to the evidence being examined and following the processing procedure. The area surrounding the intentionally deposited print shall serve as a negative control.
- 14.11.7.3 An analyst cannot proceed with the processing of the evidence until control tests bearing positive results (development of a blue-black print) and negative results (minimal background development) have been carried out and documented in the laboratory case notes.

#### 14.11.8 SAFETY:

- 14.11.8.1 The sudan black working solution contains methanol. Methanol is toxic in quantities as small as 30 ml and should not be allowed to come in contact with the skin, eyes, or mouth. It is possible for methanol to be absorbed through the skin. If

methanol comes into contact with the eyes or mouth, the area should be flushed with generous amounts of water and a doctor may be consulted. Inhalation of methanol vapors should be kept at a minimum and the sudan black should be used in a fume hood or well-ventilated area.

14.11.9 REFERENCES:

Manual of Fingerprint Development Techniques, British Home Office, Chapter 4, (1998).

Lightning Powder Technical Note No. 1-0034, "Sudan Black", (May, 1995).

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016

## 15 DIGITAL IMAGING PROCEDURE

### 15.1 BACKGROUND:

Latent print images are frequently captured, processed, and stored using digital devices. The intent of image processing is to allow for higher image clarity and contrast. Image processing may be used to increase the contrast between the print and the substrate, reverse the color of the ridges, etc.

### 15.2 SCOPE:

This sets forth the Latent Print Section's procedures for the capture, storage, processing, and output of latent print digital images.

### 15.3 RESPONSIBILITIES:

#### 15.3.1 Latent Section Supervisor

15.3.1.1 The Latent Section Supervisor shall act as the Digital Imaging System Administrator or appoint a Digital Imaging System Administrator.

15.3.1.2 The Latent Section Supervisor shall oversee and document the training of each new digital imaging system operator. This includes documenting competency testing.

15.3.1.3 The Latent Section Supervisor shall ensure access is limited to authorized users.

15.3.1.4 The Latent Section Supervisor or designee shall act as a liaison with CJIS and digital imaging system technical staff on system maintenance, upgrades, and when technical difficulties arise.

15.3.1.5 The Latent Section Supervisor or designee shall be the only personnel authorized to delete images or cases entered into the digital imaging system.

#### 15.3.2 Digital Imaging System Administrator

15.3.2.1 The Digital Imaging System Administrator shall be responsible for system maintenance to include: deletion of images/cases, archiving, etc.

15.3.2.2 The Digital Imaging System Administrator shall communicate system status to the supervisor and other system users.

#### 15.3.3 Analysts

15.3.3.1 Analysts shall only use processing techniques that are supported by their training and/or experience.

15.3.3.2 Analysts shall maintain system security.

15.3.3.2.1 Network and/or program passwords are not to be distributed to unauthorized users. Operators may change their passwords as needed.

#### 15.4 DIGITAL IMAGE CAPTURE & STORAGE

15.4.1 Analysts shall use one of the following digital image capture devices to acquire images.

15.4.1.1 Flat Bed Scanner

15.4.1.2 Digital Camera

15.4.1.3 Digital Media (e.g. Thumb Drive, CD/DVD, etc.)

15.4.1.4 Tablet

15.4.2 A primary image is the result of the first recording of an image onto media. An original image is an accurate replica (bit-for-bit value) of the primary image.

15.4.3 Digital images to be used for comparison purposes (category 2 images) shall be stored and transmitted without compression or with lossless compression (i.e. capture in a TIF or RAW file format) is recommended.

15.4.3.1 Original close up images captured by latent section analysts should fill the frame and contain a scale in centimeters. The scale should be on the same plane and as close as possible to the impression without obscuring detail.

15.4.4 Friction ridge impressions captured on a flatbed scanner (image sized 1:1) with the intention of being used for comparison purposes shall be captured in color, at a minimum resolution of 1200 ppi. Interpolation from a lower resolution up to 1200 ppi is not permitted.

15.4.4.1 Images captured on a flatbed scanner are at 1:1; therefore, no calibration of these images is needed.

15.4.4.2 Comparison quality images should be captured in color and include a scale in centimeters.

15.4.5 Images captured for documentation purposes only (category 1 images) may be captured at a lower resolution and/or file type to achieve a smaller file size.

15.4.5.1 All images acquired via Tablet fall into this category.

15.4.6 Outside agencies may submit processed film for digital capture or digitally submit latent print images.

15.4.6.1 Images of latent prints should contain a scale.

15.4.6.2 It is preferred that existing images (those submitted by outside agencies) be submitted in a lossless format such as .TIF or RAW and at as high a resolution as possible.

15.4.6.3 Upon receipt of a JPG image, the image shall immediately be converted to TIF and saved. The analyst should also magnify the image to look for "blocking" that may indicate loss of detail due to JPG compression.

15.4.7 Category 2 images shall be acquired through the digital imaging system or directly uploaded from temporary storage into the system.

- 15.4.8 Digital imaging system software shall establish a chain of custody from the time of acquisition into the program.
- 15.4.9 Images shall be designated using a file name structure generated by the digital imaging system software.
- 15.4.10 Category 1 images may be attached to the case file in ILIMS or uploaded to the digital imaging system.

## 15.5 DIGITAL IMAGE PROCESSING

- 15.5.1 Image processing shall only be conducted on working copies of the original image. Working copies used in forensic case examination shall be saved as a separate copy and shall not replace the original image.
  - 15.5.1.1 The only exception to this rule is when adjusting white balance in the camera raw converter.
- 15.5.2 Digital evidentiary images requiring processing shall be processed using Adobe Photoshop/or proprietary digital imaging system software (using a copy of the original image)
- 15.5.3 The following is a list of commonly used, generally accepted processing commands and in no way inclusive. All processing commands employed are left to the discretion of the examiner. Suggested settings/guidelines/notes appear after the command in parenthesis.

Foray Technologies preloaded "Latent Print Actions"

Image – Adjustments – **Black & White** (use to remove two or more color values and/or adjust the color values so that a color channel may be used to suppress the background)

Image – Adjustments – **Brightness/Contrast**

Image – Adjustments – **Color Balance** (use to remove two or more color values and/or adjust the color values so that a color channel may be used to suppress the background)

Image – Adjustments – **Curves** (extraordinary contrast; convert to gray scale prior to; sample lightest possible ridge where ridge are furrows are very similar in tone; avoid flatline of "S" curve)

Image – Adjustments – **Exposure** (balance tonal range)

Image – Adjustments – **Hue/Saturation** (eliminates two or more color values; used in conjunction with Calculations to eliminate background noise)

Image – Adjustments – **Invert**

Image – Adjustments – **Levels** (use to redistribute/balance tonal range; use in conjunction with the Alt key to avoid clipping or adjust midtone value only; useful for one sided histograms)

Image – Adjustments – **Photo Filter** (use to remove two or more color values and/or adjust the color values so that a color channel may be used to suppress the background)

Image – Adjustments – **Shadows & Highlight** (balance tonal range and contrast; radius of <50; optimal is 30-50 pixels)

Image – Adjustments – **Variations** (after adjusting color variations, it may be possible to suppress background noise and patterns using color modes and/or channels, etc.)

Image – **Calculations** (useful for background suppression; set blending value to Color Dodge or Linear Dodge, consider a change opacity)

Image – **Rotate Canvas** (90 degree rotation is acceptable at any stage; increments other than 90 degrees should be the last processing step; suggest utilizing the Rotate View tool in lieu of other increment rotations).

Image – Rotate Canvas – **Flip Canvas Horizontal**

**Color Channels** (RGB, CMYK, or LAB Color; used to remove one color; follow with conversion to gray scale)

Filter – **Camera Raw** (useful for correcting white balance)

Filter – Foray – **Pattern Removal Filter** (use after conversion to gray scale and prior to adjusting tonal range and contrast)

Filter – Noise – **Dust & Scratches** (removes artifacts, i.e. excess powder etc.; radius of 1 pixel per 1000 ppi +1; threshold value between 0-50; useful prior to printing and/or ABIS submission)

Filter - Noise - **Reduce Noise** (removes random artifacts)

Filter - Sharpen - **Sharpen Edges** (sharpens areas where significant color changes occur; less control than Unsharp Mask or Smart Sharpen)

Filter - Sharpen - **Smart Sharpen** (Similar to Unsharp Mask with more control)

Filter – Sharpen – **Unsharp Mask** (sharpens by increasing contrast –lighter pixels get lighter and the darker pixels get darker; amount should not exceed 100%; radius of 1 pixel per 1000 ppi +1 with threshold value set between 0-50; useful prior to printing)

**Burn Tool** – (burn shadows - feathered brush; diameter of 8-10 ridges; exposure between 15-50%; use single clicks)

**Crop Tool** – used to remove a portion of the image that is outside the area of interest.

**Dodge Tool** – (dodge highlights; feathered brush; diameter of 8-10 ridges; exposure between 15-50%; use single clicks)

**Marquee & Lasso Tools** (images with ppi >1000 determine feather by dividing resolution by 100 and multiplying by 5 – this is a recommendation only and may need to be modified based on size of area selected or as dictated by the program; avoid feathering for inversions, areas of high contrast, and straight edges)

**Type Tool** (set anti aliasing to smooth)

15.5.4 Processed images will be designated using a file name structure generated by the digital imaging system software.

15.5.5 Processing history shall be recorded via the digital imaging system software.

15.5.6 All images stored in a secured digital imaging system maintained by ISP Forensic Services shall be referenced in the case record.

## 15.6 DIGITAL IMAGE PRINTING

15.6.1 Images intended for comparison purposes should be printed on a high quality ink jet printer utilizing premium glossy photo paper.

15.6.2 Image calibration shall be checked as needed by comparing the scale in the printed image with a standard metric scale.

## 15.7 DIGITAL IMAGE STORAGE, ARCHIVAL, AND RETRIEVAL

15.7.1 Images, both original and processed, shall be stored on the digital imaging system hard drive backed up to ISP servers.

15.7.2 A backup shall be completed by the ISP CJIS staff on a routine server backup schedule.

15.7.3 Cases may be deleted from the server once the statute of limitations has been exceeded.

15.7.4 Cases with no statute of limitation shall be stored on the digital imaging server hard drive indefinitely.

## 15.8 QUALITY CONTROL:

15.8.1 Performance checks shall be conducted on equipment as needed.

15.8.2 When a problem is noted with a particular piece of equipment, software program, etc., the Digital Imaging System Administrator and/or Latent Section Supervisor shall be notified.

15.8.3 If it is determined that the situation is persistent or cannot be easily rectified, an entry shall be made on the "Instrument Maintenance Log". The log shall detail the date, the person making the entry, the piece of equipment/software involved, and relevant details of the situation.

15.8.4 Affected equipment/software shall be taken off line and all users notified.

15.8.5 If necessary, technical support shall be sought and/or the equipment repaired before being put back into operation.

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 96 of 119



15.8.6 Actions taken to repair or correct the problem shall be documented on the "Instrument Maintenance Log."

15.9 TRAINING

15.9.1 Analysts utilizing imaging technologies shall be trained and tested for competency in the standard operating procedures and the operation of the relevant imaging technologies.

15.9.2 Formal training may be modified at the discretion of the Latent Section Supervisor dependent upon previous training and/or experience.

15.9.3 Continuing education may be provided as courses become available.

15.9.4 Competency testing shall be repeated when significant changes in hardware or software are made (e.g. manufacturer/vendor changes).

15.10 REFERENCES:

SWGIT Guidelines Section 8 "General Guidelines for Capturing Latent Impressions Using a Digital Camera", Version 1.3

International Association for Identification "Resolution 97-9."

Digital Workplace Quick Reference Guide

Scientific Working Group on Imaging Technologies (SWGIT), "Guidelines for the Use of Digital Image Processing," Version 2.1.

SWGIT Guidelines, Section 11, "Best Practices for Documenting Image Enhancement", version

Scientific Working Group on Imaging Technologies (SWGIT), Section 6 "Guidelines and Recommendations for Training in Imaging Technologies in the Criminal Justice System," Version 1.3-

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy 9/16/2016  
OBSOLETE DOCUMENT

## 16 FRICTION RIDGE EXAMINATION METHODOLOGY

### 16.1 BACKGROUND:

- 16.1.1 Friction ridges are formed on the palmar portion of the hands and the plantar portion of the feet during fetal development.
- 16.1.2 The friction ridge arrangement is permanent throughout the life of the individual, barring trauma or disease.
- 16.1.3 Friction ridge skin is unique. No two areas of friction skin have ever been found to be duplicated between two individuals or within the same person.
- 16.1.4 An impression representative of the unique details of friction ridge skin may be transferred upon contact with a surface.
- 16.1.5 An impression containing a sufficient quantity and quality of detail may be identified to or excluded from a particular source.
- 16.1.6 No scientific basis exists for requiring a pre-determined minimum number of friction ridge characteristics to be present in two impressions in order to establish a positive identification.
- 16.1.7 Identification/Exclusion is supported by the theories of biological uniqueness and permanence, probability modeling, and empirical data gained through more than one hundred years of operational experience.

### 16.2 SCOPE:

Analysts shall apply the concepts of Analysis, Comparison, Evaluation, and Verification, herein referred to as ACE-V methodology, to all friction ridge impressions preserved by the Latent Section or submitted by our customer agencies. The ACE-V methodology utilizes a qualitative and quantitative assessment of Level 1, Level 2, and Level 3 details.

### 16.3 EQUIPMENT AND MATERIALS

Magnifiers  
Pointers  
Digital imaging system

### 16.4 PROCEDURE:

16.4.1 ANALYSIS is the assessment of a friction ridge impression to determine suitability for comparison.

- 16.4.1.1 The value of friction ridge impressions is assessed according to the Quality (clarity of observed features) and Quantity (amount of features and area) of features, the specificity of features and the relationships they possess. Quality and Quantity of detail may be influenced by the anatomical source (finger, palm, etc.), condition of the friction ridge skin, type of matrix, deposition factors, substrate considerations, environmental factors, development mediums, and preservation methods.

16.4.1.1.1 Level One Detail consists of overall ridge flow and pattern configuration. Level one detail may include information enabling orientation and can be used to determine anatomical source (i.e., finger, palm, foot, etc.). Anatomical information may be used to prioritize the potential corresponding areas and limit unnecessary comparisons. Certain orientation indicators such as recurves, deltas, creases, and scars may provide specific guidance on where to begin the comparison. Level one detail also includes general morphology (e.g. presence of incipient ridges, overall size). Level one detail cannot be used alone to individualize but may be used to exclude.

16.4.1.1.2 Level Two Detail consists of the individual ridge path, presence or absence of ridge path deviation (ending ridge, bifurcation and dot or continuous ridge), and ridge path morphology (e.g., size and shape). Level two detail is used in conjunction with level one detail to individualize or exclude.

16.4.1.1.3 Level Three Detail is confined to small shapes on individual ridges, relative pore positions, and other specific skin morphology (e.g., secondary creases, ridge breaks, etc.). Level three detail is used in conjunction with level one and two detail to individualize or exclude.

16.4.1.1.4 Other features associated with friction ridge skin (e.g., creases, scars, warts, paper cuts, blisters) may also be considered. These features may be permanent or temporary and exist as level one, two, or three detail. These other features may be used in conjunction with friction ridge detail to individualize or exclude.

16.4.1.2 Minimum quality assurance measures are associated with each level of complexity according to the following:

16.4.1.2.1 Non-Complex Prints - Limited documentation of the relevant features used as a basis for a conclusion; standard verification will be completed.

16.4.1.2.2 Complex Prints - Extensive documentation of the relevant features (i.e. charts or diagrams) used as a basis for a conclusion; should consider the possibility of an enhanced verification and review procedure (e.g., a blind verification, multiple verifiers).

16.4.1.2.3 A non-complex impression may be classified as complex if modifying factors are present such as low specificity of features, significant distortion (e.g.,

multiple tap, superimposed impression, extreme pressure leading to tonal reversal, and slippage), high tolerances, or the original conclusion is contested during verification.

16.4.1.2.4 An impression categorized initially as complex may be classified as non-complex if modifying factors are present such as high specificity of features, presence of creases, scars, and open fields.

16.4.1.2.5 Justification for reassignment of complexity shall be documented.

16.4.1.3 Impressions deemed "of value" contain sufficient quantity and quality of ridge detail to warrant a comparison in the opinion of the analyst. The determination of sufficiency is based on the assessment of the discriminating strengths of the features and their arrangements. Impressions deemed "of value" proceed to the comparison step if there are known exemplars with which to compare and/or to be searched through ABIS or when there are no known exemplars with which to compare.

16.4.1.4 Impressions that do not contain sufficient detail to warrant a comparison in the opinion of the analyst are deemed to have "insufficient ridge detail" (IRD). This conclusion is noted as such in the case documentation.

16.4.1.5 Analysis of the unknown print also includes the selection of a suitable target area (core, delta, etc.) for use during comparison.

16.4.1.6 Analysis occurs independently of the Comparison, Evaluation and Verification steps of ACE-V.

16.4.1.7 An arc over the top of a print represents the anatomical source (i.e. finger) and anatomical orientation, unless otherwise noted.

16.4.1.8 A bracket symbol documents the anatomical source (i.e. palm, footprint), if the orientation is known it shall be indicated with a directional arrow.

16.4.1.9 The presence of friction ridge impressions assessed but not designated for comparison shall be documented. Documentation shall be accomplished by making a "no value" notation (e.g. "NV") in the Latent Analysis Matrix of ILIMS that "no value" impressions are present on a lift or photograph.

16.4.1.10 Impressions deemed of value for exclusion only- consist of impressions that contain a portion of a print that is distinguishable (e.g. complete pattern, very unique ridge arrangement, or permanent scar); however do not display sufficient characteristics to effect an identification.

16.4.1.11 The receipt of latent lift cards or photos said to contain latent prints, which upon analysis show "no ridge detail present" may be noted as "NDP."

16.4.2 COMPARISON is the side-by-side, back and forth, observation of friction ridge detail to determine whether the detail in two impressions is in agreement or disagreement based upon features, sequences, and spatial relationships within the tolerance of clarity and distortion. Comparison begins with the determination of dissimilarity or similarity between two impressions at Level 1.

If the analysis phase provides indicators as to the probable anatomical area, a side by side comparison with the appropriate area of the known prints is conducted. In the absence of indicators, all areas of available known impressions must be compared.

16.4.2.1 If similarity is determined within tolerance at Level 1 a target group is selected from the features observed during the analysis phase and is then searched within the corresponding area of the other impression. Additional arrangements of features are compared between impressions in a cyclical process to evaluate disagreement or agreement between the impressions. If the initial target group is not found, alternative target groups may be selected and compared.

16.4.2.2 Comparison is based on similarity, sequence, and spatial relationship.

16.4.2.3 Comparison is carried out in an objective manner beginning with the unknown (or impression of poorest quality) and comparing to the known (or impression of better quality).

16.4.2.4 Fingerprint and palm print records may be down loaded or printed from the Integra-ID Integrated Archive. Requests for original Fingerprint cards held by the Idaho State Police Bureau of Criminal Identification (BCI) and/or ISP Forensics shall be checked out and tracked as appropriate. Fingerprint cards may also be downloaded from the FBI database from ULW.

16.4.2.4.1 The analyst shall make copies of the card(s) and/or scan the original card(s) into the digital imaging system. These copies/digital images shall be used for comparison purposes and the original cards returned to BCI.

16.4.2.5 The current national resolution standard for the transmission of 10-print images is approximately 500 ppi.

16.4.2.5.1 The following exemplars shall be considered to meet or exceed this standard and may be used for comparison purposes: original card, high quality photocopies and/or ABIS archive printouts traceable to a single source, copies obtained from the FBI, and digital images of original exemplars.

16.4.2.5.2 Examples of images not meeting these standards are 1:1 faxed images, low quality PDF's or

photocopies. These lower resolution images may at times be used for exclusion based on level 1 detail depending on the clarity of the image.

16.4.3 EVALUATION is the formulation of a conclusion based upon analysis and comparison of friction ridge impressions. Conclusions that may be reached are Identification, Exclusion, or Inconclusive.

16.4.3.1 Identification is the decision by the examiner that there are sufficient features in agreement to conclude that two areas of friction ridge impressions originated from the same source. Identification of an impression to one source is the decision that the likelihood that the impression was made by another (different) source is so remote that it is considered a practical impossibility.

16.4.3.1.1 Identification shall be determined by a qualified analyst, applied to a common area in both impressions, based on quantity and quality of detail, contain no unexplainable discrepancies, and shall be reproducible.

16.4.3.1.2 No two prints will ever be exactly the same in *all* respects. Explainable differences are features that differ between a known and unknown print but can be explained as a result of distortion, slippage, twisting, printing defects, overlapping prints, etc.

16.4.3.2 Exclusion is the decision by a qualified analyst that there are sufficient features in disagreement to conclude that two areas of friction ridge impressions did not originate from the same source.

16.4.3.2.1 Exclusion of a subject can only be reached if all relevant comparable anatomical areas are represented and legible in the known exemplars. Conclusion should be that the subject is excluded from having made an impression based on the available exemplars. Exclusions shall refer to the available exemplars unless otherwise stated in the case notes.

16.4.3.2.2 Exclusions shall be determined by a qualified analyst, applied to all reasonable comparable anatomical areas, be based on quantity and quality of the friction ridge detail, and be reproducible.

16.4.3.3 Inconclusive findings may result from the absence of sufficient friction ridge details (lack of quantity or clarity in the questioned impression) to effect a conclusion of identification or exclusion (e.g. corresponding features are observed but not sufficient to individualize). Likewise, dissimilar features may be observed but not be sufficient to exclude (e.g.

indecipherable distortion). Inconclusive findings may also be attributed to the absence of complete and legible known prints (e.g. poor quality fingerprints or a lack of comparable areas).

16.4.3.3.1 Inconclusive conclusions shall not be construed as a statement of possible or probable identification as those conclusions are outside the acceptable limits of the science.

16.4.3.3.2 Inconclusive results shall be determined by a qualified analyst, be based on quantity and quality of the friction ridge detail of the unknown and/or available known exemplars, contain insufficient agreement or disagreement of the friction ridge details, and be reproducible.

16.4.4 VERIFICATION is the independent confirmation of ACE methodology by another qualified analyst to either support or refute the conclusions of the original examiner.

16.4.4.1 A qualified analyst shall verify all latent print comparisons and/or identifications.

16.4.4.2 Analysts shall not verify any conclusions with which they are not comfortable. Comfort level is a function of training and experience.

16.4.4.3 Analysts are encouraged to work out differing conclusions through collaboration. If the differing conclusion(s) cannot be resolved, the ISP Quality Manual Section 15.13.4.3 "conflict resolution" policy will be followed.

16.4.4.4 Analysts do not need to conduct the verification analysis on non-hit latent prints generated by the ABIS computer. If a potential hit is generated, the ACE-V methodology will be followed.

16.4.5 BLIND VERIFICATION is an independent examination of one or more friction ridge impressions at any stage of the ACE process by another competent examiner who is provided with no or limited contextual information, and has no expectation or knowledge of the determinations or conclusions of the original examiner.

16.4.5.1 Blind verification may be used in situations where a single identification and/or single exclusions exist in casework.

16.4.5.2 Blind verification may be used in casework with complex identifications or exclusions (e.g. high distortion, background interference, etc).

16.4.6 OUTSIDE AGENCY VERIFICATION is the examination of friction ridge detail previously examined by an examiner not associated with Idaho State Police Forensic Services.

16.4.6.1 ISP Latent Section will conduct outside agency verifications as if they are a new case submitted for examination.

16.4.6.2 All procedures and guidelines shall be followed when conducting outside agency verifications.

16.4.7 REFERENCES:

The Scientific Working Group on Friction Ridge Analysis, Study and Technology (SWGFAST) - *SWGFAST documents are officially published in the Journal of Forensic Identification*

Fingerprint Whorld, Vol. 26, No. 101, July 2000, "Scientific Comparison and Identification of Fingerprint Evidence", pages 135-106. *Pat A. Wertheim.*

Journal of Forensic Identification, Vol. 41, No. 1, Jan/Mar 113131, "Ridgeology," pages 16-64. *Davis R. Ashbaugh.*

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016



## 17 ABIS

- 17.1 BACKGROUND: ABIS (automated biometric identification system) is a system that includes a database of ten-print fingerprint cards, latent prints, and palm prints. ABIS also includes software that is utilized to search the database. The Idaho State Police is a member of the Western Identification Network (WIN). WIN is a consortium of several western states, referred to as central sites that share their ABIS databases. ISP contracts with WIN to maintain our database and ABIS software. WIN provides all necessary computers, scanners, printers, and software need to conduct ABIS searches. WIN also provides ISP access to the databases of central site members, other state and local agencies, and the FBI. The intention of these procedures is to provide analysts with searching parameters for latent inquiries of the ABIS databases.
- 17.2 TECHNICAL CASE REQUIREMENTS: All latent print cases cannot be ABIS searched. In order to be considered for ABIS searching, the case must contain at least one latent print impression that meets a combination of the following technical requirements.
- 17.2.1 ABIS searches should only be undertaken once all latents have been excluded to the available known exemplars for possible victims, suspects, and/or named subjects, whenever possible.
- 17.2.2 Finger: Latent print impressions from the first joint of the finger can be considered for an ABIS search.
- 17.2.3 Palm: Latent print impressions from the palmar area of the hand can be considered for an ABIS search. This includes the writers palm, thenar, hypothenar, and interdigital, as well as second and third finger joint areas of the palm.
- 17.2.4 Minutiae Number: Routinely, only latent prints containing at least 10 (ten) minutiae located in the above described areas should be considered for ABIS processing. Clarity of the overall print/minutia is also taken into consideration when determining ABIS suitability.
- 17.2.5 Core/Axis: It is not necessary to have the core area visible in the latent impression; however it is necessary to be able to place an approximate core and axis when searching finger impressions.
- 17.2.6 An analyst may use his/her discretion when evaluating the overall suitability of the latent print for ABIS searching
- 17.2.7 Latent prints can be acquired into the ABIS computer by means of direct scans or electronic image file transfer. As technology advances, additional secured image file transfers are acceptable.
- 17.3 DATABASES: Analysts may search the databases of WIN and NGI. Analysts should be guided by their experience, knowledge of the ABIS system's capabilities, laboratory workload and common sense when choosing which databases to search.
- 17.4 DATABASE SELECTION: The following criteria categorize ABIS search parameters by crime type and severity. If the analyst cannot determine the

severity either by the crime associated with the case, the investigative report, or by timely conversation with the investigator, then the lowest search parameters should be used.

17.4.1 Analysts may limit any of the searches based on the circumstances of the case.

17.4.2 Latent Section Supervisor may, as the circumstances of a case dictate, modify these search criteria.

17.4.3 Cases with latents meeting the Technical Case Requirements should be searched using the Idaho and WIN database.

17.4.4 NGI SEARCHES: NGI searches should be conducted on all crimes against person's cases if possible. NGI searches may also be conducted on property cases when warranted (i.e. requested by the agency or high dollar amount). NGI searches both the criminal and civil files in the same search. Candidates may return with either an FBI# or UCN (Universal Control number).

## 17.5 ABIS SEARCHING PROCEDURE:

17.5.1 Generally, the sequence for searching latent prints in ABIS will be: ABIS Case Entry Information entered into IBW will have the following information:

17.5.2. The case number shall be as follows: IDFS followed by a CL, ML, or PL to denote regional lab, the last two digits of the case year, followed by the last four digits of the laboratory case number, i.e. IDFSML151500 translates to laboratory case number M2015-1500.

17.5.2.1 Historical numbering for ISP Forensics was as follows: ID 04 followed by the case number followed by a C, M, or P to denote regional lab, and then the latent number (e.g.ID0420101500M1).

17.5.2.2 Historical numbering for BCI entry was as follows: ID 01 followed by the four digit year followed by the four digit BCI case number, followed by the latent number. A dash may or may not precede the latent number. (e.g.ID01201015001).

17.5.3 Date of crime

17.5.4 Crime code (e.g. 0001 through 0014)

17.5.5 The entry of case information is followed by the acquisition of "New Evidence" items from which a "New Latent" may be acquired (latent prints can be searched from hard copies or electronic copies.

17.5.5.1 To maintain the highest possible image quality for ABIS submission, do not print the ABIS processed image and then scan the printed image. The electronic file will produce a clearer image, making minutiae extraction easier and more accurate).

17.5.5.2 Copies of latent prints to be searched are not considered to be evidence.

17.5.6 After acquisition, latents may be enhanced, edited, and submitted for search. It is suggested that searches proceed as follows:

- 17.5.6.1 LI (Latent Inquiry) or LIP (Latent Inquiry Palm)- search regions set to “Include Idaho”
- 17.5.6.2 LATENT\_COMBO or LATENT\_PALM\_COMBO search regions set to “Exclude Idaho” to search the remaining WIN database and register the print should no HIT be obtained.
- 17.5.6.3 LR (Latent Registration) may also be performed in lieu of a COMBO
- 17.5.6.4 REMOTE\_LI for NGI search, if applicable. Prints submitted to NGI may be “tagged” and will result in temporary retention.
- 17.5.6.5 At times it may be beneficial to conduct additional database searches using modified search parameters e.g. (include incipient ridges, large ridges, wide ridges, search multiple cores and axis, and/or search possible reference pattern types).
- 17.5.7 The Number of Candidate Images is set at a default of 30 for WIN/NEC and 20 for NGI. If the analyst intends to perform a Latent Candidate Merge (see 17.9) then the Candidate List may contain a maximum of 255 candidates.
- 17.5.8 Qualified ABIS trained Forensic Scientists may search latent prints generated by/for other analysts. Forensic Scientists shall not perform the technical review of an ABIS search they performed.
- 17.8 SEARCHING MULTIPLE LATENT PRINTS FROM A CASE: For simultaneous impressions, the analyst will search all suitable impressions in ABIS unless a search of the first simultaneous impression results in an identification.
- 17.8.1 If a case consists of multiple latent prints made by the same finger, it is only necessary to search one latent impression unless different areas of that finger are present in different impressions.
- 17.9 CANDIDATE LIST SID NUMBER MERGE (LC Merge function): Cases searched in ABIS containing two or more latent prints may have the LC Merge function performed on them. Merge Latent Candidate scans each latent print candidate list selected and compares each list to determine if the same SID number appears on two or more candidate lists. If the same SID number appears on two or more candidate lists, ABIS will group the responses by key number and sort by score.
- 17.10 LATENT PRINT TO LATENT PRINT SEARCHES - (LLI). These are the searches of latent prints against the previously searched latent prints on file in the unsolved (unidentified) latent print database and are not performed on a routine basis
- 17.11 ABIS PRIORITY SEARCHES: different databases require different searching

priorities.

17.11.1 Idaho Only/WIN searches utilizing the standard algorithm will be conducted at a priority 6 (normal) search.

17.11.1.1 Priority 1 searches may be performed for rush homicide cases and cases where/there is an urgent need to notify the submitting agency of the results of the ABIS search. Each WIN-OPS representative may elect to modify a search to a Priority 1 for high profile crimes within their state without prior notification to WIN. In cases where the WIN-OPS representative carries out the priority change, the following information is to be forwarded to the WIN office:

- 1.Date of priority change
- 2.Brief narrative of the offense
- 3.Hit/No hit
- 4.If hit, where the hit was effected
- 5.Other interesting facts
- 6.Submit to WIN

#### 17.12 ABIS ONLY CASES

17.12.1 External agencies that employ their own latent print examiners may request and submit latents for ABIS only. Documentation of the request shall be documented in the case file.

17.12.2 In these instances, ISP Forensics will only analyze/consider for ABIS search those latents designated by the agency. Latents not designated by the agency need not be analyzed.

17.12.3 In the event of an ABIS HIT, only the latent that HIT will be fully analyzed, compared, evaluated, verified, and reported. Remaining latents will be returned to the submitting agency to complete the comparisons.

17.12.4 The latent section will provide these agencies with known exemplars of the identified individual(s) to facilitate the remaining comparisons.

17.13 ABIS CASE DOCUMENTATION: Documentation of ABIS searches and results shall be maintained in ILIMS as administrative documentation attached to the "CASE INFO" tab and shall consist of the following:

17.13.1 Candidate List - Every search conducted in ABIS will generate a candidate list of subjects in score order (probability of matching the search print). This candidate list displays a markup of the latent print showing Minutiae, Core/Axis, and Zoning.

17.13.2 In the event of an ABIS HIT, the HIT chart or a split screen image of the search print and candidate print will be preserved as administrative documentation.

17.13.2.1 Split screen images, and any other ABIS generated fingerprint or tracing images, will not be utilized to make a positive identification. Identifications can only be made as a result of comparing the actual latent prints (or photographic or high

Rev. 14

Issued: 1/20/2016

Latent Section AM

Issuing Authority: Quality Manager

Page 108 of 119

resolution copies thereof) and actual known print cards (or photographic or high resolution copies thereof).

- 17.13.3 ABIS HITS will be recorded on the ABIS HIT LOG located near the ABIS terminal.
- 17.13.4 Analysts may, at their discretion, include other ABIS documentation such as screenshots of the edited latent or demographic information pertaining to a HIT.
- 17.13.5 The ABIS module in ILIMS will be completed for each latent searched.
- 17.14 REGISTERED LATENTS: Latent prints that remain unidentified at the conclusion of the ABIS search should be registered in the WIN unidentified latent database. If a registered latent is later identified, it should be deleted from the unidentified latent database. Prints stored the database are not considered to be evidence.
- 17.15 TENPRINT TO LATENT INQUIRY CANDIDATE LISTS (TLI):
- 17.15.1 Analysts are responsible for periodically reviewing their TLI lists for possible candidates.
- 17.15.2 If the TLI candidate list produces a possible candidate, the analyst will research the statute of limitations for the case. If the statute of limitations has not expired, the analyst will request that the agency submit the original latent print(s) for comparison or rely on high quality digital images retained by the latent section to complete the examination. If the statute has expired, the analyst may delete the print from the database.
- 17.15.3 TLI HITS and their resulting actions will be documented on the TLI HIT log located near the ABIS terminal.
- 17.16 DATABASE MAINTENANCE: WIN periodically publishes lists of latent prints currently registered in the ABIS Unsolved Latent Database. These lists are generally published annually. ISP Forensic Services Latent Section is responsible for maintaining latent prints that remain in the unsolved latent prints database.
- 17.16.1 The Latent Section Supervisor shall review the list of registered unsolved latent database searches and remove all latent searches that have exceeded the case statute of limitations.
- 17.16.2 Database maintenance shall be conducted no less than annually.
- 17.17 QUALITY CHECK POLICY: Quality control checks will be conducted each day before the system is used. Controls only need to be run for the type of latents searched that day. For example, if you are only running a palm, there is no need to do the quality control check for fingerprints.
- 17.17.1 Quality check procedure:
1. From the LCMS screen
  2. Enter an ABIS case number

3. Enter an evidence number and import the desired QA print (supplied by WIN and specified for quality checks).
  4. Enter the latent number
  5. Launch LI search with no human intervention on the pre-extracted latent file
  6. Compare the resulting candidate list to ensure results are consistent with the expected results
  7. The position on the candidate list may change over time.
  8. Document the results of the QC check on the ABIS Quality Control Check Log and in the ABIS matrix of ILIMS.
  9. The job may then be killed and purged from the IBW job queue.
- 17.17.2 WIN conducts random calibration checks of the WIN Database throughout the calendar year. WIN notifies the participating agencies of the results.

17.18 TRAINING: All analysts utilizing ABIS shall be trained and tested for competency in the standard operating procedures and the operation of the system.

#### 17.19 LIMITATIONS

- 17.19.1 Matching accuracy depends on the skill of the examiner in marking minutia, calculating ridge counts, core and axis placement, proper zoning, and pattern type/finger number selection. It is also highly dependent on the quality of fingerprints located in the search database as well as the quality of the latent prints chosen for submission.
- 17.19.2 Searches are limited to NEC/WIN participants and the NGI database. All other ABIS/AFIS databases/vendors cannot be accessed by this system.
- 17.19.3 When multiple ten-print cards are entered for an individual, ABIS automatically evaluates each print and uses the best available print for comparison (e.g. the right index and right middle finger may come from different cards). ABIS continually updates and a new (better) print may be available after the initial search.
- 17.19.4 The ABIS terminal generates a candidate list and while the program tries to rank candidates, a potential match may be generated from any candidate on the list.
- 17.19.5 The ABIS terminal may create a different candidate list each time a query is performed.

#### 17.20 REFERENCES

- Integra – ID IBW Latent User Guide*
- IBW Latent Quick Reference*
- Integra-ID Archive manual*
- Integra –ID Archive Quick Reference*

*Integrated System Monitoring manual*

*Integra-ID ISM Quick Reference*

*WIN AFIS Latent Fingerprint Best Practices, September 2002*

*WIN-OPS Manual Revision 2008, September 2008*

*WIN-OPS QA Procedure Outline, April 2004*

*NEC Core and Axis User Guide*

Manuals are loaded on the ABIS system and can also be found at <http://secure.winid.org/training.asp>. The state representative will send notification of any updates or deletions on the website.

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OBSOLETE DOCUMENT 9/16/2016

## 18 CASE WORK DOCUMENTATION AND REPORT WRITING

- 18.1 Case work documentation and report writing will be according to ISPFS Quality Manual.
- 18.2 Documentation concerning item packaging and condition of seals will be documented in the Packaging matrix of ILIMS
- 18.3 A brief description of the individual contents of the package should be described in the Item Description matrix of ILIMS. This description will generate into the report. If multiple items are present inside a package then sub items may be used to differentiate items. A more detailed description may be entered into the Latent Print Processing matrix of ILIMS if needed.
- 18.4 Latent print processing is documented in the Latent Print Processing matrix of ILIMS.
- 18.5 Documentation shall be to the extent that another qualified analyst would be able to determine each examination activity conducted, their sequence, results of the activities, and any conclusions reached
- 18.5.1 As each development method is completed, it is documented in sequence and the evidence is visually examined for the presence of comparable ridge detail.
- 18.5.2 When comparable ridge detail is observed, it should be preserved prior to additional processing.
- 18.5.2.1 Comparable ridge detail may be photographed upon initial examination, as additional detail develops, after a specific method, and/or prior to a subsequent method.
- 18.5.2.1.1 Latent print photographs/images and/or case documentation shall include a scale, unique case identifier, date, analyst's initials, impression source (description or source identifier), and significant information about the orientation and/or position of the latent print on the object through description, photography, and/or diagram.
- 18.5.2.2 Prints developed via powder processing may be lifted in lieu of photography.
- 18.5.2.2.1 Latent print lifts shall contain the unique case identifier, date, analyst's initials, should include impression source (description or source identifier), and significant information about the orientation and/or position of the latent print on the object through description and/or diagram.
- 18.5.3 Latent print examination documentation shall include which prints were analyzed, compared, evaluated, and the conclusions reached.



Documentation shall be made in the ILIMS system at or near the time of the examination and may include annotated images, narrative, annotated legible copies, sketches, ABIS documents, electronic records, or any combination of these methods.

18.5.4 Analysis is documented in the Latent Print Analysis matrix of ILIMS.

The extent of documentation is related to the complexity of the examination. The friction ridge impression alone is not sufficient documentation.

18.5.4.1 Each latent impression analyzed shall have an individualizing numeric designation (1.1, 1.2., etc).

18.5.4.2 The comparison value of each impression will be documented. If the examiner changes the “of value” decision, it shall be documented along with the reason for changing the “of value” decision. Any conclusions reached up to the point the examiner changes the “of value” decision shall be documented.

18.5.4.3 Documentation of latent impressions marked of value shall include the following if known; anatomic source of the impression (finger tip, palm, etc.), anatomical orientation, pattern if discernible (loop, whorl, etc.), level of clarity (1, 2, 3) substrate, development medium, and preservation method. It may also include matrix, deposition pressure, lateral movement, rotational movement or other friction ridge skin details, if known.

18.5.4.3.1 If re-analysis of the latent print during the comparison results in new information (e.g. significant change to the orientation, anatomical source or additional ridge detail), supplemental documentation shall be added.

18.5.4.4 Latent impressions on the reverse side of lift cards or on the edge of tape lifts that appear to have been deposited by the individual making the lift (based on anatomical position/orientation) need not be preserved or analyzed, but documentation shall be recorded in case notes.

18.5.4.5 Analysts shall document to whom the latents were compared, and the results of those comparisons. Comparison conclusions are documented in the Comparison Table matrix of ILIMS

18.5.4.5.1 Documentation of identifications shall include an annotation, in proximity to the latent or in the description field of the digital imaging system, that includes the date of the identification, the initials of the analyst, unique identifier(s) of the exemplar(s) or name on exemplar(s) used to reach the conclusion, and the area identified (ex. finger #, palm etc.). The analyst shall also date and initial all exemplars used to effect the identification(s).

18.5.4.5.2 Documentation of an exclusion shall include, at a minimum, which specific impression was excluded, and unique identifier(s) of the exemplar(s) used to reach the conclusion.

18.5.3.5.3 Documentation of inconclusive findings shall include, at a minimum, which specific impression was compared, the specific anatomical source if applicable, unique identifier(s) of the exemplar(s) used to reach the conclusion, and shall include the reason(s) for the inconclusive finding. These reasons should be based on the complete exemplars and not the individual finger impressions on the exemplars (ex. latent lacks sufficient quantity/quality for identification, insufficient friction ridge detail in agreement, exemplars smudged, over-inked/under-inked, incomplete exemplars, no exemplars (palms, tips not recorded, etc.).

18.5.3.5.4 Documentation of "consultations" shall be in the case notes and include: which specific impression(s) was reviewed, the nature and result of the consultation (e.g. reviewed individualization), the identity of the examiner(s), and date of consultation. If examiners have significant interaction on a particular print, the consulted examiner shall not be used as the verifier for that particular print.

18.5.4.6 All latent impressions/lift cards given unique identifiers are verified.

18.5.4.6.1 Verification of both the latent print analysis matrix and results entered into the Comparison Table, if applicable, are documented in the ILIMS Latent Print Analysis matrix in the areas reserved for the verifier.

18.5.4.6.2 Verifications are documented by entry of the verifiers initials, date of the verification, and password into ILIMS.

18.5.4.6.3 Verifiers are encouraged to enter supplementary or differing analysis documentation into the Verifier Notes field in ILIMS.

18.5.4.6.4 The verifying analyst shall date and initial in proximity to the identified impression(s) and on all exemplars used to effect the verification(s) or in the description field of the digital imaging system.

- 18.6 The original or reproduction suitable for comparison of both the compared latent impressions and the known exemplars must be retained as part of the case record.
- 18.6.1 When the laboratory cannot ensure that the original latents or exemplars used and relied upon in the examination will be maintained by the contributing agencies, the laboratory must maintain an image of the actual data.
- 18.6.1.1 Case documentation shall contain replications or electronic scans of all latent lift cards submitted by the customer. All latents deemed of value for comparison shall be preserved in the digital imaging system.
- 18.6.2 Exemplars used for comparison are documented in the Exemplars matrix of ILIMS. Case documentation shall contain replications or electronic scans of all known exemplars used in the comparison. Known exemplars submitted by the customer agency shall be scanned prior to being returned. Scans must be suitable for comparison.
- 18.6.2.1 Exemplars used to effect an identification shall be preserved in the digital imaging system prior to being returned.
- 18.7 The report shall be as clear and concise as possible, convey the analytical findings and conclusions, and will be supported by scientific procedures.
- 18.7.1 Draft reports are automatically generated by ILIMS based on information entered into the case analysis matrices. It is the analyst's responsibility to ensure that all reports are modified to correct singular/plural and number agreement as well as correct ordering of events.
- 18.7.2 The following are some basic report wording guidelines categorized as to type of case and in according to where they would appear in the report. There may be situations that do not fit the examples given and wording will be developed as the need arises. (Blanks and italicized words indicate a choice or insertion should be made).

**PROCESSING ONLY CASE WORDING EXAMPLES:**

**EVIDENCE DESCRIPTION:**

Item (Agency Ex. ) – *this should be a brief description of the evidence received and should delineate any sub item numbers.*

**CONCLUSIONS AND INTERPRETATIONS:**

Item - was processed for latent prints.

Item - no latent prints were observed or developed. - *use for NDP items*

Items - no latent prints containing a sufficient amount of clear ridge detail necessary for comparison purposes were observed or developed. - *use for IRD items*

Item - latent prints were observed or developed. – use for RDP items

Latent print has been forwarded for comparison. Results will follow in a separate report.

**DISPOSITION OF EVIDENCE:**

One latent prints was marked and preserved. Digital images are being maintained by ISP Forensic Services. One latent lift cards was generated and retained in an Impression Evidence Packet (IEP). The IEP will be sent to the submitting agency upon completion of the comparison portion of the examination.

**COMPARISON CASE WORDING EXAMPLES:**

**EVIDENCE DESCRIPTION:**

Item (Agency Ex. ) – this should be a brief description of the evidence received and should delineate any sub item numbers.

OR

Item was previously processed for latent prints by *insert analyst name*: refer to the processing report for details. Latent prints were marked and preserved. Digital images are being retained by ISP Forensic Services.

**CONCLUSIONS AND INTERPRETATIONS:**

Latent *prints/lifts* were examined for comparable ridge detail. Latent *print/lift* \_\_ does not contain a sufficient amount of clear ridge detail necessary comparison. Latent print \_\_ is of value for comparison.

Latent print \_\_ was analyzed and compared to the known exemplars bearing the name \_\_\_\_ .

**COMPARISON RESULTS:**

Latent Print	Name
<i>Unique identifier of latent print</i>	

The identification listed above was effected using the following known exemplars: Name, SID# \_\_\_\_\_, recorded on date by name of official on behalf of the name of agency.

All latent prints of value have been identified. – optional statement use if applicable

No latent prints of sufficient quality for the Automated Biometric Identification System (ABIS) exist in this case. – optional statement use if applicable

No fingerprints/palm prints were found to be on file for *insert name*.

Property of Idaho State Police Forensic Services  
Uncontrolled Internet Copy  
OR SOLELY DOCUMENT 9/16/2016

In order to complete the comparison portion of this examination, it is requested that a quality set of fingerprints (full fingers, sides of fingers, finger tips) and/or palm prints, including sides of palms, be submitted for *insert name*. – *optional statement use if applicable*

OR

In order to complete the comparison portion of this examination, it is requested that a quality set of major case prints (palms, full fingers, sides of fingers, finger tips) be submitted for (name). – *optional statement use if applicable*

If a suspect/an additional suspect is developed by your agency at a later date a fingerprint card or the appropriate suspect information should be submitted for comparison. – *optional statement use if applicable*

### TLI HIT WORDING EXAMPLES

#### CONCLUSIONS AND INTERPRETATIONS:

Latent print was previously entered and searched through the Automated Biometric Identification System (ABIS) where SID # *number*, *name*, was generated as a possible candidate.

Latent print \_\_\_ was analyzed and compared to the known exemplars bearing the name \_\_\_\_.

#### COMPARISON RESULTS:

Latent Print	<i>Name</i>
<i>Unique identifier of latent print</i>	

The identification listed above was effected using the following known exemplars:  
*Name*, SID# *number*, recorded on *date* by *name of official* on behalf of the *name of agency*.

### ABIS ONLY CASE WORDING EXAMPLES:

#### EVIDENCE DESCRIPTION:

Item (Agency Ex. ) – *this should be a brief description of the evidence received and should delineate any sub item numbers*. Per agency request this is an ABIS only case.

#### CONCLUSIONS AND INTERPRETATIONS:

The designated latent print was entered examined for comparable ridge detail and consideration for ABIS.

Latent print is of value for comparison but is not suitable for ABIS inquiry.

OR

Latent print \_\_\_\_\_ is of value for comparison.

Latent print \_\_\_\_\_ was entered and searched through the Automated Biometric Identification System (ABIS) where no likely candidates were generated. – *use for no ABIS HIT*

OR

Latent print \_\_\_\_\_ was entered and searched through the Automated Biometric Identification System (ABIS) where SID# \_\_\_\_\_, *name*, was generated as a possible candidate. – *use for ABIS HIT*

Latent print \_\_\_\_\_ was analyzed and compared to the known exemplars bearing the name \_\_\_\_\_.

**COMPARISON RESULTS:**

Latent Print	Name
<i>Unique identifier of latent print</i>	

The identification listed above was effected using the following known exemplars:  
*Name, SID# number, recorded on date by name of official on behalf of the name of agency.*

Per agency request, only the latent print that generated the ABIS HIT was analyzed and compared. All other comparisons will be completed by the submitting agency.

Latent print is of value for comparison, but is not suitable for ABIS as submitted. Please submit a digital version of this photograph for ABIS consideration - *optional use for poor quality photo printouts*

**DISPOSITION OF EVIDENCE WORDING EXAMPLES**

All items will be returned to the submitting agency.

Latent prints were marked and preserved. Digital images are being maintained by ISP Forensic Services.

\_\_\_\_\_ lift card was generated and retained in an Impression Evidence Packet (IEP). The IEP will be sent to the submitting agency upon completion of the comparison portion of the examination.

Item \_\_\_\_\_ has been retained in the laboratory for \_\_\_\_\_ analysis.

Item \_\_\_\_\_ has been forwarded to the \_\_\_\_\_ laboratory for \_\_\_\_\_ analysis.

All remaining items will be returned to the submitting agency.

- 18.8 The verifying analyst shall perform the technical and administrative review on the case. In the event that the verifying analyst is unavailable, the section supervisor may perform the reviews.

- 18.9 DNA database swab collection kits needing fingerprint comparisons and verifications will be conducted as per ISPFs Latent Section established procedures.
- 18.9.1 DNA database swab collection kits shall be checked out from and tracked by DNA database personnel.
  - 18.9.2 Latent section personnel will store DNA database swab collection kits in a secured location when not actively being worked.
  - 18.9.3 Comparisons may be conducted electronically on screen or using printouts of known exemplars. Exemplars will be generated from established databases.
  - 18.9.4 Verifications will be conducted according to Latent Analytical Method 16.4.4.
  - 18.9.5 DNA database swab collection kits that are not associated with the state identification numbers (SID#) and/or name listed on the sample will be searched through the ABIS database for possible identification. Established ABIS guidelines will be followed.
  - 18.9.6 Non confirmed/identified DNA database kits will be returned to the Biology Section.
  - 18.9.7 Initials and date of analysis will be placed on the DNA database kit. Initials will serve as necessary confirmation documentation. Comparisons are worked outside of ILIMS and as such, no report will be generated.
- 18.10 The latent section shall conduct annual proficiency testing in latent print comparison and latent print processing.
- 18.10.1 Testing shall be in accordance with the ISPFs Quality/Procedure Manual.
  - 18.10.2 Electronic copies and or scans are sufficient documentation of latent prints and exemplars for latent comparison proficiency tests. Images need not be entered into the digital imaging system.
  - 18.10.3 Only case number and initials shall be documented on hard copies of proficiency tests. No annotation of identifications shall be made due to other analysts taking the same test.